

## A comparison of different approaches to automatic control for sewer systems

Kolechkina, Alla; van Nooijen, Ronald

**Publication date** 2019 **Document Version** Final published version Published in **Geophysical Research Abstracts** 

## Citation (APA)

Kolechkina, A., & van Nooijen, R. (2019). A comparison of different approaches to automatic control for sewer systems. Geophysical Research Abstracts, 21, Article EGU2019-12743-2.

## Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

Geophysical Research Abstracts Vol. 21, EGU2019-12743-2, 2019 EGU General Assembly 2019 © Author(s) 2019. CC Attribution 4.0 license.



## A comparison of different approaches to automatic control for sewer systems

Alla Kolechkina and Ronald van Nooijen Delft University of Technology, Den Hoorn (ZH), Netherlands

In low lying areas like the Netherlands, sewer systems depend on pumps to manage the flow. Many of these systems are still combined systems, where storm water and foul water flow through the same pipes. These are usually designed to perform well under uniform precipitation. In practice, precipitation is not uniform, and the systems themselves have grown over the years and during that growth process the original design philosophy may not have been respected. During dry weather, this is usually not a problem as pump capacities are more than sufficient. During wet weather, sewer systems need to be carefully managed to make optimal use of in-system storage and compensate for in-homogeneous inflow due to precipitation. We will compare the effectiveness of different strategies for pump use.