

Flight Path Optimization for Airborne Wind Energy Applications Using Multiple Tethered Aircrafts

Elhesasy, Mohamed; Dief, Tarek N.; Kamra, Mohamed; Alnuaimi, Saeed K.; Okasha, Mohamed; Schmehl, R.

Publication date

2024

Document Version

Final published version

Citation (APA)

Elhesasy, M., Dief, T. N., Kamra, M., Alnuaimi, S. K., Okasha, M., & Schmehl, R. (2024). *Flight Path Optimization for Airborne Wind Energy Applications Using Multiple Tethered Aircrafts*. Abstract from 10th International Airborne Wind Energy Conference (AWEC 2024), Madrid, Spain.
<http://resolver.tudelft.nl/uuid:b5c436fe-3ce0-4b36-9c13-0fc8c1d02c74>

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.



Mohamed Elhesasy

MSc Student
Department of Mechanical and Aerospace
Engineering
United Arab Emirates University

Al Ain P.O. Box 15551,
United Arab Emirates

mohamed_m@uaeu.ac.ae
www.uaeu.ac.ae

Flight Path Optimization for Airborne Wind Energy Applications Using Multiple Tethered Aircrafts

Mohamed Elhesasy¹, Tarek N.Dief¹, Mohamed Kamra¹,
Saeed K. Alnuaimi¹, Mohamed Okasha¹, Roland Schmehl²

¹United Arab Emirates University

²Delft University of Technology

Generating electricity can be more efficient and cost-effective through the utilization of multi-aircraft systems in the process of airborne wind energy (AWE) applications. This approach involves the operation of multiple tethered aircraft connected by a shared main tether. In this way, the lateral motion of the shared tether is reduced, thereby minimizing aerodynamic drag and maximizing the harvested energy. Extensive research on tethered multi-aircraft systems has revealed significant efficiency improvements. These conceptual extensions offer advantages such as scalability, more consistent power output profiles, and increased power densities within the entire farm structure. However, they are accompanied by a set of challenges, including increased complexity, optimization of path trajectories of the system to avoid collisions during flight, and handling the process of reeling in and out of the tether during take-off and landing.

For any AWE system, efficient flight paths are critical for path planning, system optimization, and controller design. While previous research in this area has been primarily conducted through simulations, our work introduces practical outcomes derived from real-world experi-

ments to optimize the flight trajectory of two tethered unmanned aerial vehicles (UAVs).

In this talk, I will present the initial setup of our multiple-tethered aircraft system, including the hardware configuration of each tethered UAV, controller design, and optimization of their flight paths to maximize lift when flying across the wind in a figure-of-eight pattern. Furthermore, I will discuss the conclusions obtained from our work with this configuration and outline future steps to enhance our model to maximize its power generation capabilities.

References:

[1] De Schutter, Jochem, et al. "Optimal control of stacked multi-kite systems for utility-scale airborne wind energy." 2019 IEEE 58th Conference on Decision and Control (CDC). IEEE, 2019.

[2] De Schutter, Jochem, et al. "Awebox: An optimal control framework for single-and multi-aircraft airborne wind energy systems." *Energies* **16**(4), 1900, 2023.

