- Bitumen
- Wooden planks 20 mm
- water permeable film
- Hemplax 160 mm
- 160 x 60 mm, distance between centers is 600 mm
- vapor barrier film
- Wooden planks 20 mm
- Hemplax 100 mm
- 100 x 60 mm, distance between centers is 600 mm
- Perforated wooden plank 20 mm
- Metalwood-Finnjost 500 x 89 mm
- Wooden support for wooden structure
- Brickwork (waalformaat) 50 x 100 x 210 mm
- BioFoam pearls insulation 120 mm
- Brickwork (waalformaat) 50 x 100 x 210 mm
- Rest of paint
1:10
Rockzero window 4-15-4 mm
Steel hollow columns and beams 150 x 250 x 3 mm
Concrete finish
- Bamboo floor planks 22 mm
- Floor heating
- BioFoam insulation (hard) 55 mm
- CLT floor 200 mm
1:10
Steel hollow columns and beams 150 x 250 x 3 mm
1:5
- Moso Bamboo structure (stabalux)
- Stabalux frames for solar shading
- Moso X-treme solar shading
- Cast floor 20 mm
- Throwel floor with floor heating 102 mm
- BioFoam insulation (hard) 100 mm
- Precast concrete panel
- Poured concrete 220 mm with ventilation ducts
- Prefabricated concrete panel with steel reinforcement 80 mm
- Foundation beam poured concrete
- Concrete foundation (screw) piles
1:20
Existing foundation
- Moso Bamboo X-treme floor planks (terrace)
- Throwel floor 102 mm
- Precast concrete panel
- Poured concrete 220 mm
- Prefabricated concrete panel with steel reinforcement 80 mm
- Foundation beam poured concrete
- Concrete foundation (screw) piles
1:20