


Sustainable Design Development of a Concrete Lock Chamber

Reaching a sustainable and durable design of a ship lock concrete hard structure, enabling navigation through the Haringvliet storm surge barrier as part of the Delta21 Project

Sóley Hjörvarsdóttir

Thesis defence

April 11th 2024



Agenda

01. Introduction

02. Design

03. Life Cycle
Assessment Results
and discussion

04. Conclusion






Introduction

.

Introduction



Environment and the construction sector


- Construction industry is responsible for 25% of global GHG emissions
- Concrete is the 2nd most consumed material in the world
- Responsible for roughly 8% of global CO₂ emissions
- Global cement production has increased more than 30-fold since the 1950s

Why concrete was chosen for this study

- Steel structures have much lower global warming potential than concrete structures
 - Steel has better tension properties, high strength and stiffness per weight, thus resulting in a much lighter structure

However

- Concrete is very popular; not showing any trends in decreasing popularity worldwide
- Important to make concrete structures more sustainable




Research Question

How can a concrete hydraulic hard structure be designed sustainably, using a ship lock chamber as a case study, with the aim of reducing CO₂/year by 50%?

- What is a sustainable concrete structure
- Which aspects of the design are the most influential on the sustainability of the structure
- Which aspects of the design are most influential when it comes to the cost of the structure

Ship Lock



Methodology

- Two Concrete lock chamber alternatives are designed
 - Base case: Designed based on what is most commonly done in practice
 - Optimised design: Sustainable concrete chamber alternative
- A more sustainable concrete chamber alternative is chosen:
 - Different structural wall types are investigated. Best performing one, resulting in the lowest shear forces and moments is chosen for the optimised design
- Partial LCA performed

Case study

- Design of a concrete ship lock chamber as part of the Delta21 project
- Delta21 plans:
 - Protect the Dutch coast against floods
 - Open Storm surge barrier (no. 3)
 - Energy storage lake connected to the tidal lake via a spillway (no. 2)
 - Fish migration river
 - Ship passage
 - Pumps to discharge water into the North Sea (no.1)






Design of the Lock Chamber

Load case

Wall load case:


- Soil pressure
- Hydrostatic pressure from ground water
- Surcharge load on the surface
- Self weight
- Water within the chamber at minimum locking level

Year	2050	2100	2150	2200	2250
SLR [m]	0.32	0.82	1.50	2.60	3.88



Base Case Design



- Concrete U-basin chamber with a trapezoidal wall
 - Wall reinforced into the concrete floor – stiff connection
- No shear reinforcement is provided
- C50/60 concrete



- Step design along the dike
 - Wall height decreases by 0.5 m with each step
 - Dike slope 1:3
- $H_{seaside} = 12.2 \text{ m}$
- $H_{riverside} = 9.7 \text{ m}$
- $H_{center} = 16.2 \text{ m}$



Alternative design

- Goal of the thesis: Find a sustainable concrete chamber design alternative to the base case
- Four different shape typologies were considered for the optimized design




- The wall that best performed in terms of shear and moment was chosen for the design

- **Anchored chamber wall**



Anchored wall chamber design

- Added width to allow for the same ship clearance:
 - $B_{ch} = 16.5\text{ m}$
- Wall height on the seaside is constructed in stages:
- Shear reinforcement is now included in the design
- Concrete used for the optimised design:
 - C35/45
 - C25/30 – wall increment in 2150



- Wall height decreases gradually along the slope
- $H_{seaside,2100} = 9.7\text{ m}$
- $H_{seaside,2150} = 12.2\text{ m}$

Design results



- 88% reduction in maximum moments
- 56% reduction in shear force at the bottom of the wall

- 47% reduction in concrete volume
- 46% reduction in reinforcement volume

- Rebar-to-concrete ratio:
 - Base case chamber: 1.1%
 - Anchored wall chamber: 1.1%




LCA Results

.


Life Cycle Assessment

Life cycle stages




Global Warming Potential (GWP)


- Quantifies the impact of GHG emission on global warming
- kg CO₂/unit




LCA Results




Material contribution to the total GWP




Contribution of the chamber and the underwater concrete floor to the total GWP



Underwater concrete used as the chamber floor



Cost [$\text{€}\cdot 10^{-3}$] and GWP [$\text{ton CO}_2\text{-eq}$] for different reinforcement-concrete ratios





Conclusions

.

Conclusion

- Goal of the thesis: reduce carbon footprint by 50%
- Anchors effectively reduced the maximum moments and shear forces
- Optimising the design was beneficial in two ways:
 - Improved structural performance
 - Reduced carbon footprint

Conclusion

- An optimum reinforcement-to-concrete ratio for the anchored chamber wall was found as 2.3%
 - Sustainable design solutions can be economically viable
 - This ratio can be used as a guide for other concrete walls with shear reinforcement

Conclusion

- Potential for integrating sustainability objectives into the structural design process
- Principles underlying the optimisation process can be applied to other soil retaining concrete structures:
 - Optimisation through structural elements
 - Reduction of material volumes
 - Comparative analysis

Recommendations

- Development of integrated design frameworks that consider sustainability from early stages in design
 - Optimum reinforcement-to-concrete ratio for different types of concrete elements
- Research on the feasibility of using underwater concrete floor as a primary flooring in a hydraulic structure



Thank you