

Vehicle-to-Grid Concept for Hydrogen Fuel Cell Hybrid-Electric Regional Trains

Kapetanović, Marko; Núñez, Alfredo; van Oort, Niels; Goverde, Rob M.P.

DOI

[10.37528/FTTE/9788673954677/RailBelgrade.2023.ZE](https://doi.org/10.37528/FTTE/9788673954677/RailBelgrade.2023.ZE)

Publication date

2023

Document Version

Final published version

Citation (APA)

Kapetanović, M., Núñez, A., van Oort, N., & Goverde, R. M. P. (2023). *Vehicle-to-Grid Concept for Hydrogen Fuel Cell Hybrid-Electric Regional Trains*. 141-141. Abstract from RailBelgrade 2023, Belgrade, Serbia. <https://doi.org/10.37528/FTTE/9788673954677/RailBelgrade.2023.ZE>

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

Green Open Access added to TU Delft Institutional Repository

'You share, we take care!' - Taverne project

<https://www.openaccess.nl/en/you-share-we-take-care>

Otherwise as indicated in the copyright section: the publisher is the copyright holder of this work and the author uses the Dutch legislation to make this work public.

Session 1.1B: Emerging railway technologies
Submission type: Research paper
Presentation type: Oral
Paper ID: [139]

Vehicle-to-Grid Concept for Hydrogen Fuel Cell Hybrid-Electric Regional Trains

Marko Kapetanović^a, Alfredo Núñez^b, Niels van Oort^a and Rob M.P. Goverde^a.

^a *Department of Transport and Planning, Delft University of Technology P.O. Box 5048, 2600 GA Delft, The Netherlands*

^b *Section of Railway Engineering, Delft University of Technology P.O. Box 5048, 2600 GA Delft, The Netherlands*

Hydrogen fuel cell multiple unit vehicles are acquiring a central role in the transition process towards carbon neutral trains operation in non-electrified regional railway networks. In addition to their primary role as a transport mean, these vehicles offer significant potential for applications in innovative concepts such as smart grids. Compared to the pure electric propulsion systems, fuel cell technology allows for cogeneration processes by recovering generated heat in addition to the provision of the electrical power. This paper presents the analysis of fuel cell hybrid-electric multiple unit vehicle employed in regional railway transport during regular service, and in vehicle-to-grid application during the off-service hours, where it provides the electrical and thermal energy for stationary consumers in terminal stations. The system dynamics are modelled using a backward-looking quasi-static simulation approach, with implemented real-time optimization-based control strategy for managing the power flows between different components. In a case study of selected vehicle and railway services in the Netherlands, the fuel cell system showed average hydrogen consumption of 0.4 kg/km, with the overall electrical efficiency of 38.89%. In vehicle-to-grid scenario, the system satisfied complete stationary power demand, and provided about 327 kWh of thermal energy during two-hours operation, reaching overall cogeneration efficiency of 66.81%.

Keywords

Regional railways, Hydrogen, Fuel cell hybrid-electric systems, Vehicle-to-grid