

Preliminary analysis of ionosphere-corrected PPP-RTK user performance

Psychas, Dimitrios; Verhagen, S.; Liu, Xianglin

Publication date

2019

Document Version

Final published version

Citation (APA)

Psychas, D., Verhagen, S., & Liu, X. (2019). *Preliminary analysis of ionosphere-corrected PPP-RTK user performance*. Poster session presented at EGU General Assembly 2019 , Vienna, Austria.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

1. Introduction

The realization of the integer ambiguity resolution (IAR) enabled precise point positioning (PPP) method, the so-called **PPP-RTK**, is enabled by providing single-receiver PPP users with **satellite phase biases to recover the integerness of the user ambiguities**. Successful IAR can greatly reduce the solution convergence time. However, the unknown ionospheric delay parameters that are estimated by the PPP-RTK user (ionosphere-float model) do not allow for fast (or instantaneous) convergence to the centimeter level.

In this poster, we present a preliminary analysis on the improvement of PPP-RTK GPS dual-frequency user positioning performance **using precise ionospheric corrections**, which are expected to **greatly reduce the convergence time**. The ionospheric corrections used at the user level are determined by modeling PPP-RTK ionospheric slant delays computed from receivers of a regional network. The improvement of the PPP-IAR user performance is analyzed in terms of the required time to fix the integer ambiguities (TTFA) and the achieved convergence time to the 10 cm level.

2. PPP-RTK network system

The basis of the PPP-RTK network system is the **uncombined** GNSS code and carrier-phase observation equations:

$$E(p_{r,j}^s) = \rho_r^s + (dt_r - dt^s) + m_r^s \tau_r + \mu_j l_r^s + (d_{r,j} - d_{r,j}^s)$$

$$E(\phi_{r,j}^s) = \rho_r^s + (dt_r - dt^s) + m_r^s \tau_r - \mu_j l_r^s + \lambda_j (\delta_{r,j} - \delta_{r,j}^s + a_{r,j}^s)$$

Since not all the unknown parameters are unbiasedly estimable, we apply the S-system theory to eliminate the rank-deficiencies [1]. Assuming that precise orbits and clocks are used, the estimable parameters are:

$$\tilde{d}_r = (dt_r + d_{r,IF}) - (dt_p + d_{p,IF}), \quad \forall r \neq p \quad (p: \text{pivot rec./sat.})$$

$$\tilde{l}_r^s = l_r^s + d_{r,GF} - d_{GF}^s, \quad \forall r, s \quad (\text{IF: ionosphere-free})$$

$$\tilde{\delta}_{r,j} = \left(\delta_{r,j} - \frac{1}{\lambda_j} [d_{r,IF} - \mu_j d_{r,GF}] + a_{r,j}^p \right) \quad (\text{GF: geometry-free})$$

$$- \left(\delta_{p,j} - \frac{1}{\lambda_j} [d_{p,IF} - \mu_j d_{p,GF}] + a_{p,j}^p \right), \quad \forall j, r \neq p$$

$$\tilde{\delta}_{j,j}^s = \left(\delta_{j,j}^s - \frac{1}{\lambda_j} [d_{j,IF}^s - \mu_j d_{j,GF}^s] \right)$$

$$- \left(\delta_{p,j} - \frac{1}{\lambda_j} [d_{p,IF} - \mu_j d_{p,GF}] + a_{p,j}^s \right), \quad \forall j, s$$

$$\tilde{a}_{r,j}^s = (a_{r,j}^s - a_{r,j}^p) - (a_{p,j}^s - a_{p,j}^p), \quad \forall j, r \neq p, s \neq p$$

3. PPP-RTK user system

The definition and estimability of the ionosphere-float PPP-RTK user parameters are the same as in the network component:

$$E(p_{u,j}^s + \tilde{d}t^s) = \rho_u^s + \tilde{d}t_u + m_u^s \tau_u + \mu_j \tilde{l}_u^s$$

$$E(\phi_{u,j}^s + \tilde{d}t^s + \lambda_j \tilde{\delta}_{j,j}^s) = \rho_u^s + \tilde{d}t_u + m_u^s \tau_u - \mu_j \tilde{l}_u^s + \lambda_j (\tilde{\delta}_{u,j} + \tilde{a}_{u,j}^s)$$


The user phase ambiguities are now double-differenced and therefore **integer**.

If ionospheric corrections are provided to the user, the **receiver code bias parameter** of the user becomes estimable.

4. Data – Processing strategy

For the network and user processing, a network in US with the **largest inter-station distance being ~170 km** was processed for 24 hours on February 15, 2014. **Dual-frequency GPS-only** 30 s data are used for the processing with an elevation mask of 10 degrees.


- Meas. noise at zenith: 30cm / 3mm for code / phase
- Parameter estimation using **Kalman filter**
- Full integer ambiguity resolution using **LAMBDA** [2]
- **User-specific ionospheric slant delays are determined** using the least-squares collocation [3] and the best linear unbiased prediction model [4].







5. Results

- When precise ionospheric corrections are provided to the user, **the model becomes stronger** than before leading to **more precise phase ambiguities** and, therefore, to higher ambiguity success rates and **shorter TTFA's**, see (a) and (b).
- The quite stable satellite phase biases, see (c), allow for realizing PPP-RTK. When **ionospheric corrections** are further used, the **convergence time drops to only 9 minutes**, see (d).
- The estimable **receiver code bias** shows a **stability over time**, with its daily variation not exceeding 20 cm, see (e).

Ionosphere-float PPP-RTK user



Ionosphere-corrected PPP-RTK user



- ## 6. Conclusions
- The **ionosphere-float model is weak in terms of IAR** due to the increased number of unknown parameters.
 - **Precise ionospheric corrections** can significantly reduce the convergence time.
- Outlook:** A large number of sample data will be processed to infer the **distribution of the achieved convergence times**, due to the **random nature of the GNSS data**.



References:

- [1] Odijk, D., Zhang, B., Khodabandeh, A., et al., 2016. On the estimability of parameters in undifferenced, uncombined GNSS network and PPP-RTK user models by means of S-system theory. *J. Geod.* 90 (1), 15-44.
- [2] Teunissen, P.J.G., 1995. The least-squares ambiguity decorrelation adjustment: a method for fast GPS integer ambiguity estimation. *J. Geod.* 70 (1-2), 65-82.
- [3] Moritz, H., 1978. Least-squares collocation. *Rev. Geophys.* 16 (3), 423-430.
- [4] Teunissen, P.J.G., Khodabandeh, A., 2013. BLUE, BLUP and the Kalman filter: some new results. *J. Geod.* 87 (5), 461-473.

Acknowledgements:

This project has received funding from the European Union's Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie Grant Agreement No 722023.
The authors would like to acknowledge the National Geodetic Survey of the United States for making its CORS GNSS data publicly available.

