

## The influence of anomalous Doppler waves on the Hyperloop stability

Fărăgău, Andrei B.; Metrikine, Andrei; Paul, Jithu; van Leijden, Rens; van Dalen, Karel

**Publication date**

2024

**Document Version**

Final published version

**Citation (APA)**

Fărăgău, A. B., Metrikine, A., Paul, J., van Leijden, R., & van Dalen, K. (2024). *The influence of anomalous Doppler waves on the Hyperloop stability*. Abstract from The Third International Conference on Rail Transportation, Shanghai, China.

**Important note**

To cite this publication, please use the final published version (if applicable). Please check the document version above.

**Copyright**

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

**Takedown policy**

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.



# ICRT2024

The Third International Conference of Rail Transportation

August 7~9, 2024 | Shanghai, China

## ABSTRACT

### Title

**The influence of anomalous Doppler waves on the Hyperloop stability**

Andrei B. Fărăgău<sup>1\*</sup>, Andrei Metrikine<sup>1</sup>, Jithu Paul<sup>1</sup>, Rens van Leijden<sup>1</sup>, and Karel van Dalen<sup>1</sup>  
<sup>1</sup>Faculty of Civil Engineering and Geosciences, Delft University of Technology, the Netherlands

\*Corresponding Author: a.b.faragau@tudelft.nl

### Abstract

The Hyperloop is an innovative transportation system that is currently under development. It minimizes air resistance by enclosing the vehicle in a de-pressurized tube and eliminates wheel-rail contact friction through the use of an electromagnetic suspension/levitation, similar to Maglev trains. This design can potentially achieve much higher velocities compared to traditional railways, positioning the Hyperloop as an environmentally friendly alternative to air transportation.

A potential challenge for Hyperloop is ensuring the dynamic stability at large velocities, where multiple instability sources can be present. An apparent source is the electro-magnetic suspension (adopted by some designs) making a control strategy mandatory to ensure stability even at quasi-static velocities. A less obvious instability mechanism is that the vibration of a vehicle on an elastic guideway can become unstable when surpassing a critical velocity.

The authors have previously investigated the interplay between the electro-magnetic and wave-induced instability mechanisms and showed that the stability space changes significantly above a certain velocity. In other words, the control strategy can ensure the overall system stability only for a very limited range of its gains. The cause for this drastic change was attributed to the wave-induced instability mechanism. Metrikin demonstrated that this instability arises with the radiation of anomalous Doppler waves, which introduce more energy to the vehicle's vibration than normal Doppler waves radiate away from the vehicle. The current study demonstrates that the change of stability domain is indeed caused by the anomalous Doppler waves. While identifying unstable velocity regimes is practical for Hyperloop design, gaining insight into the contribution of individual instability mechanisms can be crucial for efficient mitigation.

### Preferred Presentation Type

Oral       Poster       Only proceedings       No preference

### List Relevant Conference Theme(s) below

New type of rail transport