Viand & Discovery Haarlem

a user experience-based design of the public space

Rachel Mein | 4342410 Vacant Heritage | P5



I ResearchII ProgrammeIII Climate


Personal connection



© View roof terrace V&D Haarlem, 2015 (Haarlemnieuws)



V&D building



V&D building - Grote Houtstraat





V&D building - Verwulft



V&D building - Gierstraat





Public space



© V&D Haarlem terrace, 1991 (Beeldbank)

Sustainable development goals

"Universal access to safe, inclusive and accessible, green and public spaces, in particular for women and children, older persons and persons with disabilities"

(United Nations, 2015)


Historic Urban Landscape



 \circledast (PARK)ing day Minneapolis, 2008 (SV Johnson)


How could V&D Haarlem be reactivated through a user experience-based design of the public space according to Gehl's 12 quality criteria concerning the pedestrian landscape?

Methodology



© 12 quality criteria concering the pedestrian landscape, 2010 (Gehl)

Interrelated quality criteria








ŧ


















Interrelated quality criteria Haarlem



5 challenges



5 challenges



21

Field observations



Public transport


Cyclists

Pedestrians




Public transport






Street profile






5 challenges



Site plan



Averdung Platz, Duisburg



5 challenges

3 Delight



Site plan

































I ResearchII ProgrammeIII Climate

Concept




Programme



Subtropical garden
Bicycle mechanic
Circulation
Storage
Services


Programme



5 Interactive museum

Subtropical garden
Bicycle mechanic
Circulation
Storage
Services

Existing building





















Interventions ground floor










Limits of acceptable change








Maintain


Interfere

Demolition ground floor





Ground floor



- 1 Food market
- 2 Shop
- 3 Fish market
- 4 Bicycle mechanic

Ground floor




- 1 Food market
- 2 Shop
- 3 Fish market
- 4 Bicycle mechanic


Elevation Verwulft




Eusebius church, Arnhem



Fragment plinth



d floor	01	Existing timber window frame with single stained glass
	02	Second timber window frame HR ++
	03	
floor	04	 Floorfinish 10 mm Fermacell floor plates with floor heating 2 x 9mm Thermal insulation 10 mm Fiberboard 10 mm Existing concrete floor 140mm Thermal insulation 160 mm Steel beam Stainless steel wire rope Gypsum plate 12,5mm Timber frame 200 mm Zinc sheet corten steel coat Oxydecor 2 mm Seam in line with facade for rainwater
	05	 Gypsum plate 12,5 mm Thermal insulation 160 mm Existing concrete floor 140mm Equalising sand layer 30 mm Pavement 60 mm



















































































Section




Concept modules









Modules



Modules




Second floor minimum scenario



- 1 Study area
- 2 Reception
- 3 Exposition
- 4 Lecture room

66


Second floor maximum scenario



- 1 Food market
- 2 Presentation area
- 3 Cloak room
- 4 Bar



Fragment second floor




01 Existing timber window frame with single stained glass

O2 Second timber window frame HR ++
O3 - Existing masonry 340mm
- Existing stucco 10mm
- Thermal insulation 140 mm
- Gypsum plate 12,5mm
- White stucco 10 mm


O4 - Floorfinish 10 mm
- Fermacell floor plates with floor heating 2 x 9mm
- Thermal insulation 10 mm
- Fiberboard 10 mm
- Existing concrete floor 140mm
- Acoustic spray

Fragment ramp



```
- Perforated acoustic
    bamboo panel 10 mm
    - Steel truss 120 mm
    - Mineral wool 100 mm
    - Perforated acoustic
    bamboo panel 10 mm
02 - Round column
    diameter 300 mm
    - Bamboo floorfinish 10 mm
    - Dovetailed sheet
    floor 34-16 mm
    - Steel truss 120 mm
    - Crossbars
    - HEA 300
    - Perforated acoustic
    bamboo panel 10mm
03 - LED light in bamboo panel
04 - Irrigation system
05 - Grey linoleum floorfinish 10 mm
   - Fermacell floor panels
   with floor heating 2 x 9mm
   - Thermal insulation 10 mm
   - Fiberboard 10 mm
   - Existing concrete floor 140mm
   - Grey acoustic spray
```

Fragment ramp horizontal




01 - Existing concrete column octogonal 700 mm


- 02 Steel round column diameter 300 mm
 - Stainless steel railing 40 mm
 Perforated acoustic

 - bamboo balustrade 140 mm
 - Planter
 - Aluminium glass panel 120 mm


Fragment ramp 3D



Fragment ramp 3D



Fragment ramp 3D
































I ResearchII ProgrammeIII Climate

Thermal zones



16 degrees | atrium, circulation space heated by residual heat

20 degrees | education, cooking studio, restaurant


18 degrees | foodmarket, shop-in-shop, museum

Self regulation climate | modules cooking studio

Exterior climate | bicycle parking, storage


80

Winter situation




- 1. Glass roof with BIPV 50% transparent
- 2. Greenhouse as thermo buffer: Preheating in winter
- 3. Rain water collector: Grey water system for plants
- 4. Thermal insulation plinth
- 5. Secondary windows and thermal insulation
- 6. Floor heating
- 7. Mechanical ventilation, pre-heated
- 8. Thermal insulation roof
- 9. Greenhouse with BIPV 50% transparent
- 10. Air handling units (WTW)
- 11. Water collector for reuse toilets
- 12. Heat pump and open groundenergy system (WKO), water water with two aquifers

Summer situation



- 1. Glass roof with BIPV 50% transparent
- 2. Greenhouse as thermo buffer: Cooling in summer
- 3. Rain water collector: Grey water system for plants
- 4. Thermal insulation plinth
- 5. Secondary windows and thermal insulation
- 6. Floor cooling
- 7. Mechanical ventilation
- 8. Thermal insulation roof
- 9. Store remaining heat for winter
- 10. Greenhouse with BIPV 50% transparent
- 11. Air handling units (WTW)
- 12. Dynamic sunscreens
- 13. Water collector for reuse toilets
- 14. Heat pump and open groundenergy system (WKO), water water with two aquifers 82

Detail gutter



01 Thermal insulation 40 mm Steel profile 3 mm


02 Steel gutter width 220 mm Steel square tube 300 x 40 mm

03 Glass 6.6/18/6.6 mm Rainwater discharge

04 Bolt M6 Steel head plate Steel square tube 200 x 100 mm

05 LED light

Rooftop



- 1 Amphitheatre
- 2 Bar
- 3 Kids playground
- 4 Greenhouse




84


Bird view
























Video




Viand & Discovery Haarlem


a user experience-based design of the public space

Rachel Mein | 4342410 Vacant Heritage | P5

Detail Octatube




Detail gutter




02 Steel gutter width 220 mm Steel square tube 300 x 40 mm

Steel head plate Steel square tube 200 x 100 mm


Elevation Grote Houtstraat



Elevation Gierstraat




Basement -2





- 1 Storage
- 2 Installations


Basement -1



- 1 Bicycle parking
- 2 Installations
- 3 Storage




First floor





1 Shop-in-shops


Third floor





- 2 Reception
- 3 Exposition


Fourth floor



- 1 Cooking module
- 2 Diner area
- 3 Reception
- 4 Bar




Fifth floor




- 1 Interactive museum
- 2 Ticket shop
- 3 Museum shop
- 4 Lecture room

Sixth floor




- 1 Restaurant
- 2 Café
- 3 Bar
- 4 Kitchen


Escape routes



Scores field observations



Subtropical garden plants



Relation void and staircase

