



Delft University of Technology

#### Document Version

Final published version

#### Citation (APA)

Han, C., Yang, G., Procel, P., Mazzarella, L., Zhao, Y., Eijt, S., Schut, H., Zeman, M., Isabella, O., & More Authors (2021). Correction: Realizing the potential of RF-sputtered hydrogenated fluorine-doped indium oxide as an electrode material for ultrathin SiO<sub>2</sub>/poly-si passivating contacts (*ACS Applied Energy Materials* (2020) 3:9 (8606-8618) DOI: 10.1021/acsaem.0c01206). *ACS Applied Energy Materials*, 4(3), 2961. <https://doi.org/10.1021/acsaem.1c00519>

#### Important note

To cite this publication, please use the final published version (if applicable).  
Please check the document version above.

#### Copyright

In case the licence states "Dutch Copyright Act (Article 25fa)", this publication was made available Green Open Access via the TU Delft Institutional Repository pursuant to Dutch Copyright Act (Article 25fa, the Taverne amendment). This provision does not affect copyright ownership.  
Unless copyright is transferred by contract or statute, it remains with the copyright holder.

#### Sharing and reuse

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

#### Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.  
We will remove access to the work immediately and investigate your claim.

*This work is downloaded from Delft University of Technology.*

# Correction to “Realizing the Potential of RF-Sputtered Hydrogenated Fluorine-Doped Indium Oxide as an Electrode Material for Ultrathin SiO<sub>x</sub>/Poly-Si Passivating Contacts”

Can Han,\* Guangtao Yang, Ana Montes, Paul Procel, Luana Mazzarella, Yifeng Zhao, Stephan Eijt, Henk Schut, Xiaodan Zhang, Miro Zeman, and Olindo Isabella\*

ACS Applied Energy Materials 2020, 3, 9, 8606–8618. DOI: 10.1021/acsaem.0c01206



Cite This: ACS Appl. Energy Mater. 2021, 4, 2961–2961



Read Online

ACCESS |



Metrics & More



Article Recommendations

The authors inadvertently misreported the order of magnitude of the TCO deposition pressure, for which all “10<sup>-3</sup> Pa” should be intended as “Pa”. The following errors appear in the article.

P8607. EXPERIMENTAL SECTION, 2.1.

“2.50 × 10<sup>-3</sup> Pa”, “1.6 × 10<sup>-5</sup> Pa”, and “2.20 × 10<sup>-3</sup> Pa” should be read as “2.50 Pa”, “1.6 × 10<sup>-2</sup> Pa”, and “2.20 Pa”, respectively.

These errors do not affect the “RESULTS AND DISCUSSION” or “CONCLUSIONS” of this article.

Published: March 1, 2021

