

Thermo-fluid modeling of influence of attenuated laser beam intensity profile on melt pool behavior in laser-assisted powder-based direct energy deposition

Sattari, Mohammad ; Ebrahimi, Amin; Luckabauer, Martin; Römer, Gert-willem R.B.E.

Publication date

2023

Document Version

Final published version

Citation (APA)

Sattari, M., Ebrahimi, A., Luckabauer, M., & Römer, G. R. B. E. (2023). *Thermo-fluid modeling of influence of attenuated laser beam intensity profile on melt pool behavior in laser-assisted powder-based direct energy deposition*. Abstract from Flow-3D World User Conference, Strasbourg, France.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

Thermo-fluid Modeling of Influence of Attenuated Laser Beam Intensity Profile on Melt Pool Behavior in Laser-Assisted Powder-Based Direct Energy Deposition

Mohammad Sattari ^{a,*}, Amin Ebrahimi ^b, Martin Luckabauer ^a, Gert-willem R.B.E. Römer ^a

^a Department of Mechanics of Solids, Surfaces and Systems, Faculty of Engineering Technology, University of Twente, Drienerlolaan 5, 7522NB Enschede, The Netherlands

^b Department of Materials Science and Engineering, Faculty of Mechanical, Maritime and Materials Engineering, Delft University of Technology, Mekelweg 2, 2628CD Delft, The Netherlands

* Corresponding author: m.sattari@utwente.nl (M. Sattari)

Abstract

A numerical framework based on Computational Fluid Dynamics (CFD), using the Finite Volume Method (FVM) and Volume of Fluid (VOF) technique is presented to investigate the effect of the laser beam intensity profile on melt pool behavior in Laser-assisted powder-based Directed Energy Deposition (L-DED). L-DED is an Additive Manufacturing (AM) process that utilizes a laser beam to fuse metal powder particles. To assure high-fidelity modeling, it was found that it is crucial to accurately model the interaction between the powder stream and the laser beam in the gas region above the substrate. The proposed model considers various phenomena including laser energy attenuation and absorption, multiple reflections of the laser rays, powder particle stream, particle-fluid interaction, temperature-dependent properties, buoyancy effects, thermal expansion, solidification shrinkage and drag, and Marangoni flow. The latter is induced by temperature and element-dependent surface tension. The model is validated using experimental results, and highlights the importance of considering laser energy attenuation. Furthermore, the study investigates how the laser beam intensity profile affects melt pool size and shape, influencing the solidification microstructure and mechanical properties of deposited material. The proposed model has the potential to optimize the L-DED process for a variety of materials and provides insights into the capability of numerical modeling for additive manufacturing optimization.