



Delft University of Technology

Is “green” ammonia a misnomer?

Unpacking the green label from a food-water-energy nexus perspective in water-scarce regions

Simha, Prithvi; van der Merwe, Gert

DOI

[10.1186/s44329-024-00005-3](https://doi.org/10.1186/s44329-024-00005-3)

Publication date

2024

Document Version

Final published version

Published in

BMC Environmental Science

Citation (APA)

Simha, P., & van der Merwe, G. (2024). Is “green” ammonia a misnomer? Unpacking the green label from a food-water-energy nexus perspective in water-scarce regions. *BMC Environmental Science*, 1, Article 5. <https://doi.org/10.1186/s44329-024-00005-3>

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

COMMENT

Open Access



Is “green” ammonia a misnomer? Unpacking the green label from a food-water-energy nexus perspective in water-scarce regions

Prithvi Simha^{1,2*} and Gert van der Merwe^{2,3,4}

Abstract

The term ‘green ammonia’ can be misleading. For fertilisers to merit a green label, the industry must adopt a planetary boundaries framework that includes reducing carbon emissions and circular management of nutrients. It should seek to achieve net reductions in reactive nitrogen and phosphorus fluxes to terrestrial and marine ecosystems.

Keywords Circular Economy, Water Scarcity, Fertiliser Production, Nitrogen Recycling, Wastewater

Introduction

The global drive for circularity and sustainability has intensified research and development into ‘green’ and ‘eco-friendly’ technologies [1]. These technologies are expected to be more environmentally benign than their conventional counterparts [2]. However, ‘green’ is often a broad categorisation encompassing diverse concepts and is frequently used interchangeably with terms such as ‘sustainable’, ‘eco-friendly’ and ‘ecological’ [3]. This can create confusion among consumers regarding the specific attributes that make a technology or product truly green [4].

In this commentary, we evaluate the accuracy of the term ‘green ammonia’. ‘Green’ implies that ammonia production has minimal environmental impacts, but in reality the impacts of green ammonia synthesis are

rather complex. Production of green ammonia requires availability of ‘green’ hydrogen, a product of water electrolysis powered by renewable energy. However, large-scale electrolysis requires abstraction and/or production of substantial amounts of freshwater, a critical resource in regions like Australia and Namibia that are poised to produce most of this green hydrogen. Here, we unpack the ‘green’ label for hydrogen and ammonia, considering aspects of water security and the food-water-energy nexus. Furthermore, we argue for a broader application of circular economy principles in the fertiliser industry. As sustainable alternatives to green ammonia, we propose recycling of human excreta and other organic wastes as fertilisers, as this would reduce carbon emissions as well as decrease reactive nitrogen and phosphorus fluxes to ecosystems.

The term ‘green ammonia’ is misleading and overly simplistic

‘Green ammonia’ is described as a green fertiliser and zero-carbon fuel and is promoted as one approach to accelerate global transition toward net-zero carbon emissions [5]. Conventional ‘brown ammonia’, mostly used in agriculture as crop fertiliser [6] is typically produced in the Haber–Bosch process, where hydrogen sourced from steam reforming of fossil-derived

*Correspondence:

Prithvi Simha

Prithvi.Simha@slu.se; Prithvi.Simha@mespom.eu

¹ Department of Energy and Technology, Swedish University of Agricultural Sciences, P.O. Box 7032, SE 75007 Uppsala, Sweden

² Gobabeb Namib Research Institute, Walvis Bay 13013, Namibia

³ Faculty of Engineering and the Built Environment, Department of Architecture, Planning and Construction, Namibia University of Science and Technology, Windhoek Private Bag 13388, Namibia

⁴ Faculty of Architecture and the Built Environment, Delft University of Technology, Building 8, Julianalaan 134, 2628 BL Delft, Netherlands



© The Author(s) 2024. **Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

methane is combined with nitrogen extracted from air. Brown ammonia production accounts for 1–2% of global carbon dioxide emissions [6]. Green ammonia production also relies on the Haber–Bosch process, but a key difference is that hydrogen is derived from renewable energy-powered electrolysis of water [7], thereby “greening” and decarbonising ammonia synthesis. Globally, the green hydrogen market is projected to experience significant growth, with investments expected to reach USD 570 billion by 2030, in around 1,400 projects across various regions [8].

Extraction of nitrogen from the atmosphere is an energy-intensive process that is fundamentally linear, irrespective of whether the nitrogen is used in green or brown ammonia synthesis. Unreactive atmospheric nitrogen is fixed by natural processes globally in oceans and on land, but anthropogenic nitrogen extraction through Haber–Bosch ammonia synthesis has almost doubled global nitrogen fixation [9]. Current assessments indicate that the biogeochemical cycle of nitrogen has now exceeded its delineated safe operating space within the ‘planetary boundaries’ [10]. Increased reactive nitrogen in the environment is creating issues far beyond the boundaries of its industrial use, including eutrophication of water bodies [11], acidification of soil [12], nitrous oxide emissions [13], PM_{2.5} air pollution [14], loss of biodiversity and changes in ecosystem functions. Therefore, despite significant reductions in carbon emissions associated with hydrogen production, green ammonia used as fertiliser is likely to have substantial life cycle impacts and the term ‘green ammonia’ is inaccurate.

Water security and environmental impact dimensions of green hydrogen production

Green hydrogen production relies on freshwater, an increasingly scarce resource globally and particularly in regions where many of the world’s largest green hydrogen projects are planned or underway. Apart from 87 GW of green hydrogen projects announced in Western Europe and an additional 2 GW in Brazil, the remaining projects are all situated in arid regions. Australia leads, with combined capacity of 58.6 GW across seven projects, followed by Kazakhstan with 30 GW and Mauritania with 21 GW [15]. Many hydrogen projects are planned in regions already experiencing extreme water stress, such as Oman (14 GW), Chile (8 GW), Namibia (3 GW) and Saudi Arabia (2GW) [15, 16]. In Namibia, the driest country in Sub-Saharan Africa, construction is underway on a gigawatt-scale project to produce 350,000 tonnes of green hydrogen and 2 million tonnes of green ammonia annually by 2030 [17]. In that project and in many others globally, desalination will be

performed by seawater reverse osmosis (SWRO), a process that contributes just 1% to the total cost of hydrogen production but has significant economic, social and environmental impacts [18, 19]. For example, SWRO requires multiple chemicals, such as acids to regulate pH, chlorine to prevent biofouling and anti-scalants to inhibit mineral precipitation. The byproduct is brine, a highly concentrated saline solution that also contains these chemicals. When brine is discharged to marine environments, it can significantly alter local pH and increase salinity, water temperature, concentrations of heavy metals and ultimately water toxicity, reducing biodiversity around discharge points [19]. To produce 1 kg of hydrogen via electrolysis, approximately 10 kg of freshwater are needed [18]. SWRO desalination has an average recovery rate of 40% [18, 20], so around 25 L of seawater are needed to produce 10 L of freshwater, with the process also resulting in production and discharge of approximately 15 L of brine. The energy demand for SWRO desalination is ~3.5 kWh/m³ [21], but can increase to 5.8–10.8 kWh/m³ depending on water salinity [21].

Environmental impact assessments of SWRO desalination for hydrogen projects in Namibia suggest that impacts from brine discharge will likely be low, except for localised effects near discharge points [19]. However, these assessments do not consider regional environmental impacts accruing over time resulting from the brine discharges of multiple projects [19]. Zero-/minimal-liquid-discharge (ZLD/MLD) technologies can be applied to mitigate environmental impacts associated with brine discharge. These technologies tap the economic potential of brine mining, since the pre-concentrated brine from SWRO is rich in sodium, lithium, boron, scandium, gallium, indium, vanadium and molybdenum [19]. These minerals are essential for driving the green energy transition and advancing the fourth Industrial Revolution.

Hydrogen has a high energy content by weight (~33.3 kWh kg⁻¹) [22]. The energy requirement for production of hydrogen via water electrolysis can vary significantly depending on the efficiency, scale and operating conditions of the electrolyser. Mean electric energy demand for water electrolysis is currently ~55 kWh per kg hydrogen, reflecting energy conversion efficiency of around 60%, not accounting for additional energy demands from SWRO and mechanical pumping [22]. Hydrogen production accounts for 80% of total energy demand in ammonia synthesis [23]. Novel methods for ammonia production, such as low-temperature electrochemical ammonia synthesis, have a theoretical minimum energy demand of 21.18–21.30 GJ per ton of ammonia [23, 24]. However, industrial-scale processes

for electrochemical ammonia synthesis currently achieve efficiencies of only 60–70%, resulting in energy demand of 30.3–35.3 GJ per ton of ammonia [22, 24]. Even with improved methods for producing nitrogen, such as using an air separation unit, the energy demand for green ammonia production methods remains similar to that of conventional processes like the Haber–Bosch method [23]. In real-world, smaller-scale operations, the energy demand for both low- and high-temperature electrochemical ammonia production is likely to exceed the amount suggested by theoretical models, reflecting a significant efficiency gap [22]. Technological advances are needed to bridge the gap between theoretical efficiency and practical application in hydrogen and ammonia production.

Food security versus green hydrogen production

Globally, Africa has the highest estimated technical potential for producing green hydrogen [15]. However, current estimates primarily consider land availability for electricity production, taking into account exclusion zones such as existing cropland, but overlook freshwater availability required for producing hydrogen. Around 65% of the world's uncultivated arable land is in Africa, but using this land for hydrogen production rather than food production poses significant ethical and sustainability issues, given the acute food security challenges globally and particularly in Africa [25]. According to the FAO Global Information and Early Warning System on Food and Agriculture (GIEWS), 46 of Africa's 54 countries requested external food assistance or faced agricultural shocks in 2022 [26]. Only five of these 46 countries did not meet GIEWS criteria, three of whom received external assistance from FAO and/or WFP and two from WFP/UNHCR for hosting refugee populations [26]. Furthermore, only four African countries experienced 0–10% food-price inflation, whereas the rest faced 11–20% or higher increases. Notably, Egypt, Nigeria and Ethiopia—home to the largest populations on the continent—saw food price inflation of 20–50% [26]. From a land use perspective, this suggests that a critical balance must be struck between advancing green energy projects and ensuring food security. It also raises ethical concerns, as prioritising green hydrogen production could undermine food security in regions already vulnerable to food scarcity.

A circular perspective on fertilisers?

Decarbonising the global economy is vital for our shared future, but exclusively focusing on reducing carbon dioxide emissions is somewhat shortsighted. For fertilisers to genuinely merit a green label, the industry

must adopt a planetary boundaries framework that extends beyond the current industry focus on merely offsetting or reducing carbon emissions from fertiliser production. Specifically, the framework should include management of global biogeochemical flows of nitrogen and phosphorus. The fertiliser industry has a significant impact on these nutrient cycles and thus has extended producer responsibility for minimising the environmental impacts of its products. The safe planetary boundaries for both nitrogen and phosphorus have already been exceeded, so the industry should aim for substantial reductions in fluxes of reactive nitrogen and phosphorus to terrestrial and marine ecosystems via its products. But how can such reductions be achieved if not through use of 'green ammonia'? One solution is for the industry to engage in large-scale production of bio-based fertilisers. Domestic wastewater, particularly source-separated fractions such as human urine [27, 28], is rich in bio-based nutrients that can be mined and recycled. Human urine is a rich source of urea, a waste product of nitrogen metabolism in the human body. Urea is also the most widely used fertiliser globally, with approximately half of the ammonia produced by the Haber–Bosch process utilised in manufacturing urea [29]. Simply storing human urine naturally converts urea back to ammonia [30], while both urea and ammonia can be feasibly recovered from human urine using a wide variety of technologies [31]. Life cycle assessments have demonstrated that recycling urine as fertiliser reduces greenhouse gas emissions, lowers energy consumption, and decreases eutrophication [32–34].

In a recently published UNEP [35] rapid response assessment report [35], we show that the human urine produced annually at global scale contains 31 Tg of nitrogen. Recycling nitrogen derived from urine could potentially meet 25% of global nitrogen demand in agriculture, or even more if other organic waste streams such as human faeces, livestock manure and crop residues are also recycled [36]. Such recycling could significantly offset the demand for anthropogenic nitrogen fixation via green/brown ammonia synthesis, thus aligning food systems more closely with the principles of a truly green and circular economy.

Transitioning the fertiliser industry to 'green' ammonia production is simpler than transitioning it to the production of bio-based fertilisers, since the former still uses the Haber–Bosch process, with the primary change being the substitution of water for fossil fuel as the hydrogen source. However, moving the industry to nutrient circularity will require the development of feasible and scalable technologies that safely recycle organic wastes like human urine. It will also require concerted efforts from academia, industry leaders,

policymakers and the public to critically rethink nutrient flows in society and identify fertilisers and food products that are genuinely worthy of the 'green' label. To reduce the ambiguity of the term 'green' within industrial applications, a more nuanced understanding and redefinition are required.

Acknowledgements

The authors are grateful to Dyllon Randall and Caitlin Courtney for providing useful feedback on an earlier draft of this paper.

Authors' contributions

Both authors, PS and G.V.D.M., contributed equally to all aspects of the research and manuscript preparation. This includes conceptualization, methodology, data collection and analysis, writing—original draft preparation, and reviewing and editing the final manuscript.

Funding

This study was supported by funding from SLU Urban Futures (Grant No. UF 66) and Research Council of Norway (Grant No. 335008) for the project 'Food Security Through Better Sanitation: The Case of Urine Recycling'.

Availability of data and materials

No datasets were generated or analysed during the current study.

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Competing interests

Prithvi Simha reports a relationship with Sanitation 360 AB, an SLU spin-off company commercializing technologies for recycling urine as fertilizer. His involvement includes co-ownership and board membership. He does not receive a salary from this company. The other author declares no competing interest.

Received: 14 May 2024 Accepted: 24 June 2024

Published online: 27 June 2024

References

- Santeramo FG. Circular and green economy: the state-of-the-art. *Heliyon*. 2022;8(4):e09297.
- Mulvaney DR. Green technology: an A-to-Z guide. The SAGE Reference Series on Green Society: Toward a Sustainable Future. P. Robbins, editor. Los Angeles: Sage Publications; 2011.
- Sdrolia E, Zarotiadis G. A comprehensive review for green product term: from definition to evaluation. *Journal of Economic Surveys*. 2018;33(1):150–78.
- Gershoff AD, Frels JK. What makes it green? The role of centrality of green attributes in evaluations of the greenness of products. *J Mark*. 2015;79(1):97–110.
- Royal Society. Ammonia: zero-carbon fertiliser, fuel and energy store. London: The Royal Society; 2020.
- IEA. Ammonia Technology Roadmap. Towards more sustainable nitrogen fertiliser production. Paris: International Energy Agency (IEA); 2021.
- Lee B, et al. Which water electrolysis technology is appropriate? Critical insights of potential water electrolysis for green ammonia production. *Renew Sustain Energy Rev*. 2021;143:110963.
- Council Hydrogen, Insights Hydrogen 2023. The state of the global hydrogen economy, with a deep dive into renewable hydrogen cost evolution. Geneva: Hydrogen Council, McKinsey & Company; 2023.
- Bodirsky BL, et al. Reactive nitrogen requirements to feed the world in 2050 and potential to mitigate nitrogen pollution. *Nat Commun*. 2014;5:3858.
- Steffen W, et al. Sustainability. Planetary boundaries: guiding human development on a changing planet. *Science*. 2015;347(6223):1259855.
- Diaz RJ, Rosenberg R. Spreading dead zones and consequences for marine ecosystems. *Science*. 2008;321(5891):926–9.
- Guo JH, Liu XJ, Zhang Y, Shen JL, Han WX, Zhang WF, Christie P, Goulding KWT, Vitousek PM, Zhang FS. Significant acidification in major Chinese croplands. *Science*. 2010;327(5968):1008–10.
- Zaehle S, et al. Carbon benefits of anthropogenic reactive nitrogen offset by nitrous oxide emissions. *Nat Geosci*. 2011;4(9):601–5.
- Gu B, et al. Abating ammonia is more cost-effective than nitrogen oxides for mitigating PM_{2.5} air pollution. *Science*. 2021;374(6568):758–62.
- IRENA. Geopolitics of the Energy Transformation: The Hydrogen Factor. Abu Dhabi: International Renewable Energy Agency (IRENA); 2022.
- Kuzma S, Saccoccia L, Chertock M. 25 Countries, Housing One-quarter of the Population, Face Extremely High Water Stress. Washington DC: World Resource Institute; 2023.
- Roelf W, Nyaungwa N. Hyphen and Namibia agree next phase of \$10 billion green hydrogen project, in Reuters. Reuters; 2023.
- BMBF, Fa. Report on desalination, brine treatment and its potential impact on maritime life. Germany: Forschung für Nachhaltigkeit (FONA), Bundesministeriums für Bildung und Forschung (BMBF) Federal Ministry of Education and Research; 2023.
- Schmidt R, Frank D. GreenH₂ Namibia Feasibility Study for Green Hydrogen in Namibia Report on desalination, brine treatment options, disposal options and its potential impacts on maritime life. Frankfurt: DECHEMA Gesellschaft für Chemische Technik und Biotechnologie.V. and ISOE –Institute for Social-Ecological Research; 2023.
- Dippenaar SC, et al. Environmental impact assessment for the proposed desalination project at mile 6 near Swakopmund, Namibia, 2009. Final scoping report. Stellenbosch: CSIR; 2009.
- Aladwani SH, Al-Obaidi MA, Mujtaba IM. Performance of reverse osmosis based desalination process using spiral wound membrane: sensitivity study of operating parameters under variable seawater conditions. *Cleaner Engine Technol*. 2021;5:100284.
- Yue M, et al. Hydrogen energy systems: a critical review of technologies, applications, trends and challenges. *Renew Sustain Energy Rev*. 2021;146:111180.
- Chatterjee S, Parsapur RK, Huang K-W. Limitations of ammonia as a hydrogen energy carrier for the transportation sector. *ACS Energy Lett*. 2021;6(12):4390–4.
- Rouwenhorst KHR, Lefferts L. Feasibility study of plasma-catalytic ammonia synthesis for energy storage applications. *Catalysts*. 2020;10(9):999.
- African Development Bank Group, Ca.E.R.D. Feed Africa. Abidjan: African Development Bank Group; 2019.
- FSIN and Global Network Against Food Crises, Global Report on Food Crises,. 2023. Rome: GRFC; 2023.
- Aliahmad A, et al. Knowledge evolution within human urine recycling technological innovation system (TIS): focus on technologies for recovering plant-essential nutrients. *J Clean Prod*. 2022;379:134786.
- Simha P, Ganesapillai M. Ecological sanitation and nutrient recovery from human urine: how far have we come? A review. *Sustain Environ Res*. 2017;27(3):107–16.
- Smith C, Hill AK, Torrente-Murciano L. Current and future role of Haber-Bosch ammonia in a carbon-free energy landscape. *Energy Environ Sci*. 2020;13(2):331–44.
- Udert KM, et al. Urea hydrolysis and precipitation dynamics in a urine-collecting system. *Water Res*. 2003;37(11):2571–82.
- Harder R, et al. Recycling nutrients contained in human excreta to agriculture: Pathways, processes, and products. *Crit Rev Environ Sci Technol*. 2019;49(8):695–743.
- Hilton SP, et al. Life cycle assessment of urine diversion and conversion to fertilizer products at the city scale. *Environ Sci Technol*. 2021;55(1):593–603.
- Badeti U, et al. Impact of source-separation of urine on effluent quality, energy consumption and greenhouse gas emissions of a decentralized wastewater treatment plant. *Process Saf Environ Prot*. 2021;150:298–304.
- Tidåker P, Mattsson B, Jönsson H. Environmental impact of wheat production using human urine and mineral fertilisers – a scenario study. *J Clean Prod*. 2007;15(1):52–62.

35. UNEP. Wastewater: Turning Problem to Solution - A UNEP Rapid Response Assessment. EB Emily Corcoran, K Thygesen, editors. Nairobi: United Nations Environment Programme; 2023. <https://wedocs.unep.org/20.500.11822/43142>.
36. Perez-Mercado LF, et al. Nutrient stocks, flows and balances for the Bolivian agri-food system: Can recycling human excreta close the nutrient circularity gap? *Front Environ Sci*. 2022;10:956325.

Publisher's Note

Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.