

Utilizing AE data and stochastic modelling towards fatigue damage diagnostics and prognostics of composites

Loutas, T.; Eleftheroglou, Nikos

Publication date

2016

Document Version

Accepted author manuscript

Citation (APA)

Loutas, T., & Eleftheroglou, N. (2016). *Utilizing AE data and stochastic modelling towards fatigue damage diagnostics and prognostics of composites*. Abstract from Aircraft Economics Working Group 2016, Toronto, Canada.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

Utilizing AE data and stochastic modeling towards fatigue damage diagnostics and prognostics of composites.

T.H. Loutas¹, N.Eleftheroglou²

*¹Applied Mechanics Laboratory, Department of Mechanical Engineering & Aeronautics,
University of Patras, 26500 Rio, Greece*

*²Structural Integrity & Composites Group, Aerospace Engineering Faculty, Delft University
of Technology, 2629 HS Delft, the Netherlands*

The procedure of damage accumulation in composite materials, especially during fatigue loading, is a complex phenomenon which depends on a number of parameters such as ply orientation, material properties, geometrical non-linearities etc. Towards condition based health monitoring and decision making, the need not only for diagnostic but also for prognostic tools rises and draws increasing attention the last few years. The damage process is in general hidden and manifests itself through in-situ structural health monitoring (SHM) data. Due to the hidden nature of the damage accumulation, non-homogenous hidden Semi Markov process (NHHSMP) seems to be a suitable candidate for describing adequately the aforementioned system's degradation in time. Its non-homogeneous aspect takes into account the system's ageing. Moreover, the sojourn times in each state are assumed to be generally distributed, not necessarily exponentially distributed, which is a more realistic assumption for real world engineering systems. The SHM observations are coming from acoustic emission (AE) data recorded throughout constant amplitude fatigue testing of open-hole carbon/epoxy coupons. The scatter of the cycles to failure reported is quite large, an expected result of the stochasticity in the material properties and material inhomogeneities. A maximum likelihood approach for the estimation of the model parameters is followed and useful diagnostic and prognostic measures such as the coupon's current degradation level as well as measures the coupon's remaining useful life (RUL) are proposed for the monitoring of structural integrity of composite materials.

Keywords: composite materials, structural health monitoring, stochastic modeling, fatigue, acoustic emission