


# **TOWARDS AN EVERLASTING ARCHITECTURE**

A never ending Story - Sustainability through Durability

by Lorenz Eschke



Inspiration

# Table of Contents

**Introduction + Relevance**

**Research**

**Design principle**

**Application of the design principle**


**Detailing + Climate**




A photograph of a large industrial facility, likely a cement or chemical plant. The image shows several large, curved, metallic pipes supported by a network of steel beams and ladders. In the center, there is a tall, cylindrical control tower with a blue translucent dome on top. The sky is filled with large, billowing white clouds. The overall scene conveys a sense of industrial scale and environmental impact.

# Embodied Carbon


## Distribution of the EC among the different Building Components




Case Study 1 - Office Building



Case Study 2 - Apartment Building



Case Study 3 - 41 Office Buildings




(Fernando et al., 2018)

(Fernando et al., 2018)

(Victoria et al., 2018)

### Case Study 3 - 41 Office Buildings





# Lifespan of Buildings

## End-of-Life in the Netherlands

When?

Most buildings in the Netherlands are demolished in the age between **75 and 120** years.

Mooiman & Van Nunen, 2012

Why?

Due to **physical, social** or **economic decay** --> in the Netherlands “**physical durability** turned out to be the **least decisive reason** for the end-of-life of buildings”

Thomsen & Straub, 2018




Most buildings are demolished even though they are **not yet physically obsolete**. This causes **additional carbon emissions** when a new building is constructed as a substitute.

**Pain 2**

## Relation of Lifespan and EC footprint

Calculated environmental performance of a single family house  
Deviation in % of RSL=75 years




"If a material **lasts ten times longer** than other materials, then the **environmental impact** of such material in principle counts, **only for one tenth**."

Mooiman & Van Nunen, 2012

# Housing Shortage in the Netherlands



## Forecast of the population in the Netherlands



## Housing Shortage Numbers


2021: **279.000** missing units

2024: **316.000** missing units expected



**low annual net addition** of dwellings,  
well below 1% in the Netherlands

## Pain 3.1

## Student Population in Delft



### Pain 3.2



**Embodied carbon** in buildings makes a significant contribution to **climate change**, accounting for 11% of total carbon emissions.

The building elements frame, sub-structure, upper floors and external walls, which largely consist of the building's **load-bearing structure**, as well as the **technical services** contribute to a **large part of the initial embodied carbon** (in the study by Victoria et al., 2018 it is over 80%).

## Pain 1: Embodied Carbon

Most buildings in the Netherlands are demolished even though they are **not yet physically obsolete**, but are socially or economically bad performing. This causes **additional carbon emissions** when a new building is constructed as a substitute. Studies have shown that the **environmental impact of long-lasting buildings is much lower**, as the initial embodied carbon invested is used for longer.

Experts also recommend a **longer service life** of dwellings in EU countries, as the **annual net addition** of new buildings is **too small** to meet the demand for housing.

## Pain 2: Lifespan of Buildings

The growing **housing crisis** in the Netherlands makes it difficult to find affordable housing, especially in the big cities and the Randstad. In the city of Delft, with a **rapidly growing student population**, there is **not enough housing** for students. However, this is necessary to meet the ambitions of the TU Delft to grow to the size of 40,000 students.


## Pain 3: Housing Shortage

The **construction industry** is a **major contributor** to **climate change**. To create sustainable and resilient architecture **longevity** should play a **major role**, as the **initial embodied carbon** could be **used for longer**. Furthermore, the **lifespan** of Dutch dwellings needs to be **extended** to **counteract** the **low annual net addition** of new buildings and the **housing shortage**.

## Problem Statement



# Strategy

## Shearing Layers - Steward Brand



# temporal


# eternal



# Context

# LIVING LAB

NATURE & TECHNOLOGY



## TU Delft Sustainability Goals


The TU Delft has the ambition to be **carbon neutral**, **climate-adaptive** and **circular**, with contribution to the **quality of life and biodiversity**, by **2030**.






# Program

## Project is dedicated to Students - What do students need?



## 1. Strategy

The focus, as explained in the previous chapters, lies on the design of a very durable building through the combination of long-lasting building elements that form the structure and temporal ones. This should simultaneously achieve a low environmental impact and the greatest possible adaptability for the future.




## 2. Context

This project can be considered a major experiment. Therefore, a university context is ideally suited to monitor and analyze the results that accumulate over time and eventually incorporate them into the teaching of future generations of engineers and architects.

Since the TU Delft in particular has the ambition "to be carbon neutral, climate-adaptive and circular, with contribution to the quality of life and biodiversity, by 2030", the campus in Delft was chosen as the context for this project. It is also considered as a "Living Lab" where new innovative ideas can be tested to contribute to this goal.

## 3. Program

As this project is dedicated to students, it is primarily about meeting their needs. As shown in the problem statement, there is too little accommodation for students in Delft. Therefore, a part of the building will be used for student housing in different unit sizes. Furthermore, with the growing number of students, new educational space is needed. Since the campus is immensely large and there is not really a recreational offer besides the sports facility X, a public leisure function will be integrated into the project, so that students from all faculties can be attracted.



## Design Question

How to design a **multifunctional building** on campus that **rethinks the typical timescales** of architecture and provides a **sustainable alternative** to construction methods with a low initial carbon footprint (such as timber construction) by using a **durable structure** and **passive measures** while remaining **highly adaptable** to future changes in its requirements?

# Research

## Research Question

Which **material** is best suited to create a **durable** and therefore sustainable **structure** for the design?

Sub question:

Which **material** is the best for integrating **passive measures** to **minimise active services** and the embodied carbon associated with them?

## Methodology - Definition of Requirements/Disciplines

### Physical Requirements

- **Durability:** The structure is very durable and needs minimal maintenance.
- **Repair options:** It is easily possible to repair the structure in case of damage.

### Environmental Requirements

- **Environmental impact:** The GWP of the structural material is considered and put into perspective with the possible lifespan.
- **Passive measures:** Possibilities for passive measures for instance thermal mass and transmittance of the material are considered.

## Methodology - Case Studies

### Historical Case Studies



**Pantheon**  
Rome, Italy  
Concrete  
Built ~128 AD  
~1896 years old



**Aula Palatina**  
Trier, Germany  
Brick Masonry  
Built ~312 AD  
~1712 years old



**Horyuji Temple**  
Ikaruga, Japan  
Wood  
Built ~670  
~1354 years old


### Contemporary Case Study



**Building Simply, Florian Nagler**  
Bad Aibling, Germany  
Concrete, Brick Masonry, Wood  
Built 2019-2020  
~3 years old

# Pantheon


Rome, Italy  
Concrete  
Built ~128 AD  
~1896 years old



Pantheon Section



Pantheon, Rome



Pantheon Floor Plan



Pantheon Dome


## Damages

- damages and replacements in brick envelope of opus latericum
- cracks in dome (probably soon after construction, so almost as old as the building itself)
- despite the cracks the structure is in very good condition



Pantheon external Wall





Damages 'opus latericum'



Display of Cracks in Pantheons Dome


## Opus Caementicium + modern equivalents

- opus caementicium has self-healing abilities
- small lime clasts in matrix that don't fully react initially
- in case of crack, the lime reacts with water and 'heals' the crack




## Aula Palatina


Trier, Germany  
Brick Masonry  
Built ~312 AD  
~1712 years old




Aula Palatina, Trier



Interior Space



Ancient Complex



Basilica, Antiquity




Fortress, Middle Ages



Palace Complex, Renaissance

## Damages

- demolition of east and south wall in Renaissance
- only half of original brick walls remained
- bomb attack in WWII but the structure survived with smaller damages



Remaining Walls




Destruction by WWII Bomb Raid




Destruction by WWII Bomb Raid

## "A Reconstruction of a Reconstruction of a Reconstruction"


- repairs over the centuries resolve in patchwork as some bricks and mortar joint have definitely been replaced
- today's structure is in good condition but only due to constant repair
- although most damages were man-made so probably the structure would not have needed the repairs



Original West Wall



Repairs



Repairs

## Horyuji Temple

Ikaruga, Japan  
Wood  
Built ~670  
~1354 years old

- complex partly burned down multiple times (vulnerability against fire)

-> high fire protection standards



West District

## Damages


- central trunk of pagoda is rotten (vulnerability against moisture)
- the replacement of damaged wooden parts is completely natural and planned from the initial stage -> replacement more often but also very easily doable
- the structure of the pagoda is despite the rotten central trunk in good condition although it is hard to say to which extent the wood has been replaced in the past



Pagoda



Pagoda Structure



Wrong Assumption of Trunk since its rotten and not load-bearing



Arcade, worn out Wood


**Buidling Simply, Florian  
Nagler - Research  
Houses Bad Aibling**

Bad Aibling, Germany  
Concrete, Brick Masonry,  
Wood  
Built 2019-2020  
~3 years old




Arcade, worn out Wood

## Global Warming Potential



GWP total



GWP per Building Element

## Solid Walls

Thickness  
U-Value  
Thermal Mass

**30** cm + Skin  
**0,22** W/m<sup>2</sup>\*K  
**3300** [Wh/K per room]

Thickness  
U-Value  
Thermal Mass

**42,5** cm + Plaster  
**0,25** W/m<sup>2</sup>\*K  
**4400** [Wh/K per room]

Thickness  
U-Value  
Thermal Mass

**50** cm  
**0,35** W/m<sup>2</sup>\*K  
**5600** [Wh/K per room]



U-Value + Thickness

## Final Matrix

## Conclusion

Which **material** is best suited to create a **durable** and therefore sustainable **structure** for the design?

Answer: Concrete is best suited, especially the modern **equivalent** to **Opus Caementicium** (D-Lime) is promising because of its self-healing abilities.

Which **material** is the best for integrating **passive measures** to **minimise active services** and the embodied carbon associated with them?

Answer: Since **thermal mass** is most relevant in terms of passive measures for this project, **concrete** is best suited.

	Concrete	Masonry	Wood
Historical Case Studies	Pantheon	Aula Palatina	Horyuji Temple
Age [years]	- built 128 AD - 1896 years old	- built 312 AD - 1712 years old	- built 670 - 1354 years old
History (changes, destruction, repair, replacement on structure)	<ul style="list-style-type: none"> <li>- crack in foundation (during construction)</li> <li>- damages and replacements in brick envelope of opus latericum</li> <li>- cracks in dome (probably soon after construction, so almost as old as the building itself)</li> <li>- small manmade passage trough load-bearing wall</li> <li>- potentially self-healing because of the lime clasts in the cementitious matrix</li> </ul>	<ul style="list-style-type: none"> <li>- destroyed by Germanics but structure remained</li> <li>- conversion into fortress</li> <li>- demolition of east and south wall in Renaissance</li> <li>- bomb attack in WWII but the structure survived with smaller damages</li> <li>- repairs over the centuries resolve in patchwork as some bricks and mortar joint have definitely been replaced</li> </ul>	<ul style="list-style-type: none"> <li>- complex partly burned down multiple times (vulnerability against fire)</li> <li>-&gt; high fire protection standards</li> <li>- central trunk of pagoda is rotten (vulnerability against moisture)</li> <li>- the replacement of damaged wooden parts is completely natural and planned from the initial stage</li> <li>-&gt; replacement more often but also very easily doable</li> <li>- major restoration works in 1374 AD, 1603 AD, and in the mid-20th century</li> </ul>
Condition of Structure	- despite the cracks the structure is in very good condition	<ul style="list-style-type: none"> <li>- todays structure is in good condition but only due to constant repair</li> <li>- although most damages were manmade so probably the structure would not have needed the repairs</li> <li>- „reconstruction of a reconstruction of a reconstruction“</li> <li>- 2 of the 4 walls remain the roman original as well as some plaster</li> </ul>	<ul style="list-style-type: none"> <li>- the structure of the pagoda is despite the rotten central trunk in good condition although it is hard to say to which extent the wood has been replaced in the past</li> <li>- assumption that most of the wood is original</li> </ul>
Contemporaly Case Study	Building simply concrete house	Building simply masonry house	Building simply solid timber house
GWP/surface area [kg CO <sub>2</sub> eq/m <sup>2</sup> ]	4,00	3,93	3,13
Thermal Mass [Wh/K per room]	5600	4400	3300
U-Value [W/m <sup>2</sup> K]	0,35	0,25	0,22
Wall Thickness [cm]	50	42,5	30


# Design principle

**eternal**

**temporal**

— eternal


— temporal



## eternal concrete table

— eternal


— temporal




**permeability**

— eternal


— temporal



**could be flooded**




**parking underneath**




**independent volumes underneath**




**table as one volume**




**park on top**




**insulated volumes on top**




**connected through cores**




**temporal skin + slabs, vertical flexibility**




### horizontal extensions and vertical connections






potential development in 75 years




**potential development in 150 years**

## Generic Space




generic space between core and columns



smallest possible division into 16 units


**eternal**

**temporal**




**eternal**


**temporal**




**eternal**




casted concrete core




casted concrete table/foundation




**eternal**




**eternal**




**temporal**




**eternal**




**temporal**




eternal




prestressed hollow core slabs




casted concrete core




casted concrete table/foundation



temporal




wooden beams




prestressed hollow core slabs for parking


**eternal**




**temporal**




**eternal**




**temporal**





eternal




temporal




eternal




temporal




eternal




temporal




eternal




prestressed hollow core slabs



prefab concrete columns/beam




casted concrete core




casted concrete table/foundation


temporal




solar panel, facade greening element




balconies




prefab timber frame facade elements




prefab polycarbonate/timber frame boxes, assembly on site




steel skeleton



wooden box element slab



wooden beams



prestressed hollow core slabs for parking



P5 Presentation - AE - Towards an everlasting Architecture




Lorenz Eschke





P5 Presentation - AE - Towards an everlasting Architecture





Lorenz Eschke



**horizontal extensions/vertical connections**




**eternal table with 4 towers - urban system in itself**




## growable towers


## eternal




hollow core slabs



prefab concrete columns/beam





casted concrete core




casted concrete table/foundation

## temporal


### modular, low carbon




prefab timber frame facade elements



prefab polycarbonate/timber frame boxes, assembly on site





wooden beams




wooden box element slab


### modular, reusable



cladding: fibre cement board




steel skeleton



balconies in different sizes and executions, permeable/water-tight, integrated privacy screen + plant pot

## categorization

eternal



Pantheon

“eternal” concrete cast that does not  
need to be repaired or changed  
- use of roman concrete/modern equiv-  
alent with self-healing abilities



temporal



Horyuji Temple

modular wooden construction in which parts can  
be repaired, replaced or changed when needed

## historical case studies as role models




Le Corbusiers Plan Obus, Algiers - structure becomes land

# **Application of the design principle**


Figure Ground Plan

1|5000



## Typologies and Heights

1|5000



## Green Spaces and Water


1|5000



Cemetery



Mekelpark



## Campus Real Estate Vision for 2030

1|5000

█ Densification Possibilities

— Tram Line

● Tram Stop

— Bike Lane

Student housing + parking garage

Potential transformation into housing



## Faculties + Gathering Spaces

1|5000

- Gathering/Leisure Space for Everyone
- Faculties + Gathering Spaces



## Faculties + Gathering Spaces

1|5000


- Gathering/Leisure Space for Everyone
- Faculties + Gathering Spaces




## Personal Vision


1|5000

- Gathering/Leisure Space for Everyone
- Connection via Green Space
- New Building that encloses Green Space







**status quo**




**V1 - full table**




**V4 - incomplete table**




**V2 - full table**




**V5 - incomplete table**




**V3 - full table**



**V6 - incomplete table**



**incomplete table**



## design proposal






figure ground plan




site plan






**network of public space/green**





## vertical connections







forest

field


nature contrast













groundfloor with surroundings






groundfloor




2nd floor







3rd floor





section A-A




**section B-B**




4th floor, educational with roof terrace




5th floor, educational/potentially office




section A-A







12th floor, 16 units same size



12th floor, maisonette flat 1|100



11th floor, maisonette flat 1|100




section C-C








9th floor, communal space




9th floor, common spaces 1|100




section C-C






section C-C



section A-A



section A-A



# Facade



elevation north - west



elevation south - west














P5 Presentation - AE - Towards an everlasting Architecture




Lorenz Eschke

# **Detailing**





Roof:


- substrate, 200mm
- filter fleece
- drainage mat, 100mm
- double-layer bitumen membrane
- foam glass insulation, 2x 100mm
- single-layer membrane
- hollow floor slab, 200mm
- suspended ceiling for installations



Facade:

- fibre cement board, 20mm
- horizontal aluminium profile, 40mm
- vertical aluminium profile, 40mm
- airtight sealing foil
- osb plate 15mm
- timber frame with stud and railings 180mm, insulation: mineral wool
- OSB plate, 15mm
- vapour barrier PE film
- anchoring to concrete / second layer of insulation 100mm
- gypsum fibreboard 12,5mm







Floor flats:



- wooden planks, 20mm
- heated screed, 50mm
- single-layer membrane
- foam glass impact sound insulation, 40mm
- 2nd layer of impact sound insulation, 35mm + embedded stiffening for hollow core elements
- pre stressed hollow core concrete planks 200mm

Hung-in extension box:


- six-layer polycarbonate multi-wall sheeting with tonged + grooved joints 40 mm (1.1-1.2 W/m<sup>2</sup>K)
- square hollow-section aluminium supporting construction, 50/50/4 mm
- steel flat supports, 10 + 10 mm
- steel RHS column, 180/100 mm
- steel flat supports, 10 + 10 mm
- triple glazed Okatherm (by Okalux) fixed glazing, reduced UV transmission (0.5 W/m<sup>2</sup>K)







# Climate



climate diagram

