


# The modular post-earthquake shell

A multi-objective parametric structural design approach

Joanne Jimmink

# INTRODUCTION





























# PROJECT



structural  
validity




sustainability



aesthetics





constructability



seismic  
resistance










## EXAMPLE


4 columns	steel	2 floors
6 columns	concrete	3 floors
8 columns	timber	4 floors
10 columns	glass	5 floors
	masonry	
	aluminium	







## AUTOMATED DATABASE GENERATION








## MANUAL OPTIMISATION


















GRID SIZE

7×




CONNECTIONS

2×





IN-PLANE

3x




OUT-OF-PLANE

3×



126  
variations



## ELEMENTS

STEEL

Lower strength

$I7 \times$



Higher strength

$2I \times$

TIMBER



Lower strength (local)

$I6 \times$



Higher strength (imported)

$I6 \times$




SPECIAL

STEEL TRUSS


*in timber structure*

$3 \times$





16 884  
variations










PERMANENT













## STRENGTH vs. LOADS

Is the design strong enough?


$$\frac{\tau_d}{f_{v,d}} \leq 1$$

$$\frac{\sigma_{t,0,d}}{f_{t,0,d}} + \frac{\sigma_{m,y,d}}{f_{m,y,d}} + k_m \cdot \frac{\sigma_{m,z,d}}{f_{m,z,d}} \leq 1$$

$$\frac{\sigma_{t,0,d}}{f_{t,0,d}} + k_m \cdot \frac{\sigma_{m,y,d}}{f_{m,y,d}} + \frac{\sigma_{m,z,d}}{f_{m,z,d}} \leq 1$$

$$\left(\frac{\sigma_{c,0,d}}{f_{c,0,d}}\right)^2 + \frac{\sigma_{m,y,d}}{f_{m,y,d}} + k_m \cdot \frac{\sigma_{m,z,d}}{f_{m,z,d}} \leq 1$$

$$\left(\frac{\sigma_{c,0,d}}{f_{c,0,d}}\right)^2 + k_m \cdot \frac{\sigma_{m,y,d}}{f_{m,y,d}} + \frac{\sigma_{m,z,d}}{f_{m,z,d}} \leq 1$$




# ENVIRONMENTAL IMPACT




## Environmental impact per kg structure


Exclusion:  
Chestnut


10 836  
variations





## JOINT



Environmental impact per joint









10 836  
variations


# ALL MODELS




10 836  
variations




4 788  
variations





2016  
variations



4 032  
variations








structural checks

*O.K.*




## ALL MODELS



10 836  
variations

## STRUCTURAL CHECKS


*NOT O.K.*



9 335  
variations

## STRUCTURAL CHECKS

O.K.




1 501  
variations

## EXCLUSION 2


element weight  
 $< 40 \text{ kg}$




## REMAINING MODELS



1 501  
variations



1 124  
variations




377  
variations

## EXCLUSION 3


environmentally friendly  
*top 5%*



## REMAINING MODELS




377  
variations



349  
variations

## ENVIRONMENTAL IMPACT


<5%



28  
variations

# ENVIRONMENTAL IMPACT

<5%




28  
variations


aesthetical value  
*ranking*



## RANKING




\*\*\*\*\*




\*\*\*\*\*



\*\*\*




\*\*




\*




## RANKING




\*\*\*\*\*




\*\*\*\*\*



\*\*\*




\*\*




\*


## RANKING




★★★★★




★★★★★



★★★




★★



★


## REMAINING MODELS



28  
variations


## RANKING

<★★★




13  
variations

## RANKING




15  
variations

## REMAINING MODELS




15  
variations


## TOP 3





TOP 3




TOP 1








## BOLT CONFIGURATION







## JOINT CHECKS




TOP 1

*O.K.*










$$F = m \cdot a$$

*force = mass · acceleration*





## EIGENMODES




## EIGENMODES STRUCTURE



## EIGENMODES STRUCTURE



## SEISMIC LOAD






$$F = m \cdot a$$


*force = mass · acceleration*

## MODAL ANALYSIS



mass  
per mode







$$F = m \cdot a$$

*force = mass · acceleration*


## MODAL ANALYSIS








$$F = m \cdot a$$

*force = mass · acceleration*





TOP 1


*O.K.*





# CONCLUSION











structural  
validity



sustainability





aesthetics





constructability



seismic  
resistance







THE END