




Intervention
1/200
Ground Floor





Intervention
1/200



North Facade



First Floor






East Facade




South Facade






Intervention
1/5




Detail 1

- 1 Heat exchange (air to water)
- 2 Existing structure- reinforced concrete
- 3 Air outtake 1F
- 4 Air outtake GF
- 5 Insulation XPS 100mm
- 6 Cement board 12 mm
- 7 C shaped aluminum
- 8 Clean and apply cement if stain unremovable
- 9 Double glazing




Detail 4

- 1 Aluminum double glazing window frame with existing 2° roof slope
- 2 HSS. 150mm 50 mm 7mm
- 3 L-shaped steel. Equal angle 150mm
- 4 Leveling cement if needed
- 5 Insulation XPS 100mm
- 6 Foam sealant
- 7 Aluminum flushing
- 8 Existing structure- reinforced concrete
- 9 Original steel window frame. Needed to be retreated and reinstalled




Detail 2

- 1 Double glazing
- 2 Insulation XPS 100mm
- 3 C-shaped aluminum
- 4 Wooden flooring
- 5 Floor heating
- 6 Sound insulation
- 7 Existing structure- reinforced concrete
- 8 Clean and apply cement if stain unremovable
- 9 Air outtake GF




Detail 5

- 1 Single glazing
- 2 Water tank (The water is used for controlling incoming air temperature and humidity. Water temperature range is from 15°C -23°C, year round.)
- 3 Existing structure- reinforced concrete



Detail 3

- 1 Polymer mortars for larger damage
- 2 Existing foundation- reinforced concrete



Detail 6

- 1 Prefabricated concrete base
- 2 Leveling cement if needed
- 3 Existing structure- reinforced concrete