Affective window: a seamless interaction between switchable glazing and the occupant


Sustainable Design Graduation studio Christianne Neeltje Luijten, TU Delft 4474732


Supervisors:

Mauro Overend, TU Delft Regina Bokel, TU Delft

External advisors:

Mark Allen, University of Cambridge Alessandra Luna-Navarro, University of Cambridge





EU's total CO₂ emissions






Figure: EU's total CO₂ emissions (European Commission, 2013)

A building's energy use



Source: A building's energy use during its lifecycle (Adalbert, 1997)

Energy consumption breakdown



Typical energy distribution

Glazed façades unnecessary blinds closed






30% of the time the blinds are closed


75% of the time the blinds are closed unnecessary


Figure: Glazed façades (Photo by Maciej Lulko)

New dynamic façade technologies



Visual discomfort





Disability glare
Discomfort glare

Glare










Occupants' comfort



Economic impact




Energy costs (1%)

Economic impact



- Energy costs (1%)
- Rental costs (9%)

Economic impact



- Energy costs (1%)
- Rental costs (9%)
- Staff costs in salaries and benefits (90%)

16

Figure: World Green Building Council report: typical business operating costs (WorldGBC, 2014)

Posed problem



"The existing building technologies of automated systems controlling the amount of daylight through glass often fail to correlate with the occupant's (visual) comfort."

Project aim

Effectively controlling switchable glazing:

Improving visual comfort for the occupant

By minimising glare, and optimising the use of daylight and availability of view

Research Question

Main question:

"How can an automated system, consisting of switchable glazing and a system that can sense the needs of the occupant, be used to control glare in an effective manner?"

Key performance indicators of "effective"

non-disruptive

optimize the use of daylight

enhance the energy performance of the building

increase the visual comfort


increase availability of view

benefit health and well-being of the occupant


increase the productivity


reduce visual discomfort, glare

Control system



The Face





OpenFace



Facial Action Coding System



AU01 Inner Brow Raiser



Outer Brow Raiser



AU04 Brow Lowerer



AU05 Upper Lid Raiser



AU06 Cheek Raiser



AU07 Lid Tightener



AU09 Nose Wrinkler



AU10 Upper Lip Raiser



AU12 Lip Corner Puller



AU12 Dimpler



AU15 Lip Corner Depressor



AU17 Chin Raiser



AU20 Lip stretcher



AU23 Lip Tightener



AU23 Lips part



AU26 Jaw drop



AU28 Lip Suck



AU45 Blink

Facial Action Coding System



AU01 Inner Brow Raiser



AU02 Outer Brow Raiser



AU04 Brow Lowerer



AU05 Upper Lid Raiser



AU06 Cheek Raiser



AU07 Lid Tightener



AU09 Nose Wrinkler




AU10 Upper Lip Raiser



AU12 Lip Corner Puller



AU12 Dimpler



AU15 Lip Corner Depressor



AU17 Chin Raiser



AU20 Lip stretcher



AU23 Lip Tightener



AU23 Lips part



AU26 Jaw drop



AU28 Lip Suck




25

AU45 Blink


Source: User-centred Control of Automated Shadign for Intelligent Glass Facades


Action Units



Source: User-centred Control of Automated Shadign for Intelligent Glass Facades

Light







Wearable Light Sensors






Switchable Glazing





Switchable Glazing: Merck Eyrise



Switchable Glazing: Merck Eyrise



The Novel System




The Novel System



The Novel System




Experimental set up




Source: Kent (2019), Berman (1994)

Experimental set up




Source: Kent (2019), Berman (1994)

Experimental set up



Source: Kent (2019), Berman (1994)


Artificial Glare source: Projection













Opacity 10%

Opacity 30%

Opacity 50%

Opacity 70%

Opacity 90%

Experiment I: Objectives

Objectives:

Developing the physical characteristics for Experiment II


Indicating what setting the participants may find comfortable and what not

Evaluating if the source can create glare


Indicating and verifying threshold values

Experiment I: Participants

A number of 14 participants, of which 11 females and 3 males took part in this study




Initial survey




Perform tasks


Exposed to glare source




Interval: glare source off for 2 minutes
Choose level of discomfort

Imperceptible, Perceptible, Disturbing, Intolerable





Threshold Values



Experiment I: Discussion

Different tasks at different moments

The order

The anchor point

Experiment I: Conclusion

White circle projected by the artificial glare with an opacity of 90% can be sufficient to provide a level of discomfort glare

Threshold values are set

Method to link the time of the data

Eye level of participants should be the same height

Same visual tasks

Experiment II: Objectives


Compare the Novel system with the Benchmark system


Test the effectiveness of the Novel sytem


Identify extra Action Units that show a response to light


Experiment II: Participants


A number of 16 participants, of which 11 females - and 5 males took part in this study.












	Several minutes	4 minutes	6 minutes Exposure to glare source	10 minutes Interval	6 minutes Exposure to glare source	Several minutes
Participant enters	Participant fills in survey i	Participant starts task sheet				Break Participant fills in survey ii



Experimental procedure, one half (26 minutes)

Glass state
Benchmark

Glare
Source
Source
Glare
Source
State

Glare
Source
State

Glare
Source
State

Data retrieved from:

Tasks

OpenFace

Lux Sensor

Surveys

Glass state: view and daylight

Task sheets:

124 mathematical questions
Same difficulty
Randomized order

Scores compared:

made correctness mistakes

More questions made and correct during Benchmark condition Less mistakes during Novel condition

Openface
AU02_r - Outer Brow Raiser



AU02 Outer Brow Raiser

Extra AU's:



AU01 Inner Brow Raiser



AU04 Brow Lowerer



AU07 Lid Tightener




AU09 Nose Wrinkler





AU02


Outer Brow Raiser












Lux readings 3 participants during Benchmark conditions

one half (26 minutes)


Fluctuating





Lux readings too low

most likely covered by **obstacle**



Scoring system

Glass State: Benchmark condition

Glass State: Novel condition Participant 1

	Benchmark	Novel	Benchmark	Novel	Novel
	Daylight	Daylight	View	View	View (-5, 7, 15)
Mean	83%	79%	64%	62%	71%

Survey ii

Preference:

9 participants responded: No Difference

4 participants responded: The Novel

3 particpants responded: The Benchmark

Experiment II: Discussion

Tasks - Productivity

Not a sufficient amount of people Too short experiment

Lux Sensor

Different Angles
Obstacle

Occupant response

Regarding level of discomfort

Scoring system

Experiment II: Discussion

More data:

(i) gathering the occupant's response in real time, Imperceptible, Perceptible, Disturbing, Intolerable (make image for these things)?

(ii) investigate each individual via machine learining, statistical analysis

(iii) the light should be measured via more sensors in different places

Light sensor at eye level

(iv) The experimental set up mirrors an actual office building
To enhance correlation and with real sun light is important

Conclusion

Main question:

"How can an automated system, consisting of switchable glazing and a system that can sense the needs of the occupant, be used to control glare in an effective manner?"

By taking the occupant in the loop; by adding Facial Action Units to the control system, with emphasis on the Eyebrow Movement



Conclusion

Main question:

"How can an automated system, consisting of switchable glazing and a system that can sense the needs of the occupant, be used to control glare in an effective manner?"

After **evaluating** the key indicators for **effectiveness**

At current stage Novel system appears to be no worse, then the Benchmark system

More data is needed

Translating the system into real offices



Translating the system into real offices



Privacy concerns:

- 1. not recording when their is no occupant
 - 2. not via internet
- 3. delete recording after several minutes


Multiple occupants:

Interesting to explore: who is controlling the glazing

Thank you for listening


Any questions?

Energy consumption breakdown




Typical energy distribution

Population growth



Glare Assesment



Daylight Glare Probability

Daylight Glare Index Rating

0.257

22.37

26



Increasing brightness of artificial glare source Glass state: always bright

