

Decarbonising Industry via BECCS

Promising Sectors, Challenges, and Techno-economic Limits of Negative Emissions

Tanzer, S.E.; Blok, K.; Ramírez, A.

DOI

[10.1007/s40518-021-00195-3](https://doi.org/10.1007/s40518-021-00195-3)

Publication date

2021

Document Version

Final published version

Published in

Current Sustainable/Renewable Energy Reports

Citation (APA)

Tanzer, S. E., Blok, K., & Ramírez, A. (2021). Decarbonising Industry via BECCS: Promising Sectors, Challenges, and Techno-economic Limits of Negative Emissions. *Current Sustainable/Renewable Energy Reports*, 8(4), 253-262. <https://doi.org/10.1007/s40518-021-00195-3>

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.



Decarbonising Industry via BECCS: Promising Sectors, Challenges, and Techno-economic Limits of Negative Emissions

S. E. Tanzer¹ · K. Blok¹ · A. Ramírez¹

Accepted: 20 August 2021
© The Author(s) 2021

Abstract

Purpose of Review This paper reviews recent literature on the combined use of bioenergy with carbon capture and storage (BECCS) in the industries of steel, cement, paper, ethanol, and chemicals, focusing on estimates of potential costs and the possibility of achieving “negative emissions”.

Recent Findings Bioethanol is seen as a potential near-term source of negative emissions, with CO₂ transport as the main cost limitation. The paper industry is a current source of biogenic CO₂, but complex CO₂ capture configurations raise costs and limit BECCS potential. Remuneration for stored biogenic CO₂ is needed to incentivise BECCS in these sectors. BECCS could also be used for carbon-neutral production of steel, cement, and chemicals, but these will likely require substantial incentives to become cost-competitive. While negative emissions may be possible from all industries considered, the overall CO₂ balance is highly sensitive to biomass supply chains. Furthermore, the resource intensity of biomass cultivation and energy production for CO₂ capture risks burden-shifting to other environmental impacts.

Summary Research on BECCS-in-industry is limited but growing, and estimates of costs and environmental impacts vary widely. While negative emissions are possible, transparent presentation of assumptions, system boundaries, and results is needed to increase comparability. In particular, the mixing of avoided emissions and physical storage of atmospheric CO₂ creates confusion of whether physical negative emissions occur. More attention is needed to the geographic context of BECCS-in-industry outside of Europe, the USA, and Brazil, taking into account local biomass supply chains and CO₂ storage siting, and minimise burden-shifting.

Keywords BECCS · Negative emissions · Steel · Cement · Ethanol · Paper · CO₂ capture

Introduction

We emitted 59 billion tonnes (CO₂eq) of greenhouse gases in 2019 [1], yet limiting catastrophic climate change requires global emissions to be net-zero within the next few decades. Results from integrated assessment models (IAMs) indicate that, beyond rapidly reducing emissions, this transition will require permanently removing greenhouse gases (GHGs) from the atmosphere, or “negative emissions”, to

compensate for residual or historic emissions [2]. One of the most studied potential negative emission technologies is bioenergy with carbon capture and storage (BECCS). In a BECCS system, CO₂ is removed from the atmosphere via biomass, which is then combusted for energy. The resulting biogenic CO₂ is captured and permanently stored, such as in a geologic formation, and the biomass is regrown. BECCS can result in negative emissions—that is, a decrease in atmospheric CO₂—if, and only if, more biogenic CO₂ is permanently stored than CO₂ is emitted throughout the supply chains of biomass cultivation and use and of CO₂ capture and storage [3•].¹

IAMs typically assume BECCS deployment in the power sector and/or for biofuel production [2, 4]. However, the

This article is part of the Topical Collection on *Deep Decarbonization: BECCS*

✉ S. E. Tanzer
s.e.tanzer@tudelft.nl

¹ Faculty of Technology, Policy, and Management, Delft University of Technology, Delft, Netherlands

¹ BECCS systems do not necessarily result in negative emissions. Thorough cradle-to-grave accounting of GHG emissions and removals is a critical step to determine whether net removal actually occurs.

Table 1 Overview of major CO₂-emitting industries and their current use of bioenergy and CO₂ capture [5, 6, 8, 9]

Industry	Direct CO ₂ emissions (2019, global)	Status of biomass use	Status of CO ₂ capture
Cement	2300 Mt fossil 30–80 Mt biogenic ¹	Commercial, with individual kilns firing up to 35–40% biomass, typically wastes [11]	Demonstration, up to 75 kt/year
Steel	2100 Mt fossil	Commercial partial replacement of coal with charcoal. Primarily used in small-scale production in Brazil	Demonstration for blast furnace steelmaking. Commercial for direct reduced iron steelmaking
Petrochemical refining	1400 Mt fossil	Early commercialisation for methanol (1 facility) and biomass-to-liquids from biowastes (multiple facilities under construction)	Commercial for methanol and coal-to-liquids, up to 100 kt/year
Paper	200 Mt fossil 700–800 Mt biogenic ²	Commercial. Process is inherently biobased. Residues used for cogeneration of heat and electricity	Demonstration, 11 kt/year [16]
Ethanol	82 Mt biogenic ³	Commercial. Process is inherently biobased, with maize and sugarcane as primary feedstocks. Sugarcane bagasse is used for cogeneration of heat and electricity. Early commercialisation of fermentation of cellulosic biomass	Commercial for capture of high-purity fermentation CO ₂ , including 1 Mt/year to dedicated storage

¹Three to six percent of biogenic fuel mix [10, 11], assuming 0.8–1.1 t CO₂/GJ [12]

²For an approximate global production of 400 Mt pulp [13], assuming an average biogenic CO₂ intensity of 1.9 t CO₂/t pulp [14, 15]

³Stoichiometrically, 82 Mt CO₂ from the fermentation of 86 Mt of ethanol in 2019 [17]

industrial sector, responsible for 20% of global GHG emissions [1], including 8.5 Gt of CO₂/year [5], is a stronger candidate for near-term deployment. Currently, industry's bioenergy use is more than double that of power [6], and, so far, 95% of the CO₂ stored from large-scale CCS operations has been from industry [7]. Furthermore, industry is the expected source of many residual emissions in a net-zero society, as industry uses carbon as a feedstock, reducing agent, or other stoichiometric necessity, and while the use of bioenergy or CCS alone can significantly decrease CO₂ emissions, only in combination can they result in negative emissions.

In the past five years, 50 peer-reviewed papers² considered the combined use of biomass and CO₂ capture in the five largest CO₂-emitting industries: iron steel, cement, paper, platform chemicals, and transport fuels, whose CO₂ emissions and current status of biomass and CO₂ capture are summarised in Table 1.³ The papers reviewed broadly fall into three categories:

1. Retrofitting CCS into existing biomass-based industries as an early opportunity for negative emissions, compensating for CO₂ emitted elsewhere in society.

² See [supplementary information](#) for search queries used and descriptions of all literature reviewed.

³ While transport fuels are often assigned the energy sector, they are included here as manufactured energy storage products are distinct from the on-demand provision of energy. Due to space constraints, smaller industries, such as beverage manufacturing and ceramic and glass production, were excluded, as were industry-generic BECCS options, such as BECCS-hydrogen, BECCS-boilers, and CHP.

2. Retrofitting BECCS into carbon-intensive heavy industry, compensating for CO₂ emitted during production.
3. Integrating CCS into novel biobased production pathways for carbon-based chemicals (e.g. fuels, olefins), compensating for CO₂ emitted during product use or disposal.

In this work, we review the proposed configurations and challenges for BECCS-in-industry reported in these papers. We then discuss estimated costs and environmental impacts, focusing on the potential of negative emissions via BECCS-in-industry.

CCS for Existing Biogenic Industries

Some industries already use biomass as a feedstock and emit biogenic CO₂ during production. Notably, the production of bioethanol and paper emit over 800 Mt of biogenic CO₂ per year, not including CO₂ embodied in products. As such, the addition of CCS to these industries may by itself be sufficient to result in negative emissions.

The most discussed industry in the recent literature is bioethanol, often highlighted as a “low-hanging fruit” for BECCS [18–20, 21•, 22–30]. As the CO₂ released from ethanol fermentation is nearly pure (> 98 vol% [27]), it could be prepared for transport and storage via compression alone. Currently, 1 Mt/year of ethanol fermentation CO₂ is injected into dedicated geologic storage in Illinois and three more CCS projects are under development [8].

Bioethanol is typically produced from maize, sugarcane, or other starchy food crops. Alternatively, cellulosic biomass, such as grasses and coppice wood grown on less-arable land or agricultural wastes, can also be fermented. Currently, only a few ethanol distilleries produce cellulosic bioethanol, primarily from maize and sugarcane residues [31, 32]. However, several recent BECCS-in-ethanol studies envision dedicated facilities fermenting corn stover [33•, 34], switchgrass [33•, 34, 35], miscanthus [33•, 36], and wood [33•, 37•], with captured CO₂ sent to dedicated geologic storage.

Not all CO₂ from bioethanol production is as easy to capture as the high-purity CO₂ from fermentation. In Brazilian distilleries, sugarcane residues are combusted to cogenerate heat and electricity, producing up to 90% of total distillery CO₂ in dilute flue gas streams, the capture of which was explored by [19, 20, 21•, 26], all assuming post-combustion amine-based capture, whose energy demand was estimated to reduce distillery electricity exports by 50–75% [19, 20, 26].

Pulp and paper mills also cogenerate heat and electricity, and the biogenic CO₂ from the combustion of process wastes typically accounts for over 75% of on-site emissions [38, 39]. Flue gases are typically less than 20% CO₂ and distributed between several point sources [38, 40, 41, 42•, 43, 44]. Some studies estimated that energy demand of full CO₂ capture can switch paper mills from being net energy exporters to energy importers [43] or require supplemental fuel [42•, 45]. If only on-site energy is used, estimates of capturable CO₂ ranged from less than 30% in [42•, 44], to 90% (with an 80% reduction in electricity exports) in [45], for post-combustion amine-based capture. Two studies [39, 43] considered the integration of a calcium looping CO₂ capture unit⁴ into the lime kiln⁵ of a pulp mill, which could lower the net energy intensity of CO₂ capture.

Despite these challenges, BECCS-in-paper could be particularly significant in the USA, whose mills produce a quarter of the world's paper [13], with biogenic CO₂ accounting for over 115 Mt CO₂/year [42•] and in countries like Sweden, where pulp and paper mills account for over 60% (ca. 20 Mt CO₂/year) of large-scale CO₂ emitters [40, 46].

Retrofitting BECCS Into Carbon-Intensive Industries

BECCS could also be used in industries that are large CO₂ emitters but are not currently major biomass consumers, such as steel and cement, which together emitted 5.0 Gt CO₂

in 2018 [6]. While low-carbon production technologies are under development, they will not be available on a large scale for a few decades [6]. Retrofitting BECCS could allow existing steel mills and cement plants to continue operating at or near carbon neutrality.

Globally, over 70% of steel is produced in blast furnace mills [47] that use high-grade coal as a fuel and reducing agent, emitting around 2–3 t CO₂/t steel [48•, 49, 50] from the blast furnace and associated energy production. CO₂ capture in steel has been considered by a number of studies (e.g. [27, 51–53]) and demonstration facilities [8], and the use of charcoal as a partial coal replacement is common in Brazil [6, 54]. However, as blast furnaces rely on the mechanical properties of coal as a process control mechanism, biomass replacement is likely limited to around 30% of coal use in current large blast furnaces [49, 55].

Only five studies of the fifty studies reviewed considered BECCS for blast furnace steelmaking [48•, 50, 56, 57, 58•]. They estimated that partial charcoal use with full CCS could reduce steel mill emissions over 80% but was unlikely to compensate for emissions from charcoal production or CO₂ transport and storage to allow for negative emissions. Still, BECCS deployment at 30 EU steel mills could mitigate up to 200 Mt CO₂ per year [56]. However, this requires capturing CO₂ from most point sources within the mill. If capture is limited to the largest CO₂ source, the blast furnace itself, BECCS has the potential to reduce direct CO₂ emissions by approximately 50% [50, 56].

Other steelmaking methods are more amenable to BECCS. Direct reduction of iron (DRI), which accounts for 7% of global steelmaking [47], typically uses natural gas or gasified coal to reduce iron, and CO₂ capture can be integrated into reducing gas preparation. This is already the case at Emirates Steel in Abu Dhabi, where 0.8 Mt CO₂/year is captured for use in enhanced oil recovery (EOR) [8]. Combined with CCS, a biogenic reducing gas [59, 60] could theoretically allow for “carbon negative” DRI steel [48•, 50]. Similarly, BECCS in smelt reduction steelmaking routes, such as Corex and the under-development HIsarna process, which are also more fuel-flexible than blast furnace steelmaking, could also allow for carbon-neutral or -negative steel [50, 58•].

Like steel, cement production is also CO₂ intensive. At a cement plant, roughly 60% of the CO₂ emitted results from the calcination of limestone. This fossil CO₂ is stoichiometrically unavoidable and BECCS may be the only path to CO₂-neutral cement production [61, 62•].

CO₂ capture at cement plants currently operates on scales of 50–75 kt CO₂/year [6], and demonstration plants capturing 400–600 kt CO₂/year are under development [8]. Furthermore, cement kilns already partially co-fire biomass or biogenic wastes. An estimated 3–6% of global kiln fuel is

⁴ Calcium looping CO₂ capture works by cycling carbonation (CaO+CO₂→CaCO₃+heat) and calcination (CaCO₃+heat→CaO+CO₂) to first remove CO₂ from a gas stream, and then, in an oxygen environment, release a pure stream of CO₂ for capture.

⁵ Used to regenerate paper-making process chemicals.

Table 2 CO₂ abatement cost estimates of BECCS-in-industry, compared to cost estimates for CCS-in-industry, €₂₀₂₀/t CO₂.¹ Values in parentheses refer to cost of CO₂ capture only

	BECCS, this review (CO ₂ capture cost only)	BECCS [75]	CCS only [76]	CCS only [58•]	CCS only [51]	CCS only [27]	CCS only [77]
Ethanol, fermentation CO ₂ only	22–388 (11–31) [20, 21•, 22–24, 29, 78] ([18, 21•, 27, 28])	20–180	–	–	–	13	–
Ethanol, fermentation and cogen- eration CO ₂	47–120 (13–115) [20, 21•, 34, 78] ([21•, 34, 78])	–	–	–	–	–	–
Paper	82–95 (41–110) [40, 58•] ([38, 40, 41, 42•, 43, 46])	20–70	55–87	26–91	56–58	–	–
Steel	61–200 [48•, 56, 58•]	–	62–69	26–193	10–118	30–34	35–60
Cement	55–88 [58•]	–	55–110	10–132	17–163	25–40	30–65
Drop-in transport fuels	68 [65]	20–40	–	–	–	–	–
Olefins and mixed chemicals	13–102 [58•, 74]	–	153–200	23–230	28–247	96	35

¹Costs have been standardised to €₂₀₂₀ by first adjusting for inflation in the source currency and then converting to Euros. If no basis-year was provided, the annual average for the year preceding the publication year was assumed

biogenic, with individual kilns co-firing up to 37% biomass [10, 11].

Despite this, only four studies in the past 5 years explicitly consider BECCS-in-cement [58•, 61, 62•, 63]. Tanzer et al. concluded that CO₂-negative cement and concrete are plausible via fully charcoal-fired cement kiln with post-combustion CCS [62•]. Two other studies concluded that partial biomass use with CCS can reduce emissions over 70% [58•, 61].

BECCS-Integrated Biochemical Production

The chemical sector emitted 1.4 Gt CO₂ in 2018 from direct energy use and process emissions [6], but half of its carbon inputs leaves as products, such as fuels, fertilisers, and olefins, which then release CO₂ during use or disposal. Both CCS integration and biobased production are under development to reduce the net CO₂ of chemical production [6], and some biobased production pathways also integrate CCS into their designs, aiming for carbon-neutral [58•, 64•] or carbon-negative [65–71] production.

The majority of these studies focus on biomass gasification technologies [58•, 64•, 66–68, 72–74]. Biomass gasification breaks the biomass into its component parts (H₂, H₂O, CO, CO₂), followed by catalytic processes to reassemble these components into the desired hydrocarbons, such as diesel and kerosene [73] or methanol and olefins [67–69, 73]. As CO₂ removal is typically a necessary step before

catalytic reassembly, capturing the CO₂ for storage represents a relatively minor addition to the proposed process. Two studies did not consider gasification, but used hydrogen separated from biogenic process gases, requiring CO₂ removal [65, 70]. Most of these technologies are generally at an early stage of development, though currently two plants gasify biomass into methanol, and fossil-based CO₂ capture is commercialised in methanol production [6].

Costs of BECCS-in-Industry

Cost estimates from BECCS literature are difficult to compare, as they embody widely varying assumptions regarding technical performance, technology maturity, system boundaries, financing, commodity pricing, coproduct sales, and carbon taxation.⁶ Table 2 summarises the abatement costs of BECCS-in-industry from the reviewed studies, in comparison with literature on CCS alone. When possible, costs of CO₂ capture were separated, but cost estimates were often not broken down into their components. Only one study [58•] estimated costs across multiple industries. Their estimates for BECCS integration into steel, cement, transport fuels, and pulp ranged between 50 and 90€₂₀₂₀/t CO₂ avoided. However, underlining the difficulty of direct comparison, their CO₂ abated includes emissions from

⁶ A breakdown of what each study's cost estimates include is available in the ESI.

upstream fossil and bioenergy supply chains, unlike most other studies, but did not include distance-specific transport costs.

The wide uncertainty in cost estimates is also a function of sparsity of BECCS-in-industry studies as well as the need to incorporate multiple system changes—bioenergy use, CO₂ capture, and CO₂ transport and storage—whose individual uncertainty is compounded by their interaction. Nevertheless, we can discuss the influential cost components seen in the recent literature.

Biomass Price

Wood-based biomass was used in 30 of the 41 studies that were not about sugarcane or maize ethanol. Prices ranged from 0 to 8.6€₂₀₂₀/GJ for forestry and mill residues [30, 42•, 56, 65, 66, 72], 1.9 to 7.5€₂₀₂₀/GJ for wood chips and stem wood [30, 38, 43, 59, 64•, 67, 70, 73], and 7.2 to 15.4€₂₀₂₀/GJ for charcoal and torrefied wood [48•, 58•, 74, 79]. Currently, global export prices of wood chips are 4–8€₂₀₂₀/GJ [13], and biomass pellet prices in the USA and EU are 10–22€₂₀₂₀/GJ [80, 81]. As biomass demand increases, however, prices of sustainably produced biomass are likely to increase.

CO₂ Capture

Capture costs typically include the cost of equipment, labour, chemicals, and energy to capture and compress CO₂ so that it is transport-ready. Capture costs ranged from 3 to 30€₂₀₂₀/t CO₂ [18, 22–24, 27–29, 34] for near-pure fermentation CO₂ and 42 to 110€₂₀₂₀/t CO₂ for complex configurations that use amine-based solvents to capture CO₂ from multiple dilute streams, such as in paper mills [40].

CO₂ Transport

In papers that assumed fixed CO₂ transport costs, those values ranged from 5 to 17€₂₀₂₀/t CO₂ [38, 40, 43, 58•, 64•, 74, 78]. In studies that calculated transport costs on volume and distance, the range was much wider: 5–380€₂₀₂₀/t CO₂ [20, 21•, 22–24, 29, 34, 42•, 46, 56], varying accounting for topography, existing land use, compression boosting, seasonality of biomass, shared pipelines, or multi-modal transport. However, in only four of these studies, all on Brazilian bioethanol production, was it possible to decompose costs by distance, with average costs typically between 0.2 and 0.4€₂₀₂₀/tkm CO₂, with higher costs typically the result of low volumes transported over long distances [20, 21•, 22, 23]. The use of intermediate pipeline hubs [21•, 22, 23], short-distance truck transport for low-volume distilleries [22], and shared capacity with CO₂ captured from fossil sources [21•] all led to lower transport cost estimates.

Tax on Fossil Carbon

Beyond absolute costs, an important factor is the cost of BECCS relative to the cost of fossil-based production. In several studies [46, 61, 73, 82, 83], an estimated 70€₂₀₂₀/t CO₂ tax on fossil emissions was necessary for BECCS processes to be considered cost-competitive with fossil ones. Alternatively, several BECCS studies on drop-in biofuels [64•, 66, 70, 72] estimated the crude oil price necessary for the biofuels to break even, typically between 120 and 180€₂₀₂₀/bbl.

Credits for Stored (Biogenic) CO₂

Existing biobased industries may not emit enough fossil CO₂ to be financially impacted by a fossil carbon tax. Therefore, several studies considered compensation for stored CO₂. One proposal is tradable “negative emission credits” [34, 38, 43] for stored biogenic CO₂, which can be sold to CO₂ emitters as offsets on emission trading networks. Another option is subsidies for stored CO₂, such as the 45Q scheme in the USA, which provides up to \$50/t CO₂ stored, regardless of CO₂ origin. Sanchez et al. [28] estimated that a \$50/t CO₂ credit would be sufficient to incentivise the storage of 20–25 Mt/year of CO₂ from bioethanol distilleries, but for most distilleries an additional \$20–40/t CO₂ credit would be necessary to cover transport costs [29, 42•]. Higher credits would be needed to incentivise many US paper mills as \$50/t CO₂ may be insufficient to cover even the costs of CO₂ capture alone [42•].

Achieving Negative Emissions via BECCS-in-Industry

Thirty-eight of the BECCS-in-industry studies claimed their system could result in negative emissions, but few provided sufficient detail to estimate if negative emissions occur. As negative emissions are intended to physically decrease GHGs in the atmosphere [2], they require that, as stated in [3•]:

1. *Physical greenhouse gases are removed from the atmosphere.*
2. *The removed gases are stored out of the atmosphere in a manner intended to be permanent.*
3. *Upstream and downstream greenhouse gas emissions associated with the removal and storage process, such as biomass origin, energy use, gas fate, and co-product fate, are comprehensively estimated and included in the emission balance.*

4. *The total quantity of atmospheric greenhouse gases removed and permanently stored is greater than the total quantity of greenhouse gases emitted to the atmosphere.*

Estimating negative emissions requires scrutinising the complete systems of biomass production and use and carbon capture and storage. Only 9 of the BECCS-in-industry papers performed cradle-to-grave life cycle assessment [3•, 34, 36, 37•, 62•, 63, 64•, 66, 70], though a further 9 considered a “cradle-to-gate” system, including impacts of upstream biomass and energy production, but not end of product life or CO₂ transport and storage [33•, 35, 48•, 58•, 65, 67, 68, 74, 78].

Many of the BECCS-in-industry studies that claimed to result in negative emissions added together estimates of net permanent storage of atmospheric CO₂ with estimates of avoided emissions from BECCS products replacing fossil-based production [33•, 34, 35, 58•, 63, 64•, 66, 70, 71, 74]. However, avoided emissions refer to an assumed relative change in emissions from one system to another, while negative emissions are an absolute reduction in CO₂ in the atmosphere via the physical removal and permanent storage of atmospheric CO₂. Caution is needed when interpreting such negative numbers to determine whether they actually represent net physical removal of atmospheric CO₂.

Estimates of GHG emissions from biomass supply chains ranged from 32 to 173 kg CO₂eq/t biomass and varied with biomass type, cultivation technique, transport method and distance, and greenhouse gases considered [3•, 19, 37•, 48•, 58•, 62•, 64•, 66, 67, 70, 74], with the lowest emissions for residual biomass and the highest for charcoal or torrefied pellets. Biomass system emissions are also challenging to estimate due to the variability of land use change and change in soil carbon stocks, which few studies included. In Field et al., converting forest to switchgrass production for cellulosic bioethanol released CO₂ both from the destruction of forest and loss of soil carbon, resulting in higher CO₂ emissions than uninterrupted forest growth [35]. However, in the BECCS system, the estimated biogenic CO₂ stored via CCS was more than double the total carbon storage of continued forest growth, even when considering indirect land use change. In Gelfand et al., replanting marginal land with native grasses for use in BECCS ethanol or electricity production was estimated to result in net carbon storage from both CCS and from increased soil carbon stocks [33•]. In contrast, in Fan and Friedmann, the inclusion of land use CO₂ emissions nearly negated the original estimated decarbonisation of BECCS-in-steel [48•].

With regard to downstream impacts, in the studies that separated emissions from CO₂ transport and storage [3•, 62•, 66, 70], estimates ranged from 5 to 20 kg/t CO₂ for pipeline transport to dedicated geologic storage and were not a major contributor to total emissions. However, not all studies assumed that the CO₂ was sent to dedicated geologic storage. Several studies assumed

that the CO₂ would be used in enhanced oil recovery [19, 21•, 22, 26, 30, 64•]. While EOR does lead to geologic storage of injected CO₂, it also leads to CO₂ emissions from the extracted oil, which was not considered in any of the studies. While it is possible for EOR systems to store more CO₂ than is emitted by the recovered oil, if the system is designed to maximise permanent CO₂ injection [84], that is not typically the case [85–87], and CO₂ emitted by recovered CO₂ would mute the potential “negative emissions” from BECCS systems.

Geologic storage of CO₂ is likely to store CO₂ for millennia [88] and can be considered effectively permanent. Carbon storage in concrete [62•] or buried biochar [79] may also result in long-term storage, though biochar carbon may be partially re-released over time, and carbon storage in concrete is dependent on how the concrete is disposed. In contrast, carbon in short-lived products such as urea, paper products, or olefins, as considered in [44, 59, 67–69], will re-release CO₂ during use or disposal, and thus, carbon in these products should not be counted towards negative emissions.

Timing of CO₂ storage and emissions is also relevant to upstream biomass cultivation. Biomass for bioenergy is typically combusted shortly after harvest, and CO₂ is then reabsorbed by replacement biomass, allowing CO₂ from biomass combustion to be part of the short-term carbon cycle. However, while biomass regrowth can be 1–2 years for grasses or 5–10 years for coppiced or fast-growing tree species such as eucalyptus or poplar, common boreal species such as Scots pine or Norwegian spruce take 50–100 years to mature, and CO₂ emitted from their combustion contributes to global warming for decades [89, 90]. In Tanzer et al.’s models of BECCS-in-concrete, the BECCS systems resulted in higher atmospheric CO₂ than a fossil-based CCS system for up to a third of the biomass’s rotation period and carbon-negativity was not reached until the after the biomass had been regrown (and CO₂ was reabsorbed by concrete), 50 years after the concrete was produced [62•].

Beyond global warming, in the four studies that look at other environmental impacts [25, 36, 37•, 63], the BECCS system resulted in higher acidification, human toxicity, ecosystem toxicity, water depletion, eutrophication, and ozone depletion compared to fossil-based production. These higher impacts resulted from the land and water use of bioenergy production, particulate matter and NO_x formation of biomass combustion, and the energy use of CO₂ capture. However, these studies only considered variations in the industrial production system; options for decreasing burden-shifting in the bioenergy or CCS systems were not considered.

Conclusions

As both bioenergy and CCS are more developed in industry, industry is a likely candidate for near-term BECCS implementation. In particular, bioethanol is a potential early source

of negative emissions, as fermentation CO₂ can be cheaply captured. However, when bioethanol plants are far from geologic storage, transport network design is of crucial concern to costs. Pulp and paper mills represent the other major existing biogenic industry, but CO₂ capture is likely to be costly due to the complex configuration to capture multiple point-sources of dilute CO₂. BECCS could also be retrofitted into the carbon-intensive production of steel or cement while low-carbon production technologies are developed. CCS integration into novel biobased chemical production pathways also allows for carbon neutral production of short-lived carbon-based products, such as olefins or transport fuels.

Many uncertainties remain about BECCS-in-industry, which is predominantly a prospective technology. However, interest is growing, with 16 studies published in 2020 alone, the same as in 2016–2018. From the studies available, it is clear that BECCS-based production will require fossil carbon taxes as well as incentives for biogenic stored CO₂ to be cost-competitive on the global market. Furthermore, while BECCS can reduce GHG emissions, achieving negative emissions is sensitive to specific system configurations and assumptions, and requires thorough and accurate assessment of emissions across the biomass and CCS supply chains.

While ongoing research on separate CCS and bioenergy use in industry and on BECCS-in-power will benefit BECCS-in-industry, we emphasise the following research needs for BECCS-in-industry:

- Life cycle assessment of BECCS-in-industry configurations outside of Europe and the Americas, and particularly in centres of industrial production in China and India, that take into account local availability of biomass and CO₂ storage.
- Evaluation of the logistical impacts of retrofitting both combined biomass and CO₂ capture at industrial facilities, particularly on space demand, heat recovery, and siting relative to both biomass and CO₂ storage.
- System designs that incorporate optimisation of both biomass production and CCS supply chains to minimise environmental burden-shifting.
- Interactions and optimisation between BECCS and other decarbonisation options available to industry, taking into account the timing of investment decisions, technological change, and received benefit.
- The incorporation of BECCS-in-industry into IAMs, using industry and geography-specific parameters and limitations.

As estimates of costs and environmental impacts of BECCS systems are highly sensitive to studies' assumptions, it is crucial that these assumptions as well as system boundaries are clearly documented. BECCS-in-industry studies should ensure that they account for all carbon in

their system and refrain from estimating negative emissions without a cradle-to-grave life cycle assessment. Avoided CO₂ should be accounted for separately from CO₂ that is physically and permanently removed from the atmosphere. Furthermore, CO₂ avoidance cost estimates explicitly state both what costs and CO₂ emissions are included, and provide clearly decomposed costs of CO₂ capture, transport, and storage to facilitate comparisons between studies. Finally, environmental impacts beyond GHG emissions need more attention, taking into account the local context of biomass cultivation and CO₂ fate.

BECCS is not a substitute for immediate and rapid decarbonisation of industry via increased efficiency, novel production methods, and, above all, reduced consumption and waste. Rather, the judicious use of BECCS can allow for limited continued use of fossil carbon or limited removal of historical CO₂ from the atmosphere. With or without BECCS, the transition to a “net-zero” society requires confronting the hard limits of our resource-constrained world.

Supplementary Information The online version contains supplementary material available at <https://doi.org/10.1007/s40518-021-00195-3>.

Compliance with Ethical Standards

Conflict of Interest The authors declare no competing interests.

Human and Animal Rights and Informed Consent This article does not contain any studies with human or animal subjects performed by any of the authors.

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

References

Papers of particular interest, published recently, have been highlighted as:

• Of importance

1. United Nations. Emissions gap emissions gap report. 2020. <https://www.unenvironment.org/interactive/emissions-gap-report/2019/>.
2. IPCC. Global warming of 1.5°C. An IPCC special report on the impacts of global warming of 1.5°C above pre-industrial

- levels and related global greenhouse gas emission pathways, in the context of strengthening the global response to the threat of climate change. 2018. <https://www.ipcc.ch/sr15/>.
3. • Tanzer SE, Ramírez A. When are negative emissions negative emissions? *Energy Environ Sci*. 2019. <https://doi.org/10.1039/c8ee03338b>. **(Provides criteria for assessing whether a system can result in the permanent removal of atmospheric CO₂ and a discussion on the influence of system boundary selection.)**
 4. Rogelj J, Popp A, Calvin KV, et al. Scenarios towards limiting global mean temperature increase below 1.5 °C. *Nature Climate Change*. 2018. <https://doi.org/10.1038/s41558-018-0091-3>.
 5. IEA. Tracking industry. 2020. <https://www.iea.org/reports/tracking-industry-2020>.
 6. IEA. Energy technology perspectives. 2020. <https://doi.org/10.1787/9789264109834-en>.
 7. IEA. CCUS in clean energy transitions. 2020. <https://www.iea.org/reports/ccus-in-clean-energy-transitions>.
 8. Global CCS institute. Facilities database. 2021. <https://co2re.co/FacilityData>. Accessed 1 May 2021.
 9. European Technology and Innovation Platform Bioenergy. Products. 2021. <https://www.etipbioenergy.eu/value-chains/products-end-use/products>.
 10. IEA. Cement. 2020. <https://www.iea.org/reports/cement>.
 11. World Business Council for Sustainable Development. Getting the numbers right project emissions report. 2018. <https://gccasociation.org/gnr/>.
 12. IPCC. Emission factor database. 2019. <https://www.ipcc-nggip.iges.or.jp/EFDB/main.php>. Accessed 28 Nov 2019.
 13. FAO. FAOSTAT. 2020. <http://www.fao.org/faostat/en/>. Accessed 15 Nov 2020.
 14. IEAGHG. Techno-economic evaluation of mill and an in a market pulp retrofitting CCS integrated pulp and board mill. 2016. <https://www.ieaghg.org/publications/technical-reports/reports-list/9-technical-reports/774-2016-10-techno-economic-evaluation-of-retrofitting-ccs-in-a-market-pulp-mill-and-an-integrated-pulp-and-board-mill>.
 15. Ericsson K, Nilsson LJ. Climate innovations in the paper industry: prospects for decarbonisation. 2018. http://portal.research.lu.se/portal/files/53800825/Climate_innovations_in_the_plastic_industry_IMES_report_111.pdf.
 16. CO₂ Solutions. Projects. <https://co2solutions.com/en/projects/>. 2020. Accessed 9 May 2020.
 17. Renewable Fuels Association. Annual fuel ethanol production. 2021. <https://ethanolrfa.org/statistics/annual-ethanol-production/>. Accessed 1 May 2021.
 18. Moreira JR, Romeiro V, Fuss S, Kraxner F, Pacca SA. BECCS potential in Brazil: achieving negative emissions in ethanol and electricity production based on sugar cane bagasse and other residues. *Appl Energy*. 2016. <https://doi.org/10.1016/j.apenergy.2016.06.044>.
 19. Carminati HB, de Milão RFD, de Medeiros JL, de Araújo OQF. Bioenergy and full carbon dioxide sinking in sugarcane-biorefinery with post-combustion capture and storage: Techno-economic feasibility. *Appl Energy*. 2019. <https://doi.org/10.1016/j.apenergy.2019.113633>.
 20. Restrepo-Valencia S, Walter A. Techno-economic assessment of bio-energy with carbon capture and storage systems in a typical sugarcane mill in Brazil. *Energies*. 2019. <https://doi.org/10.3390/en12061129>.
 21. • Tagomori IS, Carvalho FM, da Silva FTF, Paulo PR, Rachedo PRR, Szklo A, Schaeffer R. Designing an optimum carbon capture and transportation network by integrating ethanol distilleries with fossil-fuel processing plants in Brazil. *Int J Greenhouse Gas Control*. 2018. <https://doi.org/10.1016/j.ijggc.2017.10.013>. **(Clearly presents the many assumptions, variables, and calculations in its pipeline network design and includes the influence of biomass seasonality and pipeline sharing on design and costs.)**
 22. da Silva FTF, Carvalho FM, Corrêa JLG, de Merschmann PRC, Tagomori IS, Szklo A, Schaeffer R. CO₂ capture in ethanol distilleries in Brazil: designing the optimum carbon transportation network by integrating hubs, pipelines and trucks. *Int J Greenhouse Gas Control*. 2018. <https://doi.org/10.1016/j.ijggc.2018.02.018>.
 23. Rachedo PRR, Costa IVL, Império M, Hoffmann BS, Merschmann PRDC, Oliveira CCN, Szklo A, Schaeffer R. Carbon capture potential and costs in Brazil. *J Clean Prod*. 2016. <https://doi.org/10.1016/j.jclepro.2016.05.033>.
 24. Merschmann PR, Szklo AS, Schaeffer R. Technical potential and abatement costs associated with the use of process emissions from sugarcane ethanol distilleries for EOR in offshore fields in Brazil. *Int J Greenhouse Gas Control*. 2016. <https://doi.org/10.1016/j.ijggc.2016.07.007>.
 25. Chagas MF, Cavalett O, Klein BC, Filho RM, Bonomi A. Life cycle assessment of technologies for greenhouse gas emissions reduction in sugarcane biorefineries. *Chem Eng Trans*. 2016. <https://doi.org/10.3303/CET1650071>.
 26. de Milão RFD, Carminati HB, de Araújo OQF, de Medeiros JL. Thermodynamic, financial and resource assessments of a large-scale sugarcane-biorefinery: prelude of full bioenergy carbon capture and storage scenario. *Renew Sustain Energy Rev*. 2019. <https://doi.org/10.1016/j.rser.2019.109251>.
 27. Bains P, Psarras P, Wilcox J. CO₂ capture from the industry sector. *Prog Energy Combust Sci*. 2017. <https://doi.org/10.1016/j.pecs.2017.07.001>.
 28. Sanchez DL, Johnson N, McCoy ST, Turner PA, Mach KJ. Erratum: near-term deployment of carbon capture and sequestration from biorefineries in the United States (Proceedings of the National Academy of Sciences of the United States of America. 2018;115:4875–4880. <https://doi.org/10.1073/pnas.1719695115>). Proceedings of the National Academy of Sciences of the United States of America. <https://doi.org/10.1073/pnas.1816158115>.
 29. Pilorgé H, McQueen N, Maynard D, Psarras P, He J, Rufael T, Wilcox J. Cost analysis of carbon capture and sequestration of process emissions from the U S industrial sector. *Environ Sci Technol*. 2020. <https://doi.org/10.1021/acs.est.9b07930>.
 30. Younis A, Benders R, Delgado R, Lap T, Gonzalez-Salazar M, Cadena A, Faaij A. System analysis of the bio-based economy in Colombia: a bottom-up energy system model and scenario analysis. *Biofuels*. 2020. <https://doi.org/10.1002/bbb.2167>.
 31. Renewable Fuels Association. Ethanol biorefinery locations. 2021. <https://ethanolrfa.org/biorefinery-locations/>.
 32. Bezerra PXO, De Farias Silva CE, Soletti JI, de Carvalho SHV. Cellulosic ethanol from sugarcane straw: a discussion based on industrial experience in the northeast of Brazil. *Bioenergy Res*. 2020. <https://doi.org/10.1007/s12155-020-10169-w>.
 33. • Gelfand I, Hamilton SK, Kravchenko AN, Jackson RD, Thelen KD, Robertson GP. Empirical evidence for the potential climate benefits of decarbonizing light vehicle transport in the U.S. with bioenergy from purpose-grown biomass with and without BECCS. *Environ Sci Technol*. 2020. <https://doi.org/10.1021/acs.est.9b07019>.
 34. Kim S, Zhang X, Reddy AD, Dale BE, Thelen KD, Jones CD, Izaurrealde RC, Runge T, Maravelias C. Carbon-negative biofuel production. *Environ Sci Technol*. 2020. <https://doi.org/10.1021/acs.est.0c01097>.
 35. Field JL, Richard TL, Smithwick EAH, et al. Robust paths to net greenhouse gas mitigation and negative emissions via

- advanced biofuels. *Proc Natl Acad Sci USA*. 2020. <https://doi.org/10.1073/pnas.1920877117>.
36. Lask J, Rukavina S, Zorić I, Kam J, Kiesel A, Lewandowski I, Wagner M. Lignocellulosic ethanol production combined with CCS—a study of GHG reductions and potential environmental trade-offs. *GCB Bioenergy*. 2021. <https://doi.org/10.1111/gcbb.12781>.
 37. Bello S, Galán-Martín Á, Feijoo G, Moreira MT, Guillén-Gosálbez G. BECCS based on bioethanol from wood residues: potential towards a carbon-negative transport and side-effects. *Appl Energy*. 2020. <https://doi.org/10.1016/j.apenergy.2020.115884>. **(Clear contribution analysis of environmental impacts and highlights the impact of energy source selection.)**
 38. Onarheim K, Santos S, Kangas P, Hankalin V. Performance and cost of CCS in the pulp and paper industry part 2: economic feasibility of amine-based post-combustion CO₂ capture. *Int J Greenhouse Gas Control*. 2017. <https://doi.org/10.1016/j.ijggc.2017.09.010>.
 39. Man Y, Hu S, Gao J, Li J, Hong M. Integrated chemical looping combustion in pulp mill for high energy efficiency and low carbon emission. *J Clean Prod*. 2020. <https://doi.org/10.1016/j.jclepro.2020.122979>.
 40. Garðarsdóttir SÓ, Normann F, Skagestad R, Johnsson F. Investment costs and CO₂ reduction potential of carbon capture from industrial plants – a Swedish case study. *Int J Greenhouse Gas Control*. 2018. <https://doi.org/10.1016/j.ijggc.2018.06.022>.
 41. Nwaoha C, Tontiwachwuthikul P. Carbon dioxide capture from pulp mill using 2-amino-2-methyl-1-propanol and monoethanolamine blend: techno-economic assessment of advanced process configuration. *Appl Energy*. 2019. <https://doi.org/10.1016/j.apenergy.2019.05.097>.
 42. Sagues WJ, Jameel H, Sanchez DL, Park S. Prospects for bioenergy with carbon capture & storage (BECCS) in the United States pulp and paper industry. *Energy Environ Sci*. 2020. <https://doi.org/10.1039/d0ee01107j>. **(Combined top-down national potential and generic cost estimates with bottom-up technical modelling that provide more specific details on specific implementation concerns).**
 43. Santos MPS, Manovic V, Hanak DP. Unlocking the potential of pulp and paper industry to achieve carbon-negative emissions via calcium looping retrofit. *J Clean Prod*. 2021. <https://doi.org/10.1016/j.jclepro.2020.124431>.
 44. Kuparinen K, Vakkilainen E, Tynjälä T. Biomass-based carbon capture and utilization in kraft pulp mills. *Mitig Adapt Strat Glob Change*. 2019. <https://doi.org/10.1007/s11027-018-9833-9>.
 45. Onarheim K, Santos S, Kangas P, Hankalin V. Performance and costs of CCS in the pulp and paper industry part 1: performance of amine-based post-combustion CO₂ capture. *Int J Greenhouse Gas Control*. 2017. <https://doi.org/10.1016/j.ijggc.2017.02.008>.
 46. Johnsson F, Normann F, Svensson E. Marginal abatement cost curve of industrial CO₂ capture and storage – a Swedish case study. *Front Energy Res*. 2020. <https://doi.org/10.3389/fenrg.2020.00175>.
 47. World Steel Association. 2020 World Steel in Figures. 2020. <https://www.worldsteel.org/steel-by-topic/statistics/World-Steel-in-Figures.html>.
 48. Fan Z, Friedmann SJ. Low-carbon production of iron and steel: technology options, economic assessment, and policy. *Joule*. 2021. <https://doi.org/10.1016/j.joule.2021.02.018>. **(Presentation of CO₂ avoidance costs of BECCS-in-steel in comparison with many other decarbonization options.)**
 49. Mandova H, Leduc S, Wang C, Wetterlund E, Patrizio P, Gale W, Kraxner F. Possibilities for CO₂ emission reduction using biomass in European integrated steel plants. *Biomass Bioenerg*. 2018. <https://doi.org/10.1016/j.biombioe.2018.04.021>.
 50. Tanzer SE, Blok K, Ramírez A. Can bioenergy with carbon capture and storage result in carbon negative steel. *Int J Greenhouse Gas Control*. 2020. <https://doi.org/10.1016/j.ijggc.2020.103104>.
 51. Leeson D, Dowell NM, Shah N, Petit C, Fennell PS. Techno-economic analysis and systematic review of carbon capture and storage (CCS) applied to the iron and steel, cement, oil refining and pulp and paper industries, as well as other high purity sources. *Int J Greenhouse Gas Control*. 2017. <https://doi.org/10.1016/j.ijggc.2017.03.020>.
 52. IEAGHG. Cost of CO₂ Capture in the industrial sector: cement and iron and steel industries. 2018-TR03, September, 2018. 2018. <https://www.ieaghg.org/publications/technical-reports/reports-list/10-technical-reviews/931-2018-tr03-cost-of-co2-capture-in-the-industrial-sector-cement-and-iron-and-steel-industries>.
 53. Birat J-P. Carbon dioxide (CO₂) capture and storage technology in the iron and steel industry. Developments and innovation in carbon dioxide (CO₂) capture and storage technology. 2010. <https://doi.org/10.1533/9781845699574.5.492>.
 54. Sonter LJ, Barrett DJ, Moran CJ, Soares-filho BS. Carbon emissions due to deforestation for the production of charcoal used in Brazil's steel industry. 2015. <https://doi.org/10.1038/NCLIMATE2515>.
 55. Suopajarvi H, Kemppainen A, Haapakangas J, Fabritius T. Extensive review of the opportunities to use biomass-based fuels in iron and steelmaking processes. *J Clean Prod*. 2017. <https://doi.org/10.1016/j.jclepro.2017.02.029>.
 56. Mandova H, Patrizio P, Leduc S, Kjærstad J, Wang C, Wetterlund E, Kraxner F, Gale W. Achieving carbon-neutral iron and steelmaking in Europe through the deployment of bioenergy with carbon capture and storage. *J Clean Prod*. 2019. <https://doi.org/10.1016/j.jclepro.2019.01.247>.
 57. Toktarova A, Karlsson I, Rootzén J, Göransson L, Odenberger M, Johnsson F. Pathways for low-carbon transition of the steel industry—a Swedish case study. *Energies*. 2020. <https://doi.org/10.3390/en13153840>.
 58. Yang F, Meerman JC, Faaij APC. Carbon capture and biomass in industry: a techno-economic analysis and comparison of negative emission options. *Renew Sustain Energy Rev*. 2021. <https://doi.org/10.1016/j.rser.2021.111028>. **(Cross-industry comparison of CO₂ avoidance costs including many scenarios of CCS, bioenergy use, and BECCS.)**
 59. Hammerschmid M, Müller S, Fuchs J, Hofbauer H. Evaluation of biomass-based production of below zero emission reducing gas for the iron and steel industry. *Biomass Convers Biorefin*. 2021. <https://doi.org/10.1007/s13399-020-00939-z>.
 60. Guo D, Zhu L, Guo S, et al. Direct reduction of oxidized iron ore pellets using biomass syngas as the reducer. *Fuel Process Technol*. 2016. <https://doi.org/10.1016/j.fuproc.2016.03.009>.
 61. Obrist MD, Kannan R, Schmidt TJ, Kober T. Decarbonization pathways of the Swiss cement industry towards net zero emissions. *J Clean Prod*. 2021. <https://doi.org/10.1016/j.jclepro.2020.125413>.
 62. Tanzer SE, Blok K, Ramirez A. Curing time: a temporally explicit life cycle CO₂ accounting of mineralization, bioenergy, and CCS in the concrete sector. *Faraday Discuss*. 2021. <https://doi.org/10.1039/d0fd00139b>. **(Highlights the importance of biomass regrowth periods on when BECCS can lead to a reduction of atmospheric CO₂, which can be decades after initial CO₂ emissions.)**
 63. Schakel W, Roxanne C, Tokheim L, Hammer A, Worrell E, Ramírez A. Impact of fuel selection on the environmental performance of post-combustion calcium looping applied to a cement plant. *Appl Energy*. 2018. <https://doi.org/10.1016/j.apenergy.2017.10.123>.

64. Kreutz TG, Larson ED, Elsidio C, Martelli E, Greig C, Williams RH. Techno-economic prospects for producing Fischer-Tropsch jet fuel and electricity from lignite and woody biomass with CO₂ capture for EOR. *Appl Energy*. 2020. <https://doi.org/10.1016/j.apenergy.2020.115841>. (Considers different cases of BECCS integration to allow for carbon-equivalent, carbon-neutral, and carbon-negative production, with comparison between FOAK and NOAK cases.)
65. Lozano EM, Pedersen TH, Rosendahl LA. Integration of hydrothermal liquefaction and carbon capture and storage for the production of advanced liquid biofuels with negative CO₂ emissions. *Appl Energy*. 2020. <https://doi.org/10.1016/j.apenergy.2020.115753>.
66. Hailey AK, Meerman JC, Larson ED, Loo YL. Low-carbon “drop-in replacement” transportation fuels from non-food biomass and natural gas. *Appl Energy*. 2016. <https://doi.org/10.1016/j.apenergy.2016.09.068>.
67. Jiang P, Berrouk AS, Dara S. Biomass gasification integrated with chemical looping system for hydrogen and power. Coproduction process – thermodynamic and techno-economic assessment. *Chem Eng Technol*. 2019. <https://doi.org/10.1002/ceat.201900130>.
68. Zhao Z, Chong K, Jiang J, Wilson K, Zhang X, Wang F. Low-carbon roadmap of chemical production: a case study of ethylene in China. *Renew Sustain Energy Rev*. 2018. <https://doi.org/10.1016/j.rser.2018.08.008>.
69. Oliveira CCN, Rochedo PRR, Bhardwaj R, Worrell E, Szklo A. Bio-ethylene from sugarcane as a competitiveness strategy for the Brazilian chemical industry. *Biofuels, Bioprod Biorefin*. 2020. <https://doi.org/10.1002/bbb.2069>.
70. Meerman JC, Larson ED. Negative-carbon drop-in transport fuels produced: via catalytic hydropyrolysis of woody biomass with CO₂ capture and storage. *Sustainable Energy Fuels*. 2017. <https://doi.org/10.1039/c7se00013h>.
71. Giuliano A, Catizzone E, Freda C, Cornacchia G. Valorization of OFMSW digestate-derived syngas toward methanol, hydrogen, or electricity: process simulation and carbon footprint calculation. *Processes*. 2020. <https://doi.org/10.3390/pr8050526>.
72. Tagomori IS, Rochedo PRR, Szklo A. Techno-economic and georeferenced analysis of forestry residues-based Fischer-Tropsch diesel with carbon capture in Brazil. *Biomass Bioenerg*. 2019. <https://doi.org/10.1016/j.biombioe.2019.02.018>.
73. Celebi AD, Sharma S, Ensinas AV, Maréchal F. Next generation cogeneration system for industry – combined heat and fuel plant using biomass resources. *Chem Eng Sci*. 2019. <https://doi.org/10.1016/j.ces.2019.04.018>.
74. Berghout N, Meerman H, van den Broek M, Faaij A. Assessing deployment pathways for greenhouse gas emissions reductions in an industrial plant – a case study for a complex oil refinery. *Appl Energy*. 2019. <https://doi.org/10.1016/j.apenergy.2018.11.074>.
75. Fuss S, Lamb WF, Callaghan MW, et al. Negative emissions - part 2: costs, potentials and side effects. *Environ Res Lett*. 2018. <https://doi.org/10.1088/1748-9326/aabf9f>.
76. Roussanal S, Berghout N, Fout T, Garcia M, Gardarsdottir S, Nazir SM, Ramirez A, Rubin ES. Towards improved cost evaluation of carbon capture and storage from industry. *Int J Greenhouse Gas Control*. 2021. <https://doi.org/10.1016/j.ijggc.2021.103263>.
77. Kuramochi T, Ramírez A, Turkenburg W, Faaij A. Comparative assessment of CO₂ capture technologies for carbon-intensive industrial processes. *Prog Energy Combust Sci*. 2012. <https://doi.org/10.1016/j.pecs.2011.05.001>.
78. Yang M, Baral NR, Anastasopoulou A, Breunig HM, Scown CD. Cost and life-cycle greenhouse gas implications of integrating biogas upgrading and carbon capture technologies in cellulosic biorefineries. *Environ Sci Technol*. 2020. <https://doi.org/10.1021/acs.est.0c02816>.
79. Ubando AT, Chen WH, Tan RR, Naqvi SR. Optimal integration of a biomass-based polygeneration system in an iron production plant for negative carbon emissions. *Int J Energy Res*. 2020. <https://doi.org/10.1002/er.4902>.
80. U.S. Energy Information Administration. Monthly densified biomass fuel report (January 2021). 2021. <https://www.eia.gov/biofuels/biomass/?year=2021&month=01>. Accessed 2 May 2021.
81. Calderón C, Colla M, Jossart J-M, Hemeleers N, Cancian G, Aveni N, et al. Bioenergy Europe Statistical Report 2019: Pellet. European Pellet Council. 2019. <https://epc.bioenergyeurope.org/bioenergy-europe-pellet-report-2019>.
82. Tsiropoulos I, Hoefnagels R, de Jong S, van den Broek M, Patel M, Faaij A. Emerging bioeconomy sectors in energy systems modeling – integrated systems analysis of electricity, heat, road transport, aviation, and chemicals: a case study for the Netherlands. *Biofuels, Bioprod Biorefin*. 2018. <https://doi.org/10.1002/bbb.1881>.
83. Beal CM, Archibald I, Huntley ME, Greene CH, Johnson ZI. Integrating algae with bioenergy carbon capture and storage (ABECCS) increases sustainability. *Earth's Future*. 2018. <https://doi.org/10.1002/2017EF000704>.
84. Sminchak JR, Mawalkar S, Gupta N. Large CO₂ storage volumes result in net negative emissions for greenhouse gas life cycle analysis based on records from 22 years of CO₂-enhanced oil recovery operations. *Energy Fuels*. 2020. <https://doi.org/10.1021/acs.energyfuels.9b04540>.
85. Azzolina NA, Peck WD, Hamling JA, Gorecki CD, Ayash SC, Doll TE, Nakles DV, Melzer LS. How green is my oil? A detailed look at greenhouse gas accounting for CO₂-enhanced oil recovery (CO₂-EOR) sites. *Int J Greenhouse Gas Control*. 2016. <https://doi.org/10.1016/j.ijggc.2016.06.008>.
86. Hussain D, Dzombak DA, Jaramillo P, Lowry GV. Comparative lifecycle inventory (LCI) of greenhouse gas (GHG) emissions of enhanced oil recovery (EOR) methods using different CO₂ sources. *Int J Greenhouse Gas Control*. 2013. <https://doi.org/10.1016/j.ijggc.2013.03.006>.
87. Núñez-López V, Gil-Egui R, Hosseini S. Environmental and operational performance of CO₂-EOR as a CCUS technology: a Cranfield example with dynamic LCA considerations. *Energies*. 2019. <https://doi.org/10.3390/en12030448>.
88. IPCC. IPCC special report on carbon dioxide capture and storage. Prepared by Working Group III of the Intergovernmental Panel on Climate Change [Metz, B., O. Davidson, H. C. de Coninck, M. Loos, and L. A. Meyer (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA, 442 pp. 2005. <https://www.ipcc.ch/report/carbon-dioxide-capture-and-storage/>.
89. Cherubini F, Strømman AH. Life cycle assessment of bioenergy systems: state of the art and future challenges. *Biores Technol*. 2011. <https://doi.org/10.1016/j.biortech.2010.08.010>.
90. Norton M, Baldi A, Buda V, et al. Serious mismatches continue between science and policy in forest bioenergy. *GCB Bioenergy*. 2019. <https://doi.org/10.1111/gcbb.12643>.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.