

Assessment of the Accuracy of Numerical Morphological Models based on Reduced Saint-Venant Equations

Barneveld, Hermjan; Mosselman, Erik; Chavarrías, Víctor; Hoitink, Ton

DOI

[10.5194/egusphere-egu24-17212](https://doi.org/10.5194/egusphere-egu24-17212)

Publication date

2024

Document Version

Final published version

Citation (APA)

Barneveld, H., Mosselman, E., Chavarrías, V., & Hoitink, T. (2024). *Assessment of the Accuracy of Numerical Morphological Models based on Reduced Saint-Venant Equations*. Abstract from EGU General Assembly 2024, Vienna, Austria. <https://doi.org/10.5194/egusphere-egu24-17212>

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.



Assessment of the Accuracy of Numerical Morphological Models based on Reduced Saint-Venant Equations

Hermjan Barneveld^{1,4}, Erik Mosselman^{2,3}, Victor Chavarrias², and Ton Hoitink¹

¹Wageningen University & Research, Department of Environmental Sciences, Hydrology and Environmental Hydraulics Group, the Netherlands (hermjan.barneveld@wur.nl, ton.hoitink@wur.nl)

²Deltares, Delft, the Netherlands (Erik.Mosselman@deltares.nl, Victor.Chavarrias@deltares.nl)

³Delft University of Technology, Faculty of Civil Engineering and Geosciences, Delft, the Netherlands (E.Mosselman@tudelft.nl)

⁴HKV, Lelystad, the Netherlands (barneveld@hkv.nl)

Sustainable river management often requires long-term morphological simulations. As the future is unknown, uncertainty needs to be accounted for, which may require probabilistic simulations covering a large parameter domain. Even for one-dimensional models, simulation times can be long. One of the acceleration strategies is simplification of models by neglecting terms in the governing hydrodynamic equations. Examples are the quasi-steady model and the diffusive wave model, both widely used by scientists and practitioners. We established under which conditions these simplified models are accurate.

Based on results of linear stability analyses of the St. Venant-Exner equations, we assessed migration celerities and damping of infinitesimal, but long riverbed perturbations. We did this for the full dynamic model, i.e. no terms neglected, as well as for the simplified models. The accuracy of the simplified models was obtained from comparison between the characteristics of the riverbed perturbations for simplified models and the full dynamic model.

We executed a spatial-mode and a temporal-mode linear analysis and compared the results with numerical modelling results for the full dynamic and simplified models, for very small and large bed waves. The numerical results match best with the temporal-mode linear analysis. We show that the quasi-steady model is highly accurate for Froude numbers up to 0.7, probably even for long river reaches with large flood wave damping. Although the diffusive wave model accurately predicts flood wave migration and damping, key morphological metrics deviate more than 5% (10%) from the full dynamic model when Froude numbers exceed 0.2 (0.3).