


# The R Village



P5-ARCHITECTURAL ENGINEERING-16/06/22

QIANYI WANG 5100585

TUTORS :MO SMIT, GER WARRIES, TANYA TSUI



Architectural Engineering  
The graduation studio  
Cross-Disciplinary studio: architecture, Architecture

Harvest, 2021 to 2022

Res Landscap  
Published on 10.06.2022  
October in the studio, in the world

This graduation has several design challenges and principles. Our challenge is to valuable landscapes, villages or urban neighborhoods in rural areas. Students work on nature-inclusive architectural design solutions, using the energy transition as a lever. As a result, the design is not limited to the building. In combination with the spatial potential of the intervention area itself, we work on design solutions that strengthen the social activity, economy and its spatial identity.



## CONTENT



problems and opportunities

waste and pollution/homogeneity(countryside)

lessons from vernacular architecture



design

plans/layout/pavement

facade design and its logic

facade fragments and detail

climate solutions

materiality




future ambition


village plan

tourism

job opportunities



## LOCALLY HARVESTED RESIDUE



Process	Type	Origin
Harvesting	Straw	Field
Shelling	Husk	Factory
Milling	Bran	Factory
Milling	Germ	Factory
Milling	Brewer	Factory

# CONSTRUCTION METHODS








Table 1. The amount of rice straw used for different construction methods


Construction methods	Amount of rice straw needed per square meter/per cubic meter
Rice straw bale	non-load bearing wall: 70-110 kg/m <sup>2</sup> load-bearing wall: >130 kg/m <sup>3</sup>
Light clay	from 1 kg/m <sup>3</sup> to 50 kg/m <sup>3</sup> (depend on the clay content)
Rice straw thatching	from 1.5 kg/m <sup>2</sup> to 3 kg/m <sup>2</sup>


Table 2. Performance of the three construction methods

Method	construction ease	maintenance ease	Affordability	Thermal performance	Aesthetic acceptance
Rice straw bale	Easy when rice straw are baled before, unskilled worker can finish. Difficult when the baling process should be done by workers.	easy when extra protection added (rain screen/coating layer)	Affordable as local rice straw is cheap (20 euros for 500 kg rice straw) 1 m <sup>3</sup> wall cost 22.4 € to 41.6 € (2.8 € to 5.2 €)	u-value between 0.1 to 0.2 U = 0.167 [W/m <sup>2</sup> K] (external clay plaster 0.07 m, straw bale 0.45 m, internal clay plaster 0.04 m)	Acceptable (As the straw bale must need coverage such as rain screen or plastering therefore it is not exposed)
Light clay	Between easy and difficult. Ordinary construction workers can complete.	Feasible when skilled workers are hired.	Ditto. Besides, mud/clay is also a residue (from basement digging) 1 m <sup>3</sup> wall cost 0.32 € to 16 € (0.04 € to 2 €)	u-value = 0.19 [W/m <sup>2</sup> K] (exterior clay plaster 0.03 m, light clay 0.5 m, interior clay plaster 0.03 m) thermal conductivity 0.067 W/mK	Acceptable (As the light clay wall need coverage therefore it is not exposed)
Thatching	Quite difficult as there is a prone of leakage when the construction is not carefully done. Skilled workers needed.	Feasible when replacement is applied (every 1-3 years depending on the quality)	Ditto. 1 m <sup>2</sup> roof cost 0.48 € to 0.96 € (0.06 € to 0.12 €) Affordable but skill requirement is higher and the wage of skilled worker would be therefore higher	thermal conductivity 0.07 and a resistivity of 14.3 u-value = 0.2 [W/m <sup>2</sup> K] (0.35m of straw)	For most residents not acceptable as the rice straws are exposed. For some it can be a point to attract tourists.




## LOCALLY HARVESTED MATERIAL






brick and concrete building (84.6%)



External wall 240mm / 370mm


Internal wall 240mm / 120 mm



solid clay brick. (84.63%)

coating material

cement mortar



single layered aluminum window


## Target group

job opportunities



worker

comfortable environment  
(interior/exterior)




local villagers

added value  
of rice industry





farmer

experience



visitors



## LESSONS FROM TRADITIONAL HOUSING: Layout



Flexible plan to enhance ventilation


Use of skywell and courtyard

Gardens for different seasons\*








Enhance natural ventilation







Narrow alley to prevent direct solar gain




## LESSONS FROM TRADITIONAL HOUSING: Opening




## LESSONS FROM TRADITIONAL HOUSING: Material and structure







Plan ground floor(L+U)




Plan first floor(L+U)



Plan ground level







north elevation




west elevation





east elevation





south elevation






column/window section




## column/window section




roof tiles  
counter battens  
roofing battens  
wood fiberboard  
chopped rice straw blown-in insulation  
rafter





rain screen made of half cut  
bamboo  
wood fiber board  
timber frame with light straw-clay  
mixtures  
clay plaster




brick and concrete building (84.6%)




external wall 240mm / 370mm  
internal wall 240mm / 120 mm




solid clay brick. (84.63%)



cement mortar  
coating material



single layered aluminum window



Rsi Value (Internal Surface) m<sup>2</sup>k/w

0.12

Rso Value (External Surface) m<sup>2</sup>k/w

0.06

typical wall in rural zhejiang:

240mm brick wall lambda value (W/MK):0.7 Rvalue 0.34m<sup>2</sup>k/w

7mm cement mortar 1.73 0

15mm ceramic tiles 1.06 0.01

total u-value 1.887m<sup>2</sup>K/W

Rsi Value (Internal Surface) m<sup>2</sup>k/w

0.12

Rso Value (External Surface) m<sup>2</sup>k/w

0.06


NEW wall in rural zhejiang:

310mm rice straw light clay panel lambda value (W/MK):0.1 Rvalue 3.1m<sup>2</sup>k/w



28mm fiber board 0.2 0.14

50mm clay plaster 0.2 0.25



total u-value 0.272m<sup>2</sup>K/W





## Water purification



## Climate strategies



## Climate strategies




spring/autumn

summer

winter

## Material choice




## Sections and elevations






## Plantain and the introduced water


submergent plant









emerged plant







floating leaf formation











Sightseeing

Bed and Breakfast


"Experienece"

Sightseeing {normal development}


Bed and Breakfast {popular}

"ExperiencE"















Tourists



Tourists









The R Village

er cun

尔 村

like so

