

Novel coupling methods for fluid and kinetic solvers in the numerical modeling of helicon plasma thrusters

van Lynden, W.; Souhair, N.; Andriulli, R.; Magarotto, M.; Andrews, S.; Cervone, A.; Ponti, F.

Publication date

2023

Document Version

Final published version

Citation (APA)

van Lynden, W., Souhair, N., Andriulli, R., Magarotto, M., Andrews, S., Cervone, A., & Ponti, F. (2023). *Novel coupling methods for fluid and kinetic solvers in the numerical modeling of helicon plasma thrusters*. Abstract from 74th International Astronautical Congress, IAC 2023, Baku, Azerbaijan.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

IAF SPACE PROPULSION SYMPOSIUM (C4)
Electric Propulsion (2) (6)

Author: Mr. Willem van Lynden
Delft University of Technology (TU Delft), The Netherlands

Dr. Nabil Souhair
Alma Mater Studiorum - University of Bologna, Italy
Mr. Raoul Andriulli
Alma Mater Studiorum - University of Bologna, Italy
Mr. Shaun Andrews
Alma Mater Studiorum - University of Bologna, Italy
Dr. Mirko Magarotto
University of Padua, Italy
Dr. Angelo Cervone
Delft University of Technology (TU Delft), The Netherlands
Prof. Fabrizio Ponti
Alma Mater Studiorum - University of Bologna, Italy

NOVEL COUPLING METHODS FOR FLUID AND KINETIC SOLVERS IN THE NUMERICAL
MODELING OF HELICON PLASMA THRUSTERS**Abstract**

Helicon Plasma Thrusters (HPTs) are electric propulsion systems that offer many advantages over other systems, such as simplicity, flexibility, longer operational lifetime, and the ability to produce high-density plasma. Accurate modeling of plasma transport throughout the HPT is crucial to improve the understanding of physical phenomena within the plasma flow, optimize HPT design, and enhance thruster performance.

However, existing models for helicon sources and magnetic nozzles are separate, and coupling the two accurately is challenging. The plasma flow behaves differently in the source chamber and the magnetic nozzle, and the transition between these regimes is not well understood. To improve the accuracy of HPT modeling, a study is conducted to evaluate different coupling methods between fluid and Particle-In-Cell (PIC) solvers, with a focus on the 3D-VIRTUS numerical suite [M. Magarotto, S. Di Fede, N. Souhair, S. Andrews, F. Ponti, Numerical suite for cathodeless plasma thrusters, *Acta Astronautica*, Volume 197, 2022]. Two methods are investigated for mapping the transition between the fluid and kinetic regimes:

1. The first method involves finding the transition surface by analyzing the behavior of specific transition parameters, such as the plasma density and potential, which may vary depending on the particular HPT design and operating conditions. This method requires pre-modeling the entire thruster in the fluid model and mapping the transition surface to minimize the computational cost of applying the PIC model downstream of it.
2. The second method involves creating an artificial buffer region around or near the throat of the nozzle, where both fluid and kinetic regimes are solved simultaneously. This method requires iterative runs of the models with an updated plasma profile in the buffer zone.

Numerical simulations of plasma profiles of a real HPT thruster will be compared to experimental measurements for the different coupling approaches and analysed in terms of accuracy and computational

burden. Finding the best coupling method will not only improve the 3D-VIRTUS numerical suite's capability to simulate HPTs in an accurate yet computationally efficient fashion, but it will also provide insight into coupling other RF or microwave source chambers with magnetic nozzles in general.