

Feedforward of Sampled-Data System for High-Precision Motion Control using Basis Functions with ZOH Differentiator

Mae, Masahiro; van Haren, Max; Ohnishi, Wataru; Oomen, T.A.E.; Fujimoto, Hiroshi

DOI

10.23919/ACC53348.2022.9867640

Publication date

Document VersionFinal published version

Published in

Proceedings of the American Control Conference (ACC 2022)

Citation (APA)

Mae, M., van Haren, M., Ohnishi, W., Oomen, T. A. E., & Fujimoto, H. (2022). Feedforward of Sampled-Data System for High-Precision Motion Control using Basis Functions with ZOH Differentiator. In *Proceedings of the American Control Conference (ACC 2022)* (pp. 3350-3350). IEEE. https://doi.org/10.23919/ACC53348.2022.9867640

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

Green Open Access added to TU Delft Institutional Repository 'You share, we take care!' - Taverne project

https://www.openaccess.nl/en/you-share-we-take-care

Otherwise as indicated in the copyright section: the publisher is the copyright holder of this work and the author uses the Dutch legislation to make this work public.

Feedforward of Sampled-Data System for High-Precision Motion Control using Basis Functions with ZOH Differentiator

Masahiro Mae¹, Max van Haren², Wataru Ohnishi¹, Tom Oomen^{2,3}, and Hiroshi Fujimoto¹

Abstract—Feedforward control has an important role in high-precision mechatronic systems. The aim of this research is to design a discrete-time feedforward controller to improve on-sample and intersample errors. The developed approach is parameterized using a linear combination of parameters and basis functions, which results in a parameterization that has intuitive physical meaning. The basis functions are designed with a differentiator that considers the sampled-data and zero-order-hold aspects. The performance improvement is demonstrated by comparing the developed approach with a conventional basis function design for a motion system.

 $^{^1{\}rm The~University}$ of Tokyo, Japan. (mmae@ieee.org) $^2{\rm Eindhoven~University}$ of Technology, The Netherlands. $^3{\rm Delft~University}$ of Technology, The Netherlands.