



Delft University of Technology

Document Version

Final published version

Citation (APA)

Fărăgău, A. B., Metrikine, A., Paul, J., van Leijden, R., & van Dalen, K. (2024). *The influence of anomalous Doppler waves on the Hyperloop stability*. Abstract from The Third International Conference on Rail Transportation, Shanghai, China.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

In case the licence states "Dutch Copyright Act (Article 25fa)", this publication was made available Green Open Access via the TU Delft Institutional Repository pursuant to Dutch Copyright Act (Article 25fa, the Taverne amendment). This provision does not affect copyright ownership.
Unless copyright is transferred by contract or statute, it remains with the copyright holder.

Sharing and reuse

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

This work is downloaded from Delft University of Technology.



ABSTRACT

Title

The influence of anomalous Doppler waves on the Hyperloop stability

Andrei B. Fărăgău^{1*}, Andrei Metrikine¹, Jithu Paul¹, Rens van Leijden¹, and Karel van Dalen¹

¹Faculty of Civil Engineering and Geosciences, Delft University of Technology, the Netherlands

*Corresponding Author: a.b.faragau@tudelft.nl

Abstract

The Hyperloop is an innovative transportation system that is currently under development. It minimizes air resistance by enclosing the vehicle in a de-pressurized tube and eliminates wheel-rail contact friction through the use of an electromagnetic suspension/levitation, similar to Maglev trains. This design can potentially achieve much higher velocities compared to traditional railways, positioning the Hyperloop as an environmentally friendly alternative to air transportation.

A potential challenge for Hyperloop is ensuring the dynamic stability at large velocities, where multiple instability sources can be present. An apparent source is the electro-magnetic suspension (adopted by some designs) making a control strategy mandatory to ensure stability even at quasi-static velocities. A less obvious instability mechanism is that the vibration of a vehicle on an elastic guideway can become unstable when surpassing a critical velocity.

The authors have previously investigated the interplay between the electro-magnetic and wave-induced instability mechanisms and showed that the stability space changes significantly above a certain velocity. In other words, the control strategy can ensure the overall system stability only for a very limited range of its gains. The cause for this drastic change was attributed to the wave-induced instability mechanism. Metrikine demonstrated that this instability arises with the radiation of anomalous Doppler waves, which introduce more energy to the vehicle's vibration than normal Doppler waves radiate away from the vehicle. The current study demonstrates that the change of stability domain is indeed caused by the anomalous Doppler waves. While identifying unstable velocity regimes is practical for Hyperloop design, gaining insight into the contribution of individual instability mechanisms can be crucial for efficient mitigation.

Preferred Presentation Type

☒

Oral

☐

Poster

☐

Only proceedings

☐

No preference

List Relevant Conference Theme(s) below

New type of rail transport