













Floorplans




Opportunities & Restraints



Urban Masterplan




Ground Floor Connection




Elevations

West



East





South




North



Circulation design



Section A



Food market



Collective spaces



Corridors-dwelling connection



Dwellings Design





Outside





Dwelling Types


Solo-dweller apartments (1-2)




Co-housing units (6-8)




Family houses (3-6)




Rooftop Garden




Facade Fragment



1:10 Details



1:50




Used systems



Stabalux: (collective spaces)
- Self-supporting curtain wall
- Maximum thermal insulation
- Dismountable system
- Suitable for wooden supporting structure



Metaglas: (dwellings)
- thin window frames
- large openable area to create terrace environment




Staenis: (dry floor heating system)
- fast reaction time
- made from sustainable materials
- very light system
- high efficiency




Zigzagsolar: (solar facade)
- optimal energy production
- reducing heat stress on the facade
- creating natural sun protection


Climate section (industry)




Climate section (dwelling)




Rooftop climate concept




Structure



Axo



Indoor climate concept



Solar benefits

dwelling surface:
6,2*3,5*2 = 43,4 m²
solar panel surface:
0,35*36*2 = 25,2 m²
energy yield, East or West orientation:
125 kWh/m²
125*25,2 = 3150 kWh per (standard) dwelling (rendement circa 90%)
3150*0,90 = 2850 kWh
energy usage
1-2 person household = 1830 - 2850 kWh
total of the building:
2850*10*4*2*1,5 = 342000 kWh

Indoor climate

Heat/cold loss (winter)
Heating requirement per dwelling
Q = A * U * (delta)T
Qwinter = (7*6) * 1/5 * 30 = 252 W
Qcore = (7*6) * 1/3 * 5 = 70 W
Qtotal = 252 - 70 = 182 W
Heat/cold loss (summer)
Cooling requirement per dwelling
Q = A * U * (delta)T
Qsummer = (7*6) * 1/5 * 20 = 168 W
Qcore = (7*6) * 1/3 * 5 = 70 W
Qtotal = 168 + 70 = 238 W

Hydroponic farming

