



Delft University of Technology

Gas sensing with porous nanodrums

Roslon, Irek; Dolleman, Robin Joey; Solera Licon, Hugo; Lee, Martin; Siskins, Makars; Madauss, L.; Schleberger, M.; Alijani, Farbod; Steeneken, Peter

Publication date

2019

Document Version

Final published version

Citation (APA)

Roslon, I., Dolleman, R. J., Solera Licon, H., Lee, M., Siskins, M., Madauss, L., Schleberger, M., Alijani, F., & Steeneken, P. (2019). *Gas sensing with porous nanodrums*. Poster session presented at Graphene Week 2019, Helsinki, Finland.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.


*This work is downloaded from Delft University of Technology.
For technical reasons the number of authors shown on this cover page is limited to a maximum of 10.*

Gas sensing with porous nanodrums

I.E. Roslon¹, R.J. Dolleman^{2,3}, H. Licona², M. Lee², M. Siskins², L. Madauss⁴, M. Schleberger⁴, F. Alijani¹ and P.G. Steeneken^{1,2}

¹ Department of Precision and Microsystem Engineering, Delft University of Technology, The Netherlands,
² Kavli Institute of Nanoscience, Delft University of Technology, The Netherlands,
³ Institute of Physics, RWTH Aachen University, Germany,
⁴ Fakultät für Physik, Universität Duisburg-Essen, Germany



1 The device



The devices consist of two-layer graphene suspended over cavities. Lasers actuate the membrane thermally and detect its motion.

2 Gas-specific fingerprint

The frequency response of the drums shows two peaks in the imaginary part below the mechanical resonance.





The two peaks in the response describe thermodynamic properties of the system:

- ↓ Gas permeation time constant τ_{gas}
- ↑ Thermal equilibration time constant τ_{th}

3 Gas sensing

In the Knudsen regime, the permeation time depends linearly on the square root of the particle mass.

We have observed a gas specific response in pressures varying from 60 mbar to 1 bar and with poresizes from 10 to 400 nm.




The pore size, number of perforation and cumulative area can be adjusted to shift the permeation peak and investigate the transitional flow between molecular and continuum.

4 Thermal conduction

The gas opens a new thermal pathway, decreasing the thermal equilibration time constant.


The thermal equilibration time constant depends on the thermal contact of the membrane with the surrounding and the heat capacity of the membrane.



5 Microchannel flow

Here we show influence of a permeation resistance by a channel connecting the cavity with the pore.

The permeation time is 9 times longer through the 5 x 0.65 x 0.285 μm channel as compared to a direct connection.



6 Conclusion

We show a platform for studying nanoscale thermodynamics which can enable new types of permeation based gas sensors.

