

A close-up, low-angle shot of several parallel wooden planks. The planks are light-colored with a visible wood grain. Each plank has a small, dark, laser-cut number on its surface. The numbers are arranged in a sequence from left to right: L3-10, L3-11, L3-12, L3-11, L3-10, L3-9, L3-8, L3-7, L3-6, L3-5. The perspective is from a low angle, looking down the length of the planks, which creates a strong sense of depth and perspective. The lighting is even, highlighting the texture of the wood.

ROBOTIC WOOD CRAFTING

Daniel L. Fischer | 4502515



TUNDRA

2015 - Canadian Tundra



TUNDRA

2075 - Canadian Tundra

ARCTIC — GREENING

*„It is a fact, between 1984 and 2012,
30% of Canada became greener.“*




EFFECTS
thaw & vegetation shift




EFFECTS

thaw & vegetation shift




EFFECTS

thaw & vegetation shift




OPEN_PIT MINES

pits in Canada and the U.S.



OPEN_PITS

100 largest Open Pit Mines



NETWORK


100 largest Open Pit Mines

11




SITE

$64^{\circ}29'38,89''N$ $110^{\circ}14'34,95''E$



100km



Dhruv Airport

1000m





DIAVIK_MINE

64°29'38,89"N 110°14'34,95"E



DIAVIK_MINE


64°29'38,89"N 110°14'34,95"E

radiation max. ~1100 kwh/m²(a)
temperature -40°C - 25°C (avg. -6°C)
wind 0 - 75 km/h (avg. 12 km/h)
rain/snow avg. 150 mm/year

day lenght 5h - 21h
next city Yellowknife (308 km)
crate width ~ 900 m
crate depth ~ 250 m

ECO _____
TOURISM

*„responsible travel to natural areas
that conserves the environment [...]“*






Hotel Arctic, Greenland



Skylodge Adventure suites, Peru

REFERENCES

conceptual & programmatic





CONDITIONS


wind turbines & runway



RESTORE NATURE


dismantling industrial plants






TOPOGRAPHY

diagram




RADIATION

analysis of the sun



**CHOSEN
SITE**


64°29'38,89"N 110°14'34,95"E







VERTICAL GROWTH

agent based system studies












MATERIALI- SATION

optimizing connectivity





31



SITEPLAN


optimizing connectivity

32




SITUATIONS

optimizing connectivity





SITUATIONS

optimizing connectivity




SITUATIONS

optimizing connectivity




SITUATIONS

optimizing connectivity




SITUATIONS

optimizing connectivity




SITUATIONS

optimizing connectivity





NETWORK

64°29'38,89"N 110°14'34,95"E




NETWORK

details 1:100



LONG-TERM UNIT

details 1:100



0m

-225m






**INFORMED
GEOMETRY**

details 1:100





REFERENCES INTERIOR

double curved CLT




HOUSING UNIT

details 1:100



GREENHOUSE SECTION



details 1:100



GREENHOUSE


0

details 1:100




**SECTION
0**


details 1:100



UNIT
-1
details 1:100




UNIT
-2
details 1:100




ERGERGY CONCEPT

solar energy & ground storage










**MATERIAL
RESEARCH**





CANADIAN WOOD

dark & white spruce; birch, aspen





PROTO-TYPING

freeform wood panels



TRADITIONAL CLT

CLT fabrication principle




FREEFORM CLT

double curved CLT




PROTOTYPE_01

double-curved & cross-laminated




MOLDING

double curved CLT




CONSTRUCTION


iterative subdivision




CLT floor



*freeform beams
(main vertical structure)*





*CLT panels
(reinforcement)*



combined result

CONSTRUCTION


constructive elements






PROTOTYPE_02


riveted wood strips



**RESEARCH
GEOMETRY**

geometric preparation






SUBDIVISION

linear subdivision into strips






SUBDIVISION

linear subdivision into strips






WOOD STRIPS

parametric thickness






**WOOD
STRIPS**

cross layering



WOOD STRIPS

cross layering




**UNIQUE
STRIPS**

complex bended wood


**VIDEO
STRIPS**



iterative subdivision



VIDEO


iterative subdivision





INTEGRATION INTO STRIPS



iterative subdivision



FABRICATION



robotic milling + steam bending

- 1 100mm CLT panel
5 layer 12mm birch,
weather sealed
- 2 360 mm wood fiber insulation
 $\lambda_D 0,036 [W/(m^*K)]$
- 3 vapour barrier
- 4 10 mm birch strips,
riveted
- 5 beam, birch
robotically cut
- 6 high insulation window,
triple glazed
wood frameing
- 7 wind barrier



CONSTRUCTION

section 1:20



1:5

horizontal + vertical



EXTERIOR
perspective impression