

Experimental characterisation of self-healing in reconstituted Boom Clay

Chandan Malagar, B.R.; Vardon, P.J.; Dieudonné, A.A.M.

Publication date

Document VersionFinal published version

Citation (APA)

Chandan Malagar, B. R., Vardon, P. J., & Dieudonné, A. A. M. (2022). Experimental characterisation of self-healing in reconstituted Boom Clay. Poster session presented at 8th International Conference on Clays in Natural and Engineered Barriers for Radioactive Waste Confinement, Nancy, France. https://hopscotch.key4events.com/AbstractList.aspx?e=190&preview=1&aig=-1&ai=13915

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights. We will remove access to the work immediately and investigate your claim.

Green Open Access added to TU Delft Institutional Repository 'You share, we take care!' - Taverne project

https://www.openaccess.nl/en/you-share-we-take-care

Otherwise as indicated in the copyright section: the publisher is the copyright holder of this work and the author uses the Dutch legislation to make this work public.

EXPERIMENTAL CHARACTERISATION OF SELF-HEALING IN RECONSTITUTED BOOM CLAY

TOPIC 04: Hydro-mechanical properties

B. Chandan Malagar ¹, P. Vardon ¹, A.C. Dieudonné ¹. ¹Delft University Of Technology - Delft (Netherlands)

Abstract

Disposal of radioactive waste in deep and stable geological formations is considered a feasible approach to isolate these wastes from anthropogenic activities and the environment over a long time period. Argillaceous formations are proposed as one of the suitable host rocks for such infrastructure thanks to their low permeability, high sorption capacity and propensity to plastic rather than brittle deformation. As a result of tunnel excavation, the host rock will experience significant stress redistribution, leading to local failure of the material, the creation of excavation damage zone and a local increase of the host rock permeability. Nevertheless, laboratory and field experiments have shown that these fractures disappear or seal naturally with time (Meier et al., 2000, Bastiaens et al., 2007, Zhang, 2013). This specific behaviour has been attributed to the high plasticity and swelling of clay minerals (hydraulic) and increase in mean stress (mechanical) after the closure of facilities. Studies focusing on sealing of fractures have generally quantified these characteristics in terms of decrease in hydraulic conductivity and increase in fracture volume when it interacts with water. (De La Vaissière et al., 2014, Auvray et al., 2015). However, limited quantitative information is available on mechanical properties of self-healed fractures in preferred host rocks. Therefore, this work focuses on evaluating the recovery of strength along a discontinuity in reconstituted Boom Clay samples under different normal stresses. Normal stress is a crucial parameter affecting shear strength within continuums and the effective contact area between two surfaces of a discontinuity. This work investigates the amount of selfhealing in reconstituted Boom Clay under variable normal stresses and testing conditions (direct shear and rotary shear conditions). Further, it aims at supporting the development of models for the post-closure strength recovery of host rock for radioactive waste repositories.

References

Auvray, C., Morlot, C., Fourreau, E., & Talandier, J. (2015). X-RAY TOMOGRAPHY APPLIED TO SELF-HEALING EXPERIMENTS ON ARGILLITES. 13th International Congress of Rock Mechanics, May, 1–12.

Bastiaens, W., Bernier, F., & Li, X. L. (2007). SELFRAC: Experiments and conclusions on fracturing, self-healing and self-sealing processes in clays. Physics and Chemistry of the Earth, 32(8–14), 600–615.

https://doi.org/10.1016/j.pce.2006.04.026

De La Vaissière, R., Armand, G., & Talandier, J. (2014). Excavation damaged zone under imbibition: Evidence of self-sealing into claystone. Unsaturated Soils: Research and Applications - Proceedings of the 6th International Conference on Unsaturated Soils, UNSAT 2014, 2(May 2019), 1481–1487. https://doi.org/10.1201/b17034-216

Meier, P. M., Trick, T., Blümling, P., Vockaert, G., Parc, A., Croix, D., & Monnet, J. (2000). SELF-HEALING OF FRACTURES WITHIN THE EDZ AT THE MT. TERRI ROCK LABORATORY: RESULTS AFTER ONE YEAR OF EXPERIMENTAL WORK. Proceedings of International Workshop on Geomechanics, Hydromechanical and Thermohydro-Mechanical Behaviour of Deep Argillaceous Rocks: Theory and Experiment, 1, 267–274.

Zhang, C. L. (2013). Sealing of fractures in claystone. Journal of Rock Mechanics and Geotechnical Engineering, 5(3), 214–220. https://doi.org/10.1016/j.jrmge.2013.04.001