Appendix

Increasing Perceived Viral Safety in Air Travel

Master thesis
Maciej Zawierucha
Faculty of Industrial Design Engineering
Delft University of Technology







Master Thesis

Delft, April 2021

Maciej Zawierucha

MSc, Integrated Product Design Delft University of Technology Faculty of Industrial Design Engineering

Supervisory team

Chair

Prof. Dr. Peter Vink Department of Environmental Ergonomics Faculty of Industrial Design Engineering

Mentor

Ir. Wim Schermer Department of Human-Centered Design Faculty of Industrial Design Engineering

Company mentor

Luciana Říbeiro Monteiro Technology Development Analyst Embraer Netherlands, B.V.







4 · Table of contents

Table of contents • 5

Table of contents

Appendix A - Project Brief	6
Appendix B - Data processed from literature research	14
Appendix C - Interview guide	18
Appendix D - Processing interviews - 9 cabin moments	22
Appendix E - Processing interviews - Quirkos analysis report	28
Appendix F - Co-creation session presentation	30
Appendix G - Co-creation session voting sheet	44
Appendix H - Overview of existing concepts	46
Appendix I - Rapid prototyping	54
Appendix J - Harris Profile	58
Appendix K - User test plan	62
Appendix L - Presentation for a product designer	64
Appendix M - Materials and processes inventory	68
Appendix N - Comparison of impacts of iterations 2 and 3	70
Appendix O - EcoAudit report generated with Granta EduPack software	72
Appendix P - EcoDesign strategies for product optimization	84

Project Brief



Procedural Checks - IDE Master Graduation	ŤU Delft
APPROVAL PROJECT BRIEF To be filled in by the chair of the supervisory team.	
chair <u>PeterVink</u> date <u>23- 9- 2020</u> sig	gnature
CHECK STUDY PROGRESS To be filled in by the SSC E&SA (Shared Service Center, Education & Student Affairs), after a The study progress will be checked for a 2nd time just before the green light meeting.	pproval of the project brief by the Chair.
Master electives no. of EC accumulated in total: ECEC	all 1st year master courses passed
Of which, taking the conditional requirements into account, can be part of the exam programme EC	missing 1st year master courses are:
List of electives obtained before the third semester without approval of the BoE	
name date si	gnature
FORMAL APPROVAL GRADUATION PROJECT To be filled in by the Board of Examiners of IDE TU Delft. Please check the supervisory team: Next, please assess, (dislapprove and sign this Project Brief; by using the criteria below.	and study the parts of the brief marked **.
	PROVED NOT APPROVED
the student (taking into account, if described, the activities done next to the obligatory MSc specific Procedure: AP	PROVED NOT APPROVED
courses)? Is the level of the project challenging enough for a MSc IDE graduating student? Is the project expected to be doable within 100 working days/20 weeks? Does the composition of the supervisory team comply with the regulations and fit the assignment?	
	comments
name date si	gnature
IDETU Delft - E&SA Department /// Graduation project brief & study overview /// 2018-01 v	

Project Brief

TuDelft

Personal Project Brief - IDE Master Graduation

Increasing passengers' perceived safety in post-pandemic air travel

Please state the title of your graduation project (above) and the start date and end date (below). Keep the title compact and simple. Do not use abbreviations. The remainder of this document allows you to define and clarify your graduation project.

start date 28 - 09 - 2020 08 - 03 - 2021 end date

INTRODUCTION 5

Please describe, the context of your project, and address the main stakeholders (interests) within this context in a concise yet complete manner. Who are involved, what do they value and how do they currently operate within the given context? What are the nain opportunities and limitations you are currently aware of (cultural- and social norms, resources (time, money...), technology,...)

The COVID-19 pandemic had a huge impact on the aviation industry in 2020. Companies across the entire supply chain faced job cuts and financial difficulties due to a sharp decline in air travel, mainly caused by government restrictions and people being less willing to fly (fig. 1). Air travel facilitates the potential spread of viruses over long distances and should not be encouraged during periods of increased risk of infection. However, as with any mean of mass transport, every effort should be made to reduce these risks when travelling.

This project is in collaboration with Embraer, an international aircraft manufacturer that seeks ways to improve passengers' viral safety in air travel. This is to ensure that its airplane cabins will not only be more resistant to viruses, but also regarded as such by the passengers.

According to the latest knowledge, coronavirus primarily spreads through contact and respiratory droplets (1). This is especially relevant in economy seats class where passengers sit close to each other. A study on COVID-19 concerns shows that the fear of sitting next to an infected person in the plane is the biggest factor discouraging from flying. One-third of the respondents are planning to avoid air travel in the near future as a continued measure (2). This shows that the pandemic is likely to have long-term effects on attitudes towards flying, with an increased need for viral safety measures throughout the journey. By implementing them, aviation companies can ensure better handling of its passengers and make flying more resilient in the future.

Another important aspect is how safe people feel with these measures. Passengers perceive safety differently than aviation specialists, because their decisions are based not only on facts but also on fears (3). Their evaluation is more unpredictable and may differ from what is really effective. This thesis will focus on solutions that will be perceived as safe among passengers, to ensure that a pleasant travel experience is not compromised in the post-pandemic travel.

Embracer is involved in many environmental initiatives such as the DIPAS program, set to reduce fuel consumption, CO2 emissions, the use of harmful materials, etc. in their products (4), To reflect Embrace values, TU Delft's mission, and ypersonal goals, an important criterion in this project will be the low environmental impact of the chosen concept.

This project will be developed for the Flying V plane concept, which is currently being developed in a collaboration between TU Delft and several aviation-related companies, including Embraer. This new type of plane will use aboning 20% less fuel than the leading industry plane, Airbus ASSo, bringing significant cuts in carbon emissions in commercial aviation. The advantage of the Vs interior layout is the arrangement of economy seats in diagonal rows, which reduces physical contact of passengers compared to current airplanes (fig.2). This is a good starting point for developing a truly virus-proof plane interior, which will promote Flying V as a resilient and sustainable solution for air travel. For Embraer, the findings from this project may help improving the safety of its current and future products.

To ensure feasibility, the developed concepts will be assessed in terms of the current EASA guidelines for cabin safety and accessibility, as well as ICAO COVID-19 Passenger-Crew and Disinfection guidelines (5).

space available for images / figures on next page

IDE TU Delft - E&SA Department /// Graduation project brief & study overview /// 2018-01 v30 Page 3 of 7
Initials & Name M. Zawierucha Student number 4859502

Title of Project Increasing passengers' perceived safety in post-pandemic air travel

TUDelft

Personal Project Brief - IDE Master Graduation




image / figure 1: Number of scheduled passengers boarded by the global airline industry from 2004 to 2021 (6)



image / figure 2: The Staggered Seat in the Flying V interior (7).

IDE TU Delft - E&SA Department /// Graduation project brief & study overview /// 2018-01 v30 Page 4 of 7
Initials & Name M. Zawierucha Student number 4859502

Title of Project Increasing passengers' perceived safety in post-pandemic air travel

Project Brief

TuDelft

Personal Project Brief - IDE Master Graduation

PROBLEM DEFINITION *

Limit and define the scope and solution space of your project to one that is manageable within one Master Graduation Project of 30 FC (= 20 full time weeks or 100 working days) and clearly indicate what issue(s) should be addressed in this project.

This project focuses on designing aircraft interior element(s) that will reduce the spread of coronavirus and increase the perceived safety among passengers.

The COVID-19 pandemic in 2020 raised many concerns about the viral safety of airplane interiors. People are less willing to fly as they fear sitting next to an infected person. Known issues facilitating the spread of viruses in the cabin is the contact between passengers and the spread of respiratory droplets. Another problem is the sense of safety of passengers, which may differ from what is really effective and can have a big impact on the well-being during the trip.

For this, the perception of safety will be researched. Concepts that minimize the spread of vinuses will be generated, tested with users, and evaluated in the scope of ergonomics and their environmental impact. Furthermore, concepts will be assessed against avaition safety and disinfection guidelines to ensure their feasibility in the current context. This project will be developed on the full-scale model of the "Staggered Seat", an economy class seat in the Flying V interior, available at the Industrial Design Engineering faculty building.

In order to make the project manageable within given time, the COVID-19 will be te only type of virus taken into account. The cabin airflow and the airborne transmission (unlikely way of infection), as well as the use of the on-board lavatories will be left out of scope. Nonetheless, these aspects will be considered during consultations with experts.

ASSIGNMENT **

State in 2 or 3 sentences what you are going to research, design, create and / or generate, that will solve (part of) the issue(s) pointed out in "problem definition". Then illustrate this assignment by indicating what kind of solution you expect and / or aim to deliver, for instance: a product, a product-service combination, a strategy illustrated through product or product-service combination ideas, In case of a Specialisation and/or Annotation, make sure the assignment reflects this/these.

Design aircraft interior element(s). that will lincrease viral safety, by reducing the contact and evoking the sense of safety among passengers. Explore what influences perception of safety, ideate concepts and test with users. Consider the product's environmental impact and aviation industry quidelines.

The project is expected to result in a product/set of products that will improve the viral safety and perceived safety among the passengers of the economy class in the Flying V cabin. The main criteria when choosing the concept will be their COVID-19 safety, perceived safety, environmental impact, and compliance with aviation guidelines. Several aspects will be considered to address the comfort of passengers and flight attendants, such as intuitiveness, accessibility, and easy maintenance.

Research questions:

What interior elements will reduce contact and spread of droplets between passengers? What are the factors influencing people's perception of viral safety when flying? How to reduce the passengers' fears of catching a virus in the plane cabin, while not decreasing their sense of responsibility?

IDE TU Delft - E&SA Department /// Graduation project brief & study overview /// 2018-01 v30 Page 5 of 7


Initials & Name M. Zawierucha Student number 4859502

Title of Project Increasing passengers' perceived safety in post-pandemic air travel

Personal Project Brief - IDE Master Graduation

DI ANNINC AND ADDDOACH **

Include a Gantt Chart (replace the example below - more examples can be found in Manual 2) that shows the different phases of your project, deliverables you have in mind, meetings, and how you plan to spend your time. Please note that all activities should fit within the given net time of 30 EC = 20 full time weeks or 100 working days, and your planning should include a kick-off meeting, mid-term meeting, green light meeting and graduation ceremony. Illustrate your Gantt Chart by, for instance, explaining your approach, and please indicate periods of part-time activities and/or periods of not spending time on your graduation project, if any, for instance because of holidays or parallel activities.



The planning of this graduation project follows the Double Diamond method (8), which distinguishes the project into different phases of divergent and convergent thinking approach: Discover, Define, Develop and Deliver.

Discover phase will focus on gathering information, which will mainly involve literature research, conducting interviews, and identifying the needs of stakeholders These will be followed by the problem definition. Next, in the Define phase, concepts will be generated and tested with users. They will be assessed in the scope of the ergonomics, environmental impact and the aviation industry guidelines. Three to five concepts will be chosen and developed using rapid prototyping. In the Develop phase, chosen concepts will be assessed with experts to ensure feasibility and meeting client's needs. The selected concept will be further developed by a mean of of a full-scale prototype. This will be concluded with a final validation of the developed concepts with experts. The last phase, Deliver, will consist of making recommendations, finalizing the report, creating a presentation and developing the concept showcase.

As research on the COVID-19 virus is still ongoing, new discoveries could impact the process at any stage of the project. Adjustments in the planning may be necessary to ensure the relevance of the outcome.

Two trips to Poland (one in October, one in December) regarding family matters and the Christmas/New Year period, will push back the final presentation date by three weeks.

IDE TU Delft - E8	SA Depar	tment /// Graduation project brief & study overview	/// 2018-01 v30	Page 6 of
Initials & Name	М.	Zawierucha	Student number 4859502	
Title of Project	Increasir	ng passengers' perceived safety in post-pandem	nic air travel	

Appendix A 12 · Appendix A Appendix A · 13

Project Brief

TuDelft

Personal Project Brief - IDE Master Graduation

MOTIVATION AND PERSONAL AMBITIONS

Explain why you set up this project, what competences you want to prove and learn. For example: acquired competences from your MSc programme, the elective semester, extra-curricular activities (etc.) and point out the competences you have yet developed Optionally, describe which personal learning ambitions you explicitly want to address in this project, on top of the learning objectives of the Graduation Project, such as: in depth knowledge a on specific subject, broadening your competences or experimenting with a specific tool and/or methodology, ... Stick to no more than five ambitions.

For years now, I have been pursuing designing sustainable future mobility. This is reflected in my projects, such as Haibu - a vehicle concept for future megacities, Ford Omni - autonomous delivery van that reduces city congestion, or Ecotap EVY - an electric car charger for home use. My interest for innovative transportation led me to a recent participation in the Delft Hyperloop dream-team, where I gained experience while developing an interior concept of the full-scale hyperloop pod. Next to this, I researched the perception of safety in autonomous modes of mass transport. This project piqued my curiosity about how people's relationship with innovative means of transport will develop. In my thesis, I want to broaden my competencies into a new field of transportation, which is air travel. I believe that the chosen topic will allow me to learn on how to react to unexpected circumstances in a technically advanced field of transportation, develop a relevant and topical product, and make a one step closer towards promoting sustainable and resilient future mobility.

I am looking forward to working with Embraer, a progressive transportation company where I could learn to collaborate with professionals in my field of interest, and create a link to the future employment opportunities at design consultancies such as PriestmanGoode or Layer Design.

Furthermore, I would like to prove the competences acquired throughout my Master's courses at TU Delft, among which are: ACD, where I could further develop my conceptualization and visualisation skills (2D animation, 3D modelling, rendering), AED, where I gained experience in advanced prototyping and user testing, and Sustainable Design Strategies elective, which taught me the application of different sustainable strategies (Ecowheel, C2C, Biomimicry) into real-life projects.

References:

[1] World Health Organization: WHO. (2020, July 9). Transmission of SARS-CoV-2: implications for infection prevention precautions. WHO.

https://www.who.int/news-room/commentaries/detail/transmission-of-sars-cov-2-implications-for-infection-preventio n-precautions#:%7E:text=To%20the%20best%20of%20our,of%20COVID%2D19.

[2] Rockland, D. B. (2020). Air Traveler Response to COVID-19. IATA.

https://www.iata.org/contentassets/5f8235a4ef364ec886ad2594531c04d0/2020-07-07-01-sp.pdf

[3] Mauro, R. (2019). Perception of Aviation Safety. Risk Engineering, 119–137.

https://doi.org/10.1007/978-3-030-11456-5_8

[4] Embraer. (n.d.). Sustainability. https://embraer.com/global/en/sustainability

[5] Aircraft Module. (n.d.). ICAO. https://www.icao.int/covid/cart/Pages/Aircraft-Module.aspx

[6] Statista. (2020). COVID-19 gives us a chance to design an aviation industry fit for the future [Figure].

https://www.weforum.org/agenda/2020/06/covid-19-sustainable-aviation/

[7] Vink, P. (2020). Towards a hybrid comfortable passenger cabin interior for the flying V aircraft [Photograph]. https://www.researchgate.net/publication/339440026_Towards_a_hybrid_comfortable_passenger_cabin_interior_for _the_flying_V_aircraft_-_viewcontentcgi/figures

[8] What is the framework for innovation? Design Council's evolved Double Diamond. (2019, September 10). Design Council. https://www.designcouncil.org.uk/news-opinion/what-framework-innovation-design-councils-evolveddouble-diamond

Due to concerns around increased COVID-19 infections at the start of the project, and a possible closure of TU Delft facilities, the execution of some planned activities might be limited, such as user testing or working with the full-scale scale seat model located at the faculty.

IDE TU Delft - E8	SA Department /// Gradu	uation project brief & study overview	/// 2018-01 v30		Page 7 of 7			
Initials & Name	M. Zawierucha		Student number	4859502				
Title of Project	Title of Project — Increasing passengers' perceived safety in post-pandemic air travel							

Data processed from literature research, grouped



Data processed from literature research, clustered



Interview guide - Flight attendants

Interview guide - FLIGHT ATTENDANTS

Increasing passengers' perceived safety in post-pandemic air travel

This research focuses on investigating how the plane passengers perceive safety in the plane cabin during pandemic and how it influences their behavior. This is with an aim to address their concerns when flying and help them rebuild trust in flying after the pandemic.

INTERVIEW QUESTIONS

1. Introduction questions

- a. What was your last flight destination?
- b. Are you flying less during a pandemic? Why exactly?

2. Perception of safety

- a. Using the scale provided, indicate which setting do you think is safer from catching viruses like COVID-19. Why do you think so?
- b. Do you think the level of safety changes for longer flights such as from the Netherlands to New York, compared to short ones, like the Netherlands to Paris? Why do you think so?
- c. The image provided shows common activities when travelling by plane. Please look at each step of the journey, and think of how safe or unsafe it feels for you in the scope of viral safety from your perspective. Rate it from 1 to 5 using the scale provided, and explain why you gave it such a grade.



tering the plane



Walking through the all Looking for a seat



Storing luggage in the ov



4. Taking your sea



5. Sitting in the co.



6. Flight Attendants servi



8. Any other activ

- d. What was your biggest safety concern when being inside the cabin during a pandemic? Why did you feel it?
- e. Was there something that made you feel safe against viruses in the plane cabin? Why does it make you feel in that way?

f. What do you think could be improved to make you feel safer against viruses when being inside of the cabin? You can provide ideas for each step of the journey.

3. Passenger behavior

- a. When being inside the cabin, did you observe any behaviors among passengers that negatively impact viral safety? What were these behaviors and why did they make you feel unsafe? Why did they do it?
- b. Are there any measures you wish were executed better by the passengers or other members of the crew? If yes, what are they and why do you think they could be improved?
- c. Can you think of any measures for passengers in the cabin that would increase your feeling of safety?

4. General questions

- a. Do you think the flight attendants are protected well against viruses in the plane cabin?
- b. What would be your main message to passengers when flying during a
- c. What do you think should be changed in the aviation industry to convince people to fly in the future?

Interview guide - Passengers

Interview guide - PASSENGERS

Increasing passengers' perceived safety in post-pandemic air travel

This research focuses on investigating how the plane passengers perceive safety in the plane cabin during pandemic and how it influences their behavior. This is with an aim to address their concerns when flying and help them rebuild trust in flying after the pandemic.

INTERVIEW QUESTIONS

1. Introduction questions

- a. What was your last flight destination?
- b. What was your motivation to fly?
- c. Did you travel alone or with someone?
- d. Are you flying less during a pandemic? Why?

SLIDE 1

2. Perception of safety

- a. Using the scale provided, indicate which setting do you think is safer from catching viruses like COVID-19. Why do you think so?
- b. Do you think the level of safety changes for longer flights such as from the Netherlands to New York, compared to short ones, like the Netherlands to Paris? Why do you think so?

SLIDE 2+3

c. The image provided shows common activities when travelling by plane. Please look at each step of the journey, and think of how safe or unsafe it feels for you in the scope of viral safety. Rate it from 1 to 5 using the scale provided, and explain why you gave it such a grade.













d. What was your biggest safety concern when being inside the cabin during a pandemic? Why did you feel it?

- e. Do you think you will still have these concerns after the pandemic is gone?
- f. (If a participant flew with someone) Were you concerned about the safety of your co-traveller(s)? If yes, why were you concerned?
- g. Was there something that made you feel safe against viruses in the plane cabin? Why did it make you feel in that way?
- h. What do you think could be improved to make you feel safer against viruses when being inside of the cabin? You can provide ideas for each step of the

3. Passenger behavior

- a. When being inside the cabin, did you observe any behaviors among passengers that made you feel less safe against viruses? What were these behaviors and why did they make you feel unsafe? Why did they do it?
- b. Are there any measures you wish were executed better by the passengers or a crew? If yes, what are they and why do you think they could be improved?
- c. Can you think of any measures for passengers in the cabin that would increase your feeling of safety?

4. General questions

- a. Are you willing to go back to your normal flying patterns right after the pandemic is over? After a year? Would you change them? Please explain.
- b. If the negative things you mentioned before were improved, would you go back to your normal flying patterns faster? If not, what would?
- c. Would you pay more for a ticket if the safety measures you mentioned were implemented? How much more? 30%, 70%, 100% and more?
- a. What do you think should be changed in the aviation industry to convince people to fly in the future?

Processing interviews - 9 cabin moments

Activity	Entering the plane	Walking through the alley Looking for a seat	Storing luggage in the overhead compartment	Taking your seat	Sitting in the seat	Flight Attendants service	Eating	After landing - disembarking	using toilet
Indicative image		v							
high concern	2	2,2,3	3,3	2,2,2	1,2,2	1,1	1,1,1,2	1,1,1,3,3,2	1,2
all grades	5,3,5,4,4,5,4,5,4,5	4,2,2,3,1,5,4,5,2,2	2,1,5,3,1,5,3,4,3,3	2,1,4,4,2,5,4,3,4,4	2,2,2,4,2,5,3,5,4,5	3,1,3,2,4,5,2,5,2,5	1,1,2,2,2	1,3,1,3,1,5,4,3,	1,2,3,3
average grade	4.4	3	3	3.3	3.4	3.4	1,5	2.7	
overall priority	LOW	MED	LOW	MED	MED	MAX	MAX	MAX	MED
MA grade	5	4	2	2	2	3	1	1	1
description	entering the plane was okay because the artifue, [removed, allowed only 10 people artifue, let a supplied the plane of the	I was welfaing through the conforce and three was this woman, she was in a humber was this woman, she was in a humber was the humber and the file of the cashed my back, and I felt file, all the measures now are weald, because the measures now are weald, because the cashed th	And then he third one, the blagging comparising, everyone is louching it. Comparising the comparising comparising the comparising the comparising the comparising the control of the comparising the comparison that the compa	I think it was clay, but when I was sitting in the contine place, and then there were in the contine place, and then there were in the contine place in the contine the contin	Amsterdam to Istanbul it wasn't really full, so they arranged the seats like, try to keep the distance from each other. I had a seat gap between the other passenger and I felt really safe. And I thought "Okay, if I stay this way, I could travel more often with planes". But when I was going back, it was sunday evening, it was full, people were in a hurry, and then the passenger	but I didn't know they changed the meal after corona, so I kept myself hungry before the flight, and that was a studid idea. When I saw the meal, I thought "I hope I will survive this flight", because I		And then during landing, they announced, "please means assisted, only leave affect, and the second of t	had to again be really close to them, maybe have physical contact with them, which felt really unsafe. Being inside of the toilet made me feel safer because there were no people around me and I
AG grade	3	2	1	1	2	1	1	3	-
description	I was feeling neutral.	front of me it was quite crowded. And there was also because I was one of the last people so their were people on the side yiety were to his off, and on the left and the left was in the left and the left mask in the correct way so covering their mask in the correct way so covering their mose and face. Just when I realised and was finally able to see those people and was finally able to see the way they're wearing masks it made me feel less safe and but then it was the way they was they was the way they was they was the way they was they was the way they was they was the way they was they was the way the way they was the way they was the way the way they was the way they was the	touching that person to get there I'm not veren sure if my luggage was cyllus heavy and I had problems if someone came to help me. So I voud choose this as one as I am so close to other people. It cannot keep dislance anymore.	I was sitting close to the window so I assed the person to stand up and let me saked the person to stand up and let me control to the saked the person. The gave me the space. It's not the maximum.	control just not trying to, I don't know, hold y arms close, be aware what i'm doing with my hands not to touch to many things and a just living allon on talking to things and a just living allon on talking to much as possible sitting that close, but much as possible sitting that close, but and experienced that someone was not wearing a mask, he was taking it off during the flight. But asked the person if he can put it back. He was nice and he said sure.	For me it's so crazy that it slist happens, it is like what I doll bought an expensive fight from the Netherlands to Poland. It is suffered to the slist of the slist slight. But what happened is the opposite because (emoved) was serving food to everyone on the plane.	was just in shock. A I was keeping my mask. I didn't take it off for a minute but I was extremely feeling unsafe. One person next to me was just without a mask and everyone was without the	again I was sitting until almost the end so that Locald be the last person to leave so no people behind my arm, just I profer not have so no people behind my arm, just I profer not the stay to only in fort of me! Loss keep a distance and also I don't breathe on them they don't breathe on my back. I would say the to quite meutral, three.	
ME grade	5	-	5	4	2	3		1	using toilet - 2
description	I think the person welcoming you was also wearing a mask, so that was fine.	Well, because over there everyone was arready obser to each other and you're in each other's social area with people that you don't know and laid it was my first out offer know and laid it was my first everyone sitting and then you see like, www. these are actually quite a lot of people. And so that moment had a big impact I would say.	it was fine but I felt a bit hurried. But it was safe.	I think I had a seat in the middle so I didn't have to pass anyone.	I when I was doing the belts, you sort of have to took neach other and that was just very new for me in that whole period of time	they didn't come by, so neutral or no answer.	Did not eat during a flight	I got a bit annoyed, my boyfinend as well, because they sensively asked you to stay seated until they open the doors, so everyonic can walk of Just one by one, annoying. Because they first lo give you her right information and they try to guide you, but in the end no one did the thing, to that was just very annoying and so that was just very annoying and grabbing their shiff. It was unsafe. Also annoying.	there's not a ki of space to stand. If there is someone in fort of you waiting for it as well then you go back into the cabin and then yourse to wome or to the admit then yourse to wom ore to the admit then yourse to wom
SS grade	4	3	3	4	4	3	2	3	3
SS grade	you're not really close to people and		I don't feel that unsafe. It's not fully safe because you're still moving and people	I was sitting there in a window seat and then when I arrived there was no one.		they still serve meals during the flight.	Well I kind of feel somewhat unsafe that time because allthough they announced that it is suggested for you to have a different dining time than people around	There were less people so I don't think it was really crowded at that time. It was really smooth when I got out, so I felt	I'm sitting in a window seat, so at that point it was somewhat unsafe because I have to pass through my neighbor. But the one on the aisle seat, he was actually
description	people are wearing masks and I think the cabin crew is really aware of what they're doing in terms of safety.		are still around you.	That was somewhat safe. But the thing is that I sanitized my whole seat, to make myself feel safer.			omerent aining time than people around you. I'm one seat apart from that neighbor, but I didn't talk with him so yeah we both had received the meal at the same time, and that was somewhat not safe for me. But I just want to eat so I didn't think that much about it. After landing.	neutral because there were a lot of people but I saw that people were wearing masks and there's less people so I didn't feel that unsafe.	the one on the asses seat, ne was accually well thoughful, he just went all the way to the middle to walf for me to pass. So I think that in that sense if feels safe. Also after we used the bathroom the cabin crew sanitized everything with alcohol after every use so in that way I felt safe.

Processing interviews - 9 cabin moments

2,2,3	3,3	2,2,2	1,2,2		1,1,1,2	1,1,1,3,3,2	1,2
,5,4,5,4,5 4,2,2,3,1,5,4,5,2,2	2 2,1,5,3,1,5,3,4,3,3	2,1,4,4,2,5,4,3,4,4	2,2,2,4,2,5,3,5,4,5	3,1,3,2,4,5,2,5,2,5	1,1,2,2,2	1,3,1,3,1,5,4,3,	1,2,3,3
3	3	3.3	3.4	3.4	1,5	2.7	
MED	LOW	MED	MED	MAX	MAX	MAX	MED
you pass quite a few g	people That's the beginning of the flight, and people are still kind of wandering aroun the cabin.	I think obtained such any our seal to very saintly represent the same kind of timeframe.	 think that really depends on the behaviour of the people sitting next to you. If there's like somebody coughing or something. Even if it doesn't sound serious. It kind of 	when she's talking to me, I think they are kind of trained how to do it and I think they also probably have to take a lot of tests, so they more less know what's their	Did not eat on the flight	I think a bot of people, at least on my flight, are really availing to go out of the plane and maybe be less cultious on more chaos. But on the other hand it is because they don't want to be in the plane anymore.	
5	5	5	5	5	2	5	2
they were also boardi rows to the front rows walking through like a because you don't hat	only me and only one person in front of me so we just gave each other space at time.	every row has only one or 2 people, if the	I was alone	the flight attendants were wearing surgical face masks and they never removed it, always kept it on and they were really professional I think.	Now I'm not sure, I would and say two but it's more like my personal idea. You are supposed to wear masks and the flight is	row by row, starting from the beginning to the end, and if someone was trying to anyway you get up, the flight attendants	
4	3	4	3	2		4	3
sesengers at a time. So they're such other. They commit process, And with they can they have the speak to be speak to they can be speak to they can be speak to they can keep some led of the speak to they can keep some led of the speak to they can keep some led of the speak to t	e very close. Maybe they don't really need to touch it, they ju each other, "Can I put their bags and I think well that must	I thick all the seats and the tables have been cleaned by a cleaning staff at the airport. So it should be safe. Also they have the bowel is only can clean their have the bowel so they can clean their resisting next to other people. Maybe your saffiting next to other people. Maybe you can pass to your seats. But I think that are that they have the ask him to get up so you can pass to your seats. But I think that are that they have the safe that they have the	travel companion. Maybe there is a stranger next by vo. But I see people are stranger next by vo. But I see people are time. Yeah, I don't see a lot of interaction between passengers who don't know each other companions of the people with	sure if the face mask will keep the virus misle. And it is all on the camont have with misle and the passes of the camont have a mind have with the passes of the passes of the passes of the passes of the most hard with the passes of the pas	N/A	Again, many people are close to each other. They had to wait until the doors were open. And we still ask them to wait until the other them has until the row before them has the still ask them to wait until the properties of the plane has landle and the plane has landle and they and the plane has fart and they go but everybody when and they go but everybody who not really affailed of the verybody who not really affailed of the verybody who are not well affailed in the working at that moment, if it is sill working the same as in the air and people are the airstreams. In most area to the airstreams. In mo taure about that. The same is on the grounds walking the same is on the grounds walking the control of the properties are the airstreams. Note long to the same than the properties are the airstreams. Note long the same so not be ground to walking the same is on the grounds walking the same is on the grounds walking the airstreams. Note long the same than t	I don't know how infectious he vinus is in the totel and how much do you think the whole activity of using a tollet is saying in terms of feeling of safety. Neutral.
5	4	3	0	*			
sat. It's very safe better. As a passenger you paready seated, faces same level. you're supposed to b passengers out outside, it	cause contact is though some people take forever, or so seems, if seasy you know, you put in ware not on the are not on the open the flow of n front of the door.	it comparing the symbols, I appreciate that everybody's on a plane on a daily basis, so there's a confusion, so is A a window	facing forward. You know, the air conditioning that's blowing and the air that comes out of the little vents, sitting in your seat is very safe. I have to talk a little louder or they have to	level and contact is very brief. You keep a safe distance. You ask whatever it is that people want. And you walk away, you go get their stuff, you collect the money and well even if we	N/A	incredibly used to getting up all at once. Even though we make announcements to sort of keep a safe distance between each other, everybody gets up at the same time, faces are on the same level sort of and everybody is squished together in a tight space so that would be somewhat unsafe. Because even though contact is short you know it's within the 15 in	And so you know, I close the curtain. I keep them outside the pantry and then the restrooms are behind the last row but before the pantry so that's fine. So that's because we eat our meals in front of course at some point or we have something to drink and then when
2	3		4	3		psychological thing I guess.	
	1,5,4,5,4,5 3 MED you pass quite a few you pass you don't he because passen each other. They come of they can keep he had because you don't he because passen you don't he late you have to go the passengers and five a good passenger you have to be a few you have to be a few you have to go you passenger you go you you you you you you you you you yo	4.2.2.3.1,5.4,5.2.2 3.3 3.5 3.6 MED LOW you pass quite a few people That's the beginning of the flight, and people are still kind of wandering around the cabin. 5.5 There were 2 hallways on my plane and they were also boarding from the last walking through like an empty plane and they were also boarding from the last walking through like an empty plane plane because you don't have people that were sitting. 4.4 Well because passengers have to passengers have to passengers at a time. So they're week offers space and only use people had were sitting, and they had been been as the sound of the space of	4. 2.2.3.1.5.4.5.2.2 2.1.5.3.1.5.3.4.3.3 3.3 3.3 3.3 3.3 3.3 3.3	1,5,4,5,4,5 4,2,2,3,1,5,4,5,2,2 2,1,5,3,1,5,3,3,3 3,3 3,4 MED LOW MED ME	15.45,54.5 2.2,15.45,52.2 2.15,3.15,3.43.3 3.3 3.4	15.45.45.6 4.22.2 15.35.45.35 21.44.25.45.45.4 22.44.25.45.45.4 3 3.42.45.25.25 15.5 2.42.35 3.45.25 3	18.46.4.2.3 1.2.2.4.3.2.2.2.2.3 1.5.3.4.3.2.3 2.1.3.1.5.4.3.2.3 2.1.3.1.5.4.3.2.3 2.1.3.1.5.4.3.2.3 2.1.3.1.5.4.3.3.3 2.1.3.2.4.3.2.2.2.2.3 1.5.2.2.3 2.1.3.1.5.4.3.3 2.1.3.1.5.4.3.3 2.1.3.1.3.2.4.3.2.2.2.2.3 2.1.3.1.5.3.4.3.3 2.1.3.2.4.3.2.2.2.3 2.1.3.1.3.2.4.3.2.2.2.2.3 2.1.3.1.3.2.4.3.2.2.2.2.3 2.1.3.1.3.2.4.3.2.2.2.2.3 2.1.3.1.3.2.4.3.2.2.2.2.3 2.1.3.1.3.2.4.3.2.2.2.2.3 2.1.3.2.3.2.3.2.3.2.3 2.1.3.2.2.3.2.3.2.3.2.3.2.3.2.3.2.3.2.3.

Processing interviews - 9 cabin moments


Activity	Entering the plane	Walking through the alley Looking for a seat	Storing luggage in the overhead compartment	Taking your seat	Sitting in the seat	Flight Attendants service	Eating	After landing - disembarking	using toilet
Indicative image									
high concern	2	2,2,3	3,3	2,2,2	1,2,2	1,1	1,1,1,2	1,1,1,3,3,2	1,2
all grades	5,3,5,4,4,5,4,5,4,5	4,2,2,3,1,5,4,5,2,2	2,1,5,3,1,5,3,4,3,3	2,1,4,4,2,5,4,3,4,4	2,2,2,4,2,5,3,5,4,5	3,1,3,2,4,5,2,5,2,5	1,1,2,2,2	1,3,1,3,1,5,4,3,	1,2,3,3
average grade	4.4	3	3	3.3	3.4	3.4	1,5	2.7	
overall priority	LOW	MED	LOW	MED	MED	MAX	MAX	MAX	MED
description		I think it is better to all in the plane than to walk around. It think when making around you are the whole when the propose and I think that is less safe.			So if you just at down and breather that is in an infinite highlighthood, then I think that's pretty sale.	down and think walking is unsafe. I'm safer buf if an airfung down than it a desert buf if an airfung down than it a desert buf if an airfung down the construction of	N/A	I notice people to remain sealed until the row in front of you have been cleared. And fin pethy stot, so I will use the St. to Min see the St. to	
JFA grade	5	2	3	4	5	5	2	4	
description	Well if people come on board wearing a mouth mask, it's very safe as long as everyone is well and is actually wearing a mask. You can't adhere to the 15. metre distance, so I would say in the first image I would say very safe. Because there's I would say very safe. Because there's the passengers doesn't take long.	The second image I would say is somewhat unsafe. People really stay too close to one another.	It really depends on how many passengers are around the person. So I would say neutral. We do advise passengers to take as little hand luggage as possible but in my they want anyway, so they don't really listen to that advice.	Taking a seat, actually this is the same argument, I would go for "somewhat safe" as long as the people are not breathing on their neck.		I think it's our human nature but sometimes when you ask for someone's order they will take up the face mask to speak more clearly and so you have to remind people to keep on the mouth masks. As long as the people are not too masks, as long as the people are not too problem, but it does make it a little less safe of course. We've adapted our service for the shortest time possible.	situation or abuse situation, maybe better said, and they would have a coffee or a coke or a beer or whatever and instead of finishing it in intended 15 minutes, they will finish it in an hour. Just not to wear a facemask.	could be somewhat unsafe or neutral.	You can never know of course, but you just hope that people when they use the lavatory, they also wash their hands. But you don't have any insight on that of course. You never know if they properly any attention to hygiene. I see people going into the lavatory with bare feet so I don't think it always happens that way. It happens a lot.


Processing interviews - Quirkos analysis report

Interview analysis report generated with Quirkos software

https://drive.google.com/file/d/1uk_wOrV0j1ll5Hjsy_OB6oGWFZjmRfWr/view?usp=sharing







PROCEDURE:



Concepts

Multiple per challenge



Discussion

Pros and cons, feasibility



Voting

Selecting the best + most feasible



1. Uncertainty about measures

Masks uncertainty

Code: 1



CONCEPTS

- A) Free certified safety mask when entering the plane 1
- B) Leaflets/stickers explaining how masks work 1
- C) Describe the benefits of wearing a mask during the in-flight safety briefing/on screens 4 11
- D) Compulsory medical masks bought before flight
- E) Free WiFi + phone notifications informing about all safety features

Cabin air uncertainty

Code: 1.2



- A) Leaflets when entering, showing the details on how cabin air works 4 1
- B) Ads on the airport, explaining how safe the cabin air is **1**
- C) Free WiFi + phone notifications informing about all safety features
- D) Safety measures described online, sent together with the boarding pass 3 1

Cleaning uncertainty

Code: 1.3



CONCEPTS:

- A) Little cards indicating the seat was cleaned **2**
- B) Free WiFi + phone notifications informing about all safety features
- C) A real-time video of interior cleaning shown at the airport **2 11**
- D) A sign at the entrance: "Interior disinfected" with signatures of cleaners 2 1



2. Need for increased measures

Seat redesign/enhancers

Code: 2.



CONCEPTS:

- A) Antimicrobial materials/coatings 4 1
- B) Foldable screen divider 21
- C) Additional cover that is replaced after flight 2
- D) Redesigned armrests for less contact 1 11
- E) Cleaner seat design with no gaps, seams etc. 1
- F) Integrated UV light cleaning 1
- G) Air outlet between passenger heads
- H) Reversed central seat in the row

Too much physical contact

Code: 2.2



- A) Stricter, organized (de)boarding 1
- B) Checked-in luggage only
- C) Using light to indicate which rows can disembark **4 11**
- D) Penalty for disobeying rules
- E) No lines to the lavatory allowed

Personal safety equipment

Code: 2.3



CONCEPTS:

- A) Face shields for free when entering **3**
- B) Gloves for free



Uncertainty over passengers' health

Code: 3.:



CONCEPTS

- A) Required making a PCR test before entering the plane 1 11
- B) Free WiFi+App that describes the unlikelihood of catching a virus on board
- C) Temperature screening 4 11

Worrying about infecting others

Code: 3.2



- A) Additional protection on top of the mask. (shield?) **11**
- B) Foldable barriers between seats 11
- C) 31

Hearing coughing/sneezing



CONCEPTS:

- A) Free extra protection masks that mute
- B) Personal helmets which protect, mute and provide entertainment 11
- C) Tissue given away 3 1



Not wearing masks (properly)

Code: 4.1



- A) A right to offload a passenger who is not obeying the rules, can be banned from the next flights (open system of tracking) 1 1
- B) A face recognition camera in the seat that detects masks off 1
- C) (after pandemic) Section of the plane for people who want to wear mask
- D) An app where you can report disobedience anonymously to the cabin crew 1 11
- E) Seatbelts+masks on 111 1

Different rules in different countries



- A) Standardised flight rules 11
- B) Section of the plane for people who don't want to wear a mask
- C) App informing about the current safety measures 111 11

Unsafe when eating without masks

Code: 4.



CONCEPTS:

- A) No food allowed on the plane 11
- B) Staggered food ordering 111
- C) Removable barriers during eating 1 1
- D) Liquid food 211
- E) Food when entering 1

People rushing to the exit

Code: 4.4



CONCEPTS:

- A) An app telling when passengers can leave
- B) Using light to indicate which rows can disembark **4 111**
- C) Flight attendants walking outside-in through the alley to let people disembark
- D) App detecting movement, ringing if you leave too soon 1



5. More control by flight attendants

Stewards should be more assertive

Code: 5.:



- A) A right to offload any passenger for not adhering to viral safety measures (com) 1
- B) Fines for disobedient passengers (com) 3
- C) Warning on fines through the radio 111111

Stewards should control wearing masks

Code: 5.



CONCEPTS:

- A) A right to offload any passenger for not wearing a mask (com) 1
- B) Fines for no mask (com) 3 1
- C) Face detection camera in the seat
- D) App where you can anonymously report not wearing a mask **1**
- E) Warning on fines through the radio
- F) 1



6. New future attitudes

Lower willingness to fly in the future

Code: 6.1



CONCEPTS

- A) More eco-friendly aircrafts/technology 1111
- B) Find new niches of travellers 2 1
- C) Improving entertainment/comfort 111111
- D) More space, more expensive flights 111
- E) Easy booking, rebooking, cancellation, refunds **3**
- F) Diversification of business 1111

Sustainability concerns

Code: 6.



- A) Indicating footprint of each flight 1111
- B) Include CO2 offset in each ticket 1
- C) More efficient aircrafts 111
- D) Communicating more the ongoing development of sustainable aviation **111**

Co-creation session voting sheet

VOTING SHEET

name: _____

MOST FEASIBLE:

	1			2			3			4	1		Ę	5	6	5
1.1	1.2	1.3	2.1	2.2	2.3	3.1	3.2	3.3	4.1	4.2	4.3	4.4	5.1	5.2	6.1	6.2

BEST IN CATEGORY:

	1			2			3			4	4		Ę	5	6	5
1.1	1.2	1.3	2.1	2.2	2.3	3.1	3.2	3.3	4.1	4.2	4.3	4.4	5.1	5.2	6.1	6.2

No	Name	Creator	Description	Website	Photos	
1	PlanBay	Avioninteriors	Physical, transparent divider between the passengers. Uses the middle seat	https://edition.cn/		
2	Antiviral surface	Eboco	Antimicrobal and antiviral armrest and tray surfaces	http://journal-dow		
3	HeadZone	Factorydesign	Safety solution, which wraps around the head to give support, personal separation and a sense of reassurance.	https://www.aircr		HOUZON
4	Isolate screen kit	Factorydesign	An opportunity to transform a vacant seat into a screen that maximises personal space and helps separate passengers from each other or the aisle.	https://www.aircr	DE	
5	S2 Stagger seat	Molon Labe Design	Seat system that can vent fresh cabin air from the headrest directly towards the passenger's face, with controllable flow rates and direction similar to overhead cabin vents.	https://www.aircr		
6	Soft divider	Jamco	Airflow down the cabin could be disrupted by fitting Jamco's Soft Divider, a leather-wrapped eyebrow-type hanging class divider for single-aisle aircraft.	https://www.aircr	Dimco	

7	Lightweight seat divider	Lufthansa Technik	Seat dividers which are installed around the headrest of the middle seat in order to separate passengers. LHT says that airflow tests have shown that the shields prevent the spread of aerosols, without reducing the beneficial ventilation effects of the cabin air conditioning.	
8	Dual Disposable Seat Cover	AviationRFI	Intended to help reduce germ transfer from seats to clothing during travel. The one-piece cover is double-ended, with one end suitable for fitting to an aircraft seat, and the other a car seat (useful for taxis, etc).	https://www.aircra
9	Aircraft passenger protection	Science Lab	Physical, sealed barrier between passengers. The design is a full cocoon that fits over an aircraft seat and its occupant, keeping them completely isolated in the cabin.	https://www.aircr
10	Protection screens	Aviation Glass	Large glass screens that can be fitted onto existing aircraft seats to give a greater feeling of protection.	https://www.aircra
11	Removable Divider System	Aerofoam	Removable seat-blocking device that can be easily installed on any seating platform using the existing passenger restraint system, without restricting the function of the seat.	https://www.aircra
12	Protective screens	Autostop Aviation	Passenger protective screens to help reassure passengers in economy class.	https://edition.cn

13	Adjustable headrest	Reinhold Industries	Adjustable headrest that can be fitted to any economy seat platform, with both privacy and passenger safety in mind.	https://edition.cn/ Pag and Pag had been on be labored to it in your beind and process hashed constant turns from the control of the page. The page of Pag and Pag had been on the labored to its any out turns from the page. The page of Pag and Pag had been on the labored to its any out turns from the page of the pag
14	Glassafe	Aviointeriors	A kit-level solution that could be installed on existing seats to help separate passengers sitting in double or triple seats.	https://edition.cnr
15	Priva	Golnoosh Torkashva	An adjustable interactive shade which opens and closes over the occupant's head on demand. The wearer can choose adjustable visibility, dimmable lighting and IFE options, as well as a messaging system with flight attendants.	https://edition.cn/
16	Passenger protection system	Vision systems	A light, compact and transparent barrier that separates passengers and also features an anti-germ treatment – without requiring an empty seat between passengers.	https://edition.cn
17	The Travel Safe range	Safran	The social distancing aspect of Travel Safe involves equipment such as Ringfence, a simple removable partition that isolates neighbouring passengers. Other designs include touchless interaction equipment for suite door actuation, and pedal actuators for backrest recline functions. The virus-free solutions incorporate a range of coatings for seats and tray tables which facilitate disinfection and cleaning.	https://edition.cn
18	Interspace Lite	Safran	An easily retrofittable table and shield fits over the centre seat, providing delineation and privacy between passengers by locking out either the central or outboard seats of a row.	https://edition.cnr

19	AirShield	Teague	A single 3D-printed component that fits directly onto the passenger service unit (PSU) positioned above every passenger in the cabin. Airflow from the existing overhead air-gaspers is channelled through the AirShield, transforming freshly purified air into engineered 'air-blades' capable of controlling the spread of droplets much more effectively.	https://edition.cn
20	Janus	Avioninteriors	A new design which sees the centre seat in a row of three reversed "to ensure the maximum isolation between passengers seated next to each other". An additional clear plastic screen provides further protection.	https://www.flight
21	Pure Skies	PriestmanGoode	Dividers would be erected between each seat to provide an additional modicum of protection and privacy for adjacent flyers.	https://www.busir
22	Premium Economy Seats	PierreJean	Instead of individual seats, we could see a bench-like set up in a lacquer material that has few gaps and recesses, making it easier to clean as it has fewer difficult-to-access crevices. Each passenger would have a bubble around their head that would separate them from their neighbour.	https://www.aircra

Rapid prototyping



Appendix I Appendix I Appendix I

Rapid prototyping



Harris Profile

Criterion	Qualites assessed	2 minus	minus	plus	2 plus
Perceived safety	Area of the divider, body parts covered, physical contact	Covering a small area, obstructing the vertical airflow, not decreasing physical contact	Covering a small area, not obstructing the vertical airflow, not decreasing physical contact	Covering a medium area, not obstructing the vertical airflow, not decreasing physical contact	Covering a large area, not obstructing the vertical airflow, decreasing physical contact
Viral safety	Airflow obstruction, area covered, seclusion	Obstructing vertical airflow, covering a small area, open-ended shape	Not obstructing vertical airflow, covering a small area, open-ended shape	Not obstructing vertical airflow, covering a medium area, closed shape	Not obstructing vertical airflow, covering a large area, closed shape
Interior safety	Ease of dismantling, regressing time, size when not used, attachment type	Attached to body, takes more than 5 s to remove, takes much space when not used, limits cabin crew communication	Attached to body, takes less than 5 s to remove, takes moderate space when not used, limits cabin crew communication	Attached to the seat, takes less than 5 s to remove, takes small space when not in use, limits cabin crew communication	Attached to the seat, takes less than 5 s to remove, takes small space when not in use, not limiting cabin crew communication
Sustainability	Weight (fuel use), production impact, reusability, retro-fittability, universality - can be applied to many interiors	High weight, Single use, High production impact, not retro-fittable, not universal	High weight, Reusable, High production impact, retro-fittable, universal	Medium weight, reusable, medium production impact, retro-fittable, universal	Low weight, Reusable, Low production impact, retro-fittable, universal
Convenience	Ease of use, comfort, communication with others, actions required, acceptance	Hampering commmunication, requires many user actions, novel, reducing comfort	Hampering commmunication, requires few user actions, familiar, not reducing comfort	Not hampering commmunication, requires few user actions, familiar, not reducing comfort	Not hampering commmunication, requires no/few user actions, familia improving comfort
Maintenance	Actors involved, time needed, complexity, cleaning products required	Staff cleaning, complex to clean, timely	Staff cleaning, easy to clean, quick cleaning	Passenger cleaning, easy to clean, quick	Self cleaning/not required
Cost	Production cost, affordability, materials used, weight	Very high cost	High cost	Low cost	Very low cost

Harris Profile

	COPPORT & PANELLY PILLOW		G C			ÇQ.	Jacob San	Q=>Q	Production of the State of the
Weight	Concept #1	Concept #2	Concept #3	Concept #4	Concept #5	Concept #6	Concept #7	Concept #8	Concept #9
2	1	3	2	3	2	2	2	2	1
2	1	2	2	3	2	1	2	2	1
1.8	1	1	2	2	2	1	0	1	3
1.6	2	1	1	2	2	2	2	3	1
1.4	3	0	2	3	1	0	0	0	3
1.2	2	0	1	1	0	2	1	2	1
1	1	1	1	1	1	2	1	2	0
scores	Concept #1	Concept #2	Concept #3	Concept #4	Concept #5	Concept #6	Concept #7	Concept #8	Concept #9
Perceived safety	2	6	4	6	4	4	4	4	2
Viral safety	2	4	4	6	4	2	4	4	2
Interior safety	1.8	1.8	3.6		3.6	1.8	0	1.8	5.4
Sustainability		1.6	1.6		3.2	3.2	3.2	4.8	1.6
Convenience	4.2	0	2.8		1.4	0	0	0	4.2
Maintenance	2.4	0	1.2	1.2	0	2.4	1.2	2.4	1.2
Cost	1	1	1	1	1	2	1	2	0
	16.6	14.4	18.2	25.2	17.2	15.4	13.4	19	16.4
Selected concepts									

User test plan

User test plan



The main objective of this study is to test prototypes with users while ensuring no physical contact due to the COVID-19 restrictions. Participants will assess different prototypes in scope of the experience they provide, based on the visual input from VR goggles. All tests will be done individually by participants in their homes.

Test procedure:

The test is divided into two parts. In the first part, participants will be asked to watch videos with different prototypes, pre-recorded using an omnidirectional (360-degree) camera. This type of videos allows for an immersive experience similar to VR (Virtual Reality), and can be viewed using a commonly used YouTube application on a smartphone. In order to facilitate the test, a pair of cardboard Virtual Reality goggles will be send via postal service. Each provided pair of goggles will be new and sealed, and will remain in the possession of the participant after the test to ensure hygiene.

Preview of such goggles:

https://www.youtube.com/watch?v=hggLGKAHcno&ab_channel=TingaWinga5

Participants will use the goggles to watch a set of videos provided with an URL link. This will allow them to have an experience similar to the one with real prototypes, but in a safe home environment. The videos will be watched in a sitting position to ensure safety, and will simulate the use of prototypes from a first-point perspective.

In the second part, participants will be asked to complete a survey using Qualtrics software (Qualtrics International Inc.), with Likert-scale questions and optional open-ended answers. In this survey, users will be asked to first rate the experience in a regular aircraft seat, and later compare it with the experience when using the prototypes.

Survey questions:

Questions about prototypes 1-4

- Compared to the regular seat, how safe from viruses would this concept make you feel during eating? (1-5 Likert Scale)
- 2. Please explain your choice. (open-ended question)

- 3. Did this solution make you feel claustrophobic compared to the regular setting? Please indicate how much. (1-5 Likert Scale)
- Do you consider this concept comfortable to use? (ease of use, intuitiveness, physical comfort) Please indicate how much. (1-5 Likert Scale)
- Would you be willing to pay more for the flight equipped with such a solution? Please indicate
 what would be your maximum amount of a ticket price: (pay less/not pay extra/10%
 more/20% more/30% and more) (1-5 Likert Scale)
- 6. Would this solution make you more willing to fly during pandemic? (1-5 Likert Scale)
- Would this solution make you more willing to fly after the pandemic is over? (1-5 Likert Scale)
- 8. Do you find this concept useful? Would you like to have it on your flight? Please explain.

(open-ended question)

Questions regarding the test itself

- A. Did the provided materials (videos, instructions, goggles) give you enough data to assess concepts? (1-5 Likert Scale)
- B. (optional) Please explain your choice.
- C. Was the test easy to understand and complete? (1-5 Likert Scale)
- D. (optional) Please explain your choice.

Possible limitations of the study


- Insufficient sensory input; lack of physical interaction with objects
- No ability of manipulating objects and test their usability
- Distorted visual input and distance perception due to the technology used (VR goggles)
- · Limited freedom of movement and interaction
- Lack of direct supervision by the researcher may lead to undesired execution by participants


Presentation for a product designer


CONFIDENTIAL


Passneger divider

An aircraft interior element that separates passsengers to increase virus safety. It consists of a textile screen mounted on a frame fixed to the seat.











Presentation for a product designer






Points for discussion

- What materials are best to produce these elements at lowest weight and durability?
 What production techniques are most feasible for achieving the desired shapes?
 How can the design be optimized for ensuring low weight and producibility?

Materials and processes inventory

Qty.	Component name	Material	Recycled content	Mass (kg)	Primary process	Length (m)	Secondary process	% removed	End of life
1	frame	Aluminum, 2024, T3 ▲	Typical %	0,3	Roll forming	1,6		0	Downcycle
1	roller axle	Aluminum, 2024, T3 ▲	Typical %	0,085	Extrusion, foil rolling	0,5		0	Downcycle
1	roller tube	Aluminum, 2024, T3 ▲	Typical %	0,29	Extrusion, foil rolling	0,6		0	Downcycle
1	stretch panel	Aluminum, 2024, T3 ▲	Typical %	0,05	Roll forming	0,6		0	Downcycle
1	spring	Carbon steel, AISI 1020, a	Typical %	0,05	Wire drawing	0,5		0	Recycle
1	plastic caps	PP (random copolyme 💠	Virgin (0%)	0,03	Polymer molding	Not Required		0	Recycle
1	handle	Carbon steel, AISI 1020, a	Typical %	0,015		Not Required		0	Recycle
1	ball bearing, bolts and nuts	Carbon steel, AISI 1010, a	Virgin (0%)	0,04	Forging	Not Required		0	Re-manufacture
1	plastic cover	PET (unfilled, semi-cry 💠	Virgin (0%)	0,082		Not Required		0	Recycle
1	plastic mount	ABS (extrusion)	Virgin (0%)	0,12	Polymer molding	Not Required		0	Landfill
1	blind	TPU (Ester, aromatic, S 🔷	Virgin (0%)	0,077	Polymer extrusion	0		0	Recycle


Comparison of impacts of iterations 2 and 3




Report generated using Granta EduPack software

Second product iteration EcoAudit:







Detailed breakdown of individual life phases

Material:

Summary

Component	Material	Recycled content* (%)	Part mass (kg)	Qty.	Total mass processed** (kg)	Energy (MJ)	%
frame	Aluminum, 2024, T3	Typical %	0,3	1	0,3	38	30,6
roller axle	Aluminum, 2024, T3	Typical %	0,085	1	0,085	11	8,7
roller tube	Aluminum, 2024, T3	Typical %	0,29	1	0,29	36	29,6
stretch panel	Aluminum, 2024, T3	Typical %	0,05	1	0,05	6,3	5,1
spring	Carbon steel, AISI 1020, as rolled	Typical %	0,05	1	0,05	1,1	0,9
plastic caps	PP (random copolymer, low flow)	Virgin (0%)	0,03	1	0,03	2,1	1,7
handle	Carbon steel, AISI 1020, as rolled	Typical %	0,015	1	0,015	0,34	0,3
ball bearing, bolts and nuts	Carbon steel, AISI 1010, annealed	Virgin (0%)	0,04	1	0,04	1,3	1,0
plastic cover	PET (unfilled, semi-crystalline)	Virgin (0%)	0,082	1	0,082	6,7	5,5
plastic mount	ABS (extrusion)	Virgin (0%)	0,12	1	0,12	11	9,0
blind	TPU (Ester, aromatic, Shore A70)	Virgin (0%)	0,077	1	0,077	9,3	7,6
Total				11	1,1	1,2e+02	100

^{*}Typical: Includes 'recycle fraction in current supply'

COVR - EcoDesign.prd Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

poniedziałek, 12 kwietnia 2021

Manufacture:

Summary

Component	Process	% Removed	Amount processed	Energy (MJ)	%
frame	Roll forming	-	0,3 kg	2,2	17,6
roller axle	Extrusion, foil rolling	-	0,085 kg	1,2	9,7
roller tube	Extrusion, foil rolling	-	0,29 kg	4,1	33,2
stretch panel	Roll forming	-	0,05 kg	0,36	2,9
spring	Wire drawing	-	0,05 kg	1,1	8,6
plastic caps	Polymer molding	-	0,03 kg	0,64	5,2
ball bearing, bolts and nuts	Forging	-	0,04 kg	0,11	0,9
plastic mount	Polymer molding	-	0,12 kg	2,2	18,1
blind	Polymer extrusion	-	0,077 kg	0,47	3,8
Total				12	100

Transport:

Summary

Breakdown by transport stage

Stage name	Transport type	Distance (km)	Energy (MJ)	%
Factory to OEM	40 tonne (6 axle) truck	3e+02	0,28	100,0
Total		3e+02	0,28	100

Breakdown by components

Component	Mass (kg)	Energy (MJ)	%
frame	0,3	0,074	26,3
roller axle	0,085	0,021	7,5
roller tube	0,29	0,071	25,5
stretch panel	0,05	0,012	4,4
spring	0,05	0,012	4,4
plastic caps	0,03	0,0074	2,6
handle	0,015	0,0037	1,3
ball bearing, bolts and nuts	0,04	0,0098	3,5
plastic cover	0,082	0,02	7,2
plastic mount	0,12	0,03	10,5
blind	0,077	0,019	6,8
Total	1,1	0,28	100

COVR - EcoDesign.prd

Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

Page 3 / 13 iedziałek, 12 kwietnia

^{**}Where applicable, includes material mass removed by secondary processes

Use: Summary

Mobile mode

Fuel and mobility type	Kerosene - long haul aircraft
Country of use	Europe
Product mass (kg)	1,1
Distance (km per day)	7,4e+03
Usage (days per year)	3,7e+02
Product life (years)	7

Relative contribution of static and mobile modes

Mode	Energy (MJ)	%
Static	0	
Mobile	1,4e+05	100,0
Total	1,4e+05	100

Breakdown of mobile mode by components

Component	Energy (MJ)	%
frame	3,7e+04	26,3
roller axle	1e+04	7,5
roller tube	3,6e+04	25,5
stretch panel	6,1e+03	4,4
spring	6,1e+03	4,4
plastic caps	3,7e+03	2,6
handle	1,8e+03	1,3
ball bearing, bolts and nuts	4,9e+03	3,5
plastic cover	1e+04	7,2
plastic mount	1,5e+04	10,5
blind	9,5e+03	6,8
Total	1,4e+05	100

Disposal:

Summary

Component	End of life option	% recovered	Energy (MJ)	%
frame	Downcycle	100,0	0,15	26,2
roller axle	Downcycle	100,0	0,043	7,4
roller tube	Downcycle	100,0	0,15	25,3
stretch panel	Downcycle	100,0	0,025	4,4
spring	Recycle	100,0	0,035	6,1
plastic caps	Recycle	100,0	0,021	3,7
handle	Recycle	100,0	0,011	1,8
ball bearing, bolts and nuts	Re-manufacture	100,0	0,008	1,4
plastic cover	Recycle	100,0	0,057	10,0
plastic mount	Landfill	100,0	0,024	4,2
blind	Recycle	100,0	0,054	9,4
Total			0,57	100

EoL potential:

Component	End of life option	% recovered	Energy (MJ)	%
frame	Downcycle	100,0	-14	29,2
roller axle	Downcycle	100,0	-3,9	8,3
roller tube	Downcycle	100,0	-13	28,2
stretch panel	Downcycle	100,0	-2,3	4,9
spring	Recycle	100,0	-0,69	1,5
plastic caps	Recycle	100,0	-1,4	2,9
handle	Recycle	100,0	-0,21	0,4
ball bearing, bolts and nuts	Re-manufacture	100,0	-1,2	2,5
plastic cover	Recycle	100,0	-4,4	9,3
plastic mount	Landfill	100,0	0	0,0
blind	Recycle	100,0	-6,1	12,9
Total			-48	100

Notes: Summary

COVR - EcoDesign.prd


Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

Page 4 / 13 poniedziałek, 12 kwietnia 2021 COVR - EcoDesign.prd

Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

Page 5 / 13 iiedziałek, 12 kwietnia

2021



	CO2 (kg/year)
Equivalent annual environmental burden (averaged over 7 year product life):	1.44e+03

Detailed breakdown of individual life phases

Material:

Summary

Component	Material	Recycled content* (%)	Part mass (kg)	Qty.	Total mass processed** (kg)	CO2 footprint (kg)	%
frame	Aluminum, 2024, T3	Typical %	0,3	1	0,3	2,6	33,9
roller axle	Aluminum, 2024, T3	Typical %	0,085	1	0,085	0,73	9,6
roller tube	Aluminum, 2024, T3	Typical %	0,29	1	0,29	2,5	32,8
stretch panel	Aluminum, 2024, T3	Typical %	0,05	1	0,05	0,43	5,7
spring	Carbon steel, AISI 1020, as rolled	Typical %	0,05	1	0,05	0,083	1,1
plastic caps	PP (random copolymer, low flow)	Virgin (0%)	0,03	1	0,03	0,087	1,1
handle	Carbon steel, AISI 1020, as rolled	Typical %	0,015	1	0,015	0,025	0,3
ball bearing, bolts and nuts	Carbon steel, AISI 1010, annealed	Virgin (0%)	0,04	1	0,04	0,095	1,2
plastic cover	PET (unfilled, semi-crystalline)	Virgin (0%)	0,082	1	0,082	0,22	2,9
plastic mount	ABS (extrusion)	Virgin (0%)	0,12	1	0,12	0,41	5,4
blind	TPU (Ester, aromatic, Shore A70)	Virgin (0%)	0,077	1	0,077	0,44	5,8
Total				11	1,1	7,6	100

^{*}Typical: Includes 'recycle fraction in current supply'

COVR - EcoDesign.prd Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

Page 6 / 13 poniedziałek, 12 kwietnia 2021

Manufacture:

Summary

Component	Process	% Removed	Amount processed	CO2 footprint (kg)	%
frame	Roll forming	-	0,3 kg	0,16	17,6
roller axle	Extrusion, foil rolling	-	0,085 kg	0,09	9,7
roller tube Extrusion, foil rolling		-	0,29 kg	0,31	33,2
stretch panel	Roll forming	-	0,05 kg	0,027	2,9
spring	Wire drawing	-	0,05 kg	0,079	8,6
plastic caps	Polymer molding	-	0,03 kg	0,048	5,2
ball bearing, bolts and nuts	Forging	-	0,04 kg	0,0081	0,9
plastic mount	Polymer molding	-	0,12 kg	0,17	18,1
blind	Polymer extrusion	-	0,077 kg	0,035	3,8
Total				0,92	100

Transport:

Summary

Breakdown by transport stage

Stage name	Transport type	nnsport type Distance (km)		%
Factory to OEM	40 tonne (6 axle) truck	3e+02	0,02	100,0
Total		3e+02	0,02	100

Breakdown by components

Component	Mass (kg)	CO2 footprint (kg)	%
frame	0,3	0,0053	26,3
roller axle	0,085	0,0015	7,5
roller tube	0,29	0,0051	25,5
stretch panel	0,05	0,00089	4,4
spring	0,05	0,00089	4,4
plastic caps	0,03	0,00053	2,6
handle	0,015	0,00027	1,3
ball bearing, bolts and nuts	0,04	0,00071	3,5
plastic cover	0,082	0,0015	7,2
plastic mount	0,12	0,0021	10,5
blind	0,077	0,0014	6,8
Total	1,1	0,02	100

COVR - EcoDesign.prd

Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

Page 7 / 13 edziałek, 12 kwietnia

^{**}Where applicable, includes material mass removed by secondary processes

Use: Summary

Mobile mode

Fuel and mobility type	Kerosene - long haul aircraft
Country of use	Europe
Product mass (kg)	1,1
Distance (km per day)	7,4e+03
Usage (days per year)	3,7e+02
Product life (years)	7

Relative contribution of static and mobile modes

Mode	CO2 footprint (kg)	%
Static	0	
Mobile	1e+04	100,0
Total	1e+04	100

Breakdown of mobile mode by components

Component	CO2 footprint (kg)	%
frame	2,7e+03	26,3
roller axle	7,5e+02	7,5
roller tube	2,6e+03	25,5
stretch panel	4,4e+02	4,4
spring	4,4e+02	4,4
plastic caps	2,7e+02	2,6
handle	1,3e+02	1,3
ball bearing, bolts and nuts	3,5e+02	3,5
plastic cover	7,3e+02	7,2
plastic mount	1,1e+03	10,5
blind	6,8e+02	6,8
Total	1e+04	100

Disposal:

Summary

Component	End of life option	% recovered	CO2 footprint (kg)	%
frame	Downcycle	100,0	0,011	26,2
roller axle	Downcycle	100,0	0,003	7,4
roller tube	Downcycle	100,0	0,01	25,3
stretch panel	Downcycle	100,0	0,0018	4,4
spring	Recycle	100,0	0,0025	6,1
plastic caps	Recycle	100,0	0,0015	3,7
handle	Recycle	100,0	0,00074	1,8
ball bearing, bolts and nuts	Re-manufacture	100,0	0,00056	1,4
plastic cover	Recycle	100,0	0,004	10,0
plastic mount	Landfill	100,0	0,0017	4,2
blind	Recycle	100,0	0,0038	9,4
Total			0,04	100

EoL potential:


Component	End of life option	% recovered	CO2 footprint (kg)	%
frame	Downcycle	100,0	-0,9	32,4
roller axle	Downcycle	100,0	-0,25	9,2
roller tube	Downcycle	100,0	-0,87	31,4
stretch panel	Downcycle	100,0	-0,15	5,4
spring	Recycle	100,0	-0,049	1,8
plastic caps	Recycle	100,0	-0,058	2,1
handle	Recycle	100,0	-0,015	0,5
ball bearing, bolts and nuts	Re-manufacture	100,0	-0,086	3,1
plastic cover	Recycle	100,0	-0,098	3,6
plastic mount	Landfill	100,0	0	0,0
blind	Recycle	100,0	-0,29	10,5
Total			-2,8	100

Summary Notes:

COVR - EcoDesign.prd

Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

COVR - EcoDesign.prd Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.



Detailed breakdown of individual life phases

Material:

Component	Material		Part mass (kg)	Qty.	Total mass processed** (kg)	Cost (EUR)	%
frame	Aluminum, 2024, T3	Typical %	0,3	1	0,3	0,72	29,1
roller axle	Aluminum, 2024, T3	Typical %	0,085	1	0,085	0,21	8,4
roller tube	Aluminum, 2024, T3	Typical %	0,29	1	0,29	0,7	28,5
stretch panel	Aluminum, 2024, T3	Typical %	0,05	1	0,05	0,12	4,8
spring	Carbon steel, AISI 1020, as rolled	Typical %	0,05	1	0,05	0,04	1,6
plastic caps	PP (random copolymer, low flow)	Virgin (0%)	0,03	1	0,03	0,039	1,6
handle	Carbon steel, AISI 1020, as rolled	Typical %	0,015	1	0,015	0,011	0,5
ball bearing, bolts and nuts	Carbon steel, AISI 1010, annealed	Virgin (0%)	0,04	1	0,04	0,042	1,7
plastic cover	PET (unfilled, semi-crystalline)	Virgin (0%)	0,082	1	0,082	0,087	3,5
plastic mount	ABS (extrusion)	Virgin (0%)	0,12	1	0,12	0,25	10,0
blind	TPU (Ester, aromatic, Shore A70)	Virgin (0%)	0,077	1	0,077	0,25	10,3
Total				11	1,1	2,5	100

^{*}Typical: Includes 'recycle fraction in current supply'

COVR - EcoDesign.prd Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

poniedziałek, 12 kwietnia 2021

Manufacture:

Summary

Country of manufacture

Europe

Component	Process	Length (m)	% Removed	Amount processed		Cost (EUR)	%
frame	Roll forming	1,6	-	0,3	kg	0,0035	0,1
roller axle	Extrusion, foil rolling	0,5	-	0,085	kg	0,013	0,5
roller tube	Extrusion, foil rolling	0,6	-	0,29 kg		0,033	1,3
stretch panel	Roll forming	0,6	-	0,05 kg		0,00039	0,0
spring	Wire drawing	0,5	-	0,05	kg	0,00097	0,0
plastic caps	Polymer molding	-	-	0,03	kg	0,22	8,7
ball bearing, bolts and nuts	Forging	-	-	0,04	kg	1,9	75,9
plastic mount	Polymer molding	-	-	0,12 kg		0,34	13,4
blind	Polymer extrusion	-	-	0,077 kg		0	0,0
Total						2,6	100

Transport:

Summary

Package dimensions

Height (m)	Width (m)	Depth (m)
1	0,1	0,1

Breakdown by transport stage

Stage name	Transport type	Distance (km)	Cost (EUR)	%
Factory to OEM	40 tonne (6 axle) truck	3e+02	0,15	100,0
Total		3e+02	0,15	100

Breakdown by components

breakdown by components							
Component	Mass (kg)	Cost (EUR)	%				
frame	0,3	0,041	26,3				
roller axle	0,085	0,012	7,5				
roller tube	0,29	0,039	25,5				
stretch panel	0,05	0,0068	4,4				
spring	0,05	0,0068	4,4				
plastic caps	0,03	0,0041	2,6				
handle	0,015	0,002	1,3				
ball bearing, bolts and nuts	0,04	0,0054	3,5				
plastic cover	0,082	0,011	7,2				
plastic mount	0,12	0,016	10,5				
blind	0,077	0,01	6,8				
Total	1,1	0,15	100				

COVR - EcoDesign.prd

Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

poniedziałek, 12 kwietnia 2021

^{**}Where applicable, includes material mass removed by secondary processes

Use: Summary

Mobile mode

Fuel and mobility type	Kerosene - long haul aircraft
Country of use	Europe
Fuel rate	Commercial
Product mass (kg)	1,1
Distance (km per day)	7,4e+03
Usage (days per year)	3,7e+02
Product life (years)	7

Relative contribution of static and mobile modes

Mode	Cost (EUR)	%
Static	0	
Mobile	1,8e+03	100,0
Total	1,8e+03	100

Breakdown of mobile mode by components

Component	Cost (EUR)	%
frame	4,7e+02	26,3
roller axle	1,3e+02	7,5
roller tube	4,5e+02	25,5
stretch panel	78	4,4
spring	78	4,4
plastic caps	47	2,6
handle	23	1,3
ball bearing, bolts and nuts	62	3,5
plastic cover	1,3e+02	7,2
plastic mount	1,9e+02	10,5
blind	1,2e+02	6,8
Total	1,8e+03	100

Disposal:

Summary

Component	End of life option	% recovered	Cost (EUR)	%	
frame	Downcycle	100,0	0,0017	26,3	
roller axle	Downcycle	100,0	0,00049	7,5	
roller tube	Downcycle	100,0	0,0017	25,5	
stretch panel	Downcycle	100,0	0,00029	4,4	
spring	Recycle	100,0	0,00029	4,4	
plastic caps	Recycle	100,0	0,00017	2,6	
handle	Recycle	100,0	8,6e-05	1,3	
ball bearing, bolts and nuts	Re-manufacture	100,0	0,00023	3,5	
plastic cover	Recycle	100,0	0,00047	7,2	
plastic mount	Landfill	100,0	0,00069	10,5	
blind	Recycle	100,0	0,00044	6,8	
Total			0,0065	100	

Notes: Summary

COVR - EcoDesign.prd Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

poniedziałek, 12 l

poniedziałek, 12 kwietnia 2021 COVR - EcoDesign.prd

Report generated by GRANTA EduPack 2020 (C) Granta Design Ltd.

13

poniedziałek, 12 kwietnia 2021

EcoDesign strategies for product optimization

Next sawlysis Now doos the product spare actually fulfill coal need? What are the product spare and coally fulfill coal need? One the product spare and coally fulfill coal need? One the product spare and coally fulfill coal need of the product spare and coal fulfill coal fulfill coal fulfill to the product spare and coal fulfill coal fulfill to the product spare and coal ful								
Next sandysis Now does the product spriam actually full is located under former product maintain and supply of malerials and components. One the product spriam actually full is located under former product maintain and supply of malerials and components. One the product further product maintain and supply of malerials and components. One the product further product maintain and supply of malerials and components. One the product further product maintain and product further product members are product further product members are product further product members are product. One we enrichate the supplement of the product in product of the product in product for the product members are product for the product members are product in product product of the product in product product in product product of the product in product in product product in product product in product product in product								
What are the product fine in and auditing functions yet officiently? Can be product function to the security of the fine function with residuely and efficiently? Can be product function to be expanded of improved to life seen' model and product function and supply of materials and management and product function and supply of materials and function with the product function and supply of materials and function with the product function and supply of materials and function with the product function and supply of materials and function with the product function and supply of materials and function with the product function and supply of materials and function with the product function and supply of materials and components. What products his production and supply of materials and function with the production and supply of materials and components. What products are supply of materials and function with the production and supply of materials and components. What products are supply of materials and function with the production and supply of materials and components. What products are supply of materials and components are used? How much, and what hypes of plates are used? How much, and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much and what hypes of plates are used? How much are developed plates are the plate of the components? How much are developed plates are the plate of the components? How much are developed plates are the plate of the components are the plate of the plates are the plates are the plates are the plates a	Life cycle stage	Questions	Ecodesign strategy	strategy no.	Criteria	Description	Optimzation	Future improvements
Use to please sides in the production and supply of materials and components and supply of mater	Needs analysis	What are the product's main and auxiliary functions? Does the product fulfil these functions effectively and efficiently? What user needs does the product currently meet? Can the product functions be expanded or improved to fulfil users' needs better? Will this need change over a period of time?	New concept development	0	Shared use of the product Integration of functions Functional optimisation of product	travelling. Main function is to enhance perceived safety, additionally protects from viruses, which may be important during periods of increased infection risk, and provides privacy, which is a desired feature in public transport It provides these functions effectively, as shown in user testing, and efficiently - uses minimum space in the aircraft It currently meets the users' needs to feel safe, be protected from viruses and have privacy The product can be expanded to create a flexible interior arrangements, or cover a larger area of the body, It may be installed in different places in the cabin. The need of virus protection may change over	function was added, which indicates the seat	this product may become less relevant in the future, focus might be put on emphasizing the privacy features this product gives. Additional focus may be put on making the product adaptable to different contexts, e.g switching between different modes of transport. Furthermore, this product may be optimized to serve as a multifunctional space divider in the vehicle interiors, providing secluded spaces
and supply of materials and components? How much, and what types of plastic and rubber are used? How much, and what types of materials used? How much, and what type of surface treatments is used? How much, and what type of surface treatments is used? How much, and what type of surface treatments is used? How much, and what type of materials used? How much, and what types of materials used. How much and reproduct use an early way may injection unding processes which increase the energy use in the product none type of materials used. How much and the product is a product used. How much and type of materials used. How much and type of materials used. How much and type of materials used					Score (0-4)	3	4	5
Reduction of materials usage - Reduction in (transport) volume - Reduction in (transport) to mean components adding to weight are the frame, roller tube, and a plastic cover. As a plastic casing is integrated, reatively little packaging can be achieved. The frame has an irregular shape, which increases the transportation volume. - Reduction in weight - Reduction in weight of the product is about 2 kg. The main components adding to weight are the frame, roller tube, and a plastic cover. As a plastic casing is integrated, reatively little packaging can be achieved. The frame has an irregular shape, which increases the transportation volume. - Reduction in weight - Reduction in (transport) to weight are the frame, roller tube, and a plastic cover. As a plastic casing is integrated, reatively little packaging can be achieved. The frame has an irregular shape, which increases the transportation volume.	Life cycle stage 1: Production and supply of materials and components	components? How much, and what types of plastic and rubber are used? How much, and what types of additives are used? How much, and what types of metals are used? How much, and what other types of materials (glass, ceramics, etc.) are used? How much, and wich type of surface treatment is used? What is the environmental profile of the components? How much energy is required to transport the components and		1	Renewable materials Low energy content materials Recycled materials Recyclable materials	challenging to develop a fully clean, recyclable product. The complexity of the process needed to recycle aviation-grade aluminum make it difficult to become a viable option. Furthermore, some types of plastic that suit the needs of this product out due as relatively many injection molding processes which increase the energy use in the production phase. This product uses materials that are on EU and US Critical Elements List, specifically aluminum alloy 2024 and neodymium magnets. The product uses materials that see no EU and US Critical Elements List, specifically aluminum alloy 2024 and neodymium magnets. The product uses mainly metals (alu, steel, neodymium) and plastics (PP, PET, TPU, ABS). Aluminum is generally recyclable, however aircraft grade alloys are challenging to recycle due to the complexity of the process and material degradation. As the alloys utilized in the aerospace industry must meet high standards regarding the material composition with low tolerances on impurity (Totalmateria, 2009), the end-life of the product may require downgrading the aluminum and repurposing by industries in which higher tolerances are accepted.	neodymium magnets; replacing the with hooks Using recycled plastic in the production process	the way of making this product more sustainable in the future. One way to optimize it is to use more green materials, such as: - New type of cobalt-based permanent magnet that does not require dangerous chemicals and rare materials (https://phys.org/news/2020-03-permanent-magnet-cheap-sustainable.html) - Introducing new types of aluminum that are composed of more recycled materials - use more eco-friendly plastics and processes - use of the blind material made from recycled materials - optimize the wieght of the product to reduce resulting fuel consumption
• Reduction in (transport) volume • Reduction in (transport) transportation volume • Reduction in (transport) The main components adding to weight are the fame, roller tube, and a plastic cover. As a plastic casing is integrated, reatively little packaging can be achieved. The frame has an irregular shape, which increases the transportation volume. • The main components adding to weight are the fame, roller tube. • Cover - less weight • Excluding the plastic cover, or optimizing it using FEM analysis including a frame that can be folded into pieces to reduce size • Using a single axle for the roller					, ,		-	
Cours (0.4)				2	Reduction in (transport)	The main components adding to weight are the frame, roller tube, and a plastic cover. As a plastic casing is integrated, reatively little packaging can be achieved. The frame has an irregular shape, which increases the	cover - less	most optimal structure for the frame Excluding the plastic cover, or optimizing it using FEM analysis Including a frame that can be folded into pieces to reduce size
Score (U-4) 3 4 5					Score (0-4)	3	4	5

EcoDesign strategies for product optimization

Life cycle stage 2: In-house production	What problems can arise in the production process in your own company? How many, and what types of production processes are used? (including connections, surface treatments, printing and labelling) How much, and what types of auxiliary materials are needed? How high is the energy consumption? How much waste is generated? How many products don't meet the required quality norms?	Optimization of production techniques	3	Alternative production techniques Fewer production steps Lowiclean energy consumption Less production waste Few/clean production consumables	The processes used are primarily extrusion and injection moulding. Problems that can arise regarding the frame are the need to bend it and the welding process required, which may make the process more costly and labor intensive. Injection moulding is required for many plastic parts, which uses relatively high energy. The current process uses about 18 MJ per product. The plastic cover, roller tube and plastic mount require most energy.	Less plastic due to optimizing the cover and reducing the plastic parts. Simpler construction of the frame allows for fewer production steps No neodymium which uses rare materials and toxic chemicals	Less plastic would reduce the energy use. Some aluminum parts may have a simpler design to use different production techniques and be less energy intensive.
				Score (0-4)	3	4	4
Life cycle stage 3: Distribution	What problems can arise in the distribution of the product to the customer? What kind of transport packaging, bulk packaging, and retail packaging are used (volumes, weights, materials, reusability)? Which means of transport are used? Is transport efficiently organised?	Optimization of distribution system	4	Reduction in weight Reduction in (transport) volume	The product is being transported to the aircraft OEM and assembled on the airplanes. Little packaging is required as no retail distribution is considered. Packaging may be optimized to reduce transport volume.	Foldable design, weight reduction, less volume, more packaging may be required	Improved packaging, green or no packaging, volume and weight reduction, more foldable design
				Score (0-4)	4	4	5
Life cycle stage 4: Utilization	What problems arise when using, operating, servicing and repairing the product? How much, and what type of energy is required, direct or indirect? How much, and what kind of consumables are needed? What is the technical lifetime? How much maintenance and repairs are needed? What and how much auxiliary materials and energy are required for operating, servicing and repair? Can the product be disassembled by a layman? Are those parts often requiring replacement detachable? What is the aesthetic lifetime of the product?	Reduction of impact during use	5	Low energy consumption Clean energy source Few consumables Clean consumables No wastage of energy or consumables	This product does not require direct energy consumption There is high indirect energy consumption due to being used in the aircraft The product may require disinfecting and/or washing May require maintenance or repair Moderate to low maintenance due to antimicrobial properties Cannot be disasssembled by layman The blind material can be detached moderately easily 7+ years aesthetic lifetime due to removable blinds	Reduction in weight, optimized construction for easy removal, of the upper part,	Reduction in weight Optimizing construction for easy removal Blinds fully removable Can be washed in the aircraft instead of the laundry machines Optimization of the use per passenger, using big data to calculate the amount of seats needed
				Score (0-4)	3	4	5
		Optimization of initial lifetime	6	Reliability and durability Easy maintenance and repair Modular product structure Classic Design Strong product-user relation	The product uses a relatively simple mechanism which should be relatively easy to repair Maintenance is easy due to few mechanical parts Design is similar to other current solutions	Hooks will be more relaible than magnets Easier to disassemble and maintain due to simpler construction	Access to the mechanism should be facilitated design can be modular to make the parts easily removable
				Score (0-4)	4	5	5
Life cycle stage 5:Recovery and disposal	What problems arise in the recovery and disposal of the product? How is the product currently disposed of? Are components or materials being reused? What components could be reused? Can the components be reassembled without damage? What materials are recyclable? Are the materials identifiable? Can they be detached quickly? Are any incompatible inks, surface treatments or stickers used? Are any incompatible inks, surface treatments or stickers used? Are any incompatible inks, surface treatments or stickers used? Do problems occur while incinerating non-reusable product parts?	Optimization of end-of-life system.	7	Reuse of product (components) Remanufacturing/refurbishing Recycling of materials Safe incineration	Materials can be generally recycled, but not all The prodcut will be most likely disposed of in en masse by the airline, so a controlled process is possible Can be reassembled without damage to the components The materials can be detached in medium time Antimicrobial surface treatments The materials are identifiable Some of the materials are recyclable	Optimized for faster detachability Simpler, modular design for easier reassembly or reuse	More recyclable materials can be used Remanufacturing for different purposes should be considered
				Score (0-4)	3	3	4
	Sources:						
	http://www.madehow.com/Volume-4/Polyester-Fleece.html						



