

Retrofitting for Heat Resilience

A Dutch case study integrating overheating mitigation into cost-benefit analysis

MSc Thesis in Building Technology

P5 Presentation - 03.07.2025

Tamara Lalyko | 6075797


mentors

Dr. Simona Bianchi, Structural Design & Mechanics, TU Delft


Dr. Alessandra Luna Navarro, Facade & Product Design, TU Delft

third advisor


Diletta Ricci, PhD candidate, Design & Construction Management, TU Delft



Background




Prolonged Period of Heat




Prolonged Period of Heat



Peak above 32°C



Prolonged Period of Heat




Background



Resilience corresponds to mitigating loss before, during, and after heat hazard.

Can you mitigate through renovating?



Can you mitigate through renovating?



1
Status Quo




4
5
passive protection



3
Qualitative benefits


Can you mitigate through renovating?



Can you mitigate through renovating?




Status Quo




active cooling

Operational Cost

Can you mitigate through renovating?



Can you mitigate through renovating?



But is really worth it?

How much will heat hazards drive up cost?

Will the savings pay off my investment?

Does climate uncertainty affect financial feasibility?



The Four Main Challenges



Cost for heat hazard long term




Climate uncertainty in cost-benefit



Outline extreme scenarios in cost-benefit



Informing renovation design




The Purpose of Renovating

Reduced Costs

Higher Profits

Gain Competitive Advantage



Increase Quality of Living

Increase Productivity

Reduce Ecological Impact

Sustainable Development


The Purpose of Renovating

Renovation endorsed by policy


Energy Performance
of Buildings Directive
increase efficiency
-16% by 2030

Renovation Wave
renovate 35 million
buildings by 2030

Heating Transition



Energy retrofitting without overheating?



Overheating Mitigation


Heat wave loss reduction

Robustness for future climate



Where does overheating come in?

What does the renovation process look like?


Renovation Process




Renovation Process




Renovation Process



Renovation Process



Renovation Process



CASE STUDY

Preliminary

Design & Planning

Performance


Cost-Benefit

Decision-making



Case Study

Case study building



District Map




Neighbourhood Map




Gijsingstraat Porch Houses

Case Study

Case study building





Case Study



Case Study



North-East



South-West

Preliminary

Design & Planning

Performance

Cost-Benefit

Decision-making

Preliminary

Stakeholders



Occupant/Resident



Owner/Investor



Private Rental




Owner-occupied

MIX


Preliminary

Renovation interest of stakeholders




Preliminary

Hazard loss connection to renovation interest?



Hazard loss connection to renovation interest?



Preliminary

What are the renovation objectives?

Objective

Criteria

Reduce Energy Cost

Heating Efficiency

Cooling Efficiency

Increase Thermal Comfort

Mitigate Overheating

Minimize Carbon Footprint

Reduce Emissions

What are the renovation objectives?

Objective

Reduce Energy Cost

Increase Thermal Comfort

Minimize Carbon Footprint

Criteria

Heating Efficiency

Cooling Efficiency

Mitigate Overheating

Reduce Emissions

Financial Feasibility
=> cost-recovery

Preliminary



Diagnosis - Heating Efficiency




Apartment Floor	Energy Label	Heating Demand
03 Third Floor	G	312 kWh/m ²
	F	265.26 kWh/m ²
	E	-
	D	-
02 Second Floor	3x D	192.42 kWh/m ²
	C	149,75 kWh/m ²
01 First Floor	C	141.65 kWh/m ²
	D	-
	E	-
00 Ground floor	4x C	173.17 kWh/m ²
Average value 205.33 kWh/m²		

Up-to standard: **50,8 kWh/m²**

Preliminary Diagnosis




Uninsulated Timber
Joist Roof




External Wall Type 230
210 mm brick masonry
20 mm cement plaster



Single-glazing timber framed



Interior Wall Type 90



Interior Floor 258


Preliminary

Heating Retrofitting Solutions


Active
Solutions

Passive
Solutions


Heating Retrofitting Solutions




Heating source/system
- District Heating



Double/ Triple Glazing



Insulation




15

Air-tightening



Preliminary

Overheating Sources



Preliminary





Diagnosis - Sun Exposure



32% window to wall ratio

Overheating Mitigation

Heat Protection




Heat Control

Shading


Heat Removal




12



Thermal Mass





High-Albedo




Green Facade

Renovation Design
Shading




Renovation Design

High-Albedo Facade




17

Intervention Depth




Renovation Design

BASELINE




Air-condition
Gas Boiler
No insulation
No shading
Single glazing

SIMPLE 01 - SHADING




Air-condition
District-Heating
No insulation
Exterior shading

SIMPLE 02 - PAINT




Air-condition
District-Heating
No insulation
No shading
White paint

SIMPLE 04 COMBINATION




Air-condition
District-Heating
No insulation
Exterior shading
White paint

MEDIUM + SHADING





Air-condition
District-Heating
No insulation
Exterior shading
Double glazing

DEEP + SHADING & PAINT



Air-condition
District-Heating
Insulation-stucco wall
Exterior shading
Double glazing
White paint

Baseline




Air-conditioning
Gas Boiler

No insulation
Single glazing
No shading




Renovation Design

Simple Shading




Air-conditioning
District heating

No insulation
Single glazing
Shading




Simple Paint




Air-conditioning
District heating
No insulation
White paint
Single glazing
No shading




Simple Combination



Air-conditioning
District heating
No insulation
White paint
Single glazing
Shading




Medium shading




Air-conditioning
District heating

No insulation
Double glazing
Shading



Deep combination




- Air-conditioning
- District heating
- Exterior insulation
- White paint
- Double glazing
- Shading




Renovation Design

BASELINE




Air-condition
Gas Boiler
No insulation
No shading
Single glazing

SIMPLE 01 - SHADING




Air-condition
District-Heating
No insulation
Exterior shading

SIMPLE 02 - PAINT




Air-condition
District-Heating
No insulation
No shading
White paint

SIMPLE 04 COMBINATION




Air-condition
District-Heating
No insulation
Exterior shading
White paint

MEDIUM + SHADING



Air-condition
District-Heating
No insulation
Exterior shading
Double glazing

DEEP + SHADING & PAINT



Air-condition
District-Heating
Insulation-stucco wall
Exterior shading
Double glazing
White paint

Preliminary

Design & Planning

Performance

Cost-Benefit

Decision-making

Performance Analysis

Quantify how?

Objective

Reduce Energy Cost

Increase Thermal Comfort

Minimize Carbon Footprint

Criteria

Heating Efficiency

Cooling Efficiency

Mitigate Overheating

Reduce Emissions


Key Performance Indicator

Energy Use Intensity

???

Carbon Emission Intensity

Resiliences relates to duration and intensity



Heat Resilience Metrics

Overheated
Hours

Counting Hours
>28°C

Degree Hours

Counting Hours
& Intensity
>28°C

Overheating
Escalation
Factor

Counting Hours
& Intensity
>28°C
divided by
outdoor climate

Performance Analysis

Key Performance Indicator

Energy Use Intensity

Carbon Emission Intensity

Overheated Hours

Degree Hours

Degree Hours

Energy
Simulation

Thermal
Comfort
Simulation

Quantification needs a climate reference

Key Performance Indicator

Energy Use Intensity

Carbon Emission Intensity

Overheated Hours


Degree Hours

Degree Hours

Energy Simulation

Thermal Comfort Simulation

Climate Reference



Performance Analysis



Cost for **heat hazard long term**



Climate uncertainty in cost-benefit




Outline **extreme scenarios** in cost-benefit




Informing renovation design

Variability of thermal performance




*Historical years 1995-2024


How does annual energy demand variate?



Heating demand distribution



Distribution of overheating




What is now considered extreme?

KNMI Heat wave definition

a heat wave is a period
of at least 5 days with a daily maximum
temperature above 25°C
including at least 3 days above 30°C.

Performance Analysis


Past Heat Waves




>5 days >25°C daily maximum temperature
>3 days >30°C daily maximum temperature

Performance Analysis


Past Heat Waves



Summer heat



Summer heat



The impact of heat extremes

1995

2006

2018


2019

2020

2022


Heat Wave Contribution - Energy

- 1995
- 2006
- 2018
- 2019
- 2020
- 2022



Heat Wave Contribution - Overheating

- 1995
- 2006
- 2018
- 2019
- 2020
- 2022



Heat extremes

1995

2006

2018


2019

2020

2022

Extremes on the distribution

- 1995
- 2006
- 2018
- 2019
- 2020
- 2022



The Extreme Range

1995


2006

2018

2019

2020

2022



15% extreme range

The Extreme Range

1995


2006

2018

2019


2020

2022



15% extreme range



Probabilistic Analysis



Let's look at the results!

Cooling Energy




- max extreme 2020
- min extreme
- mean



Baseline

Cooling Energy





- max extreme 2020
- min extreme
- mean



Simple shading






Cooling Energy

- max extreme 2020
- min extreme
- mean



Simple paint







Cooling Energy



Simple combi

Cooling Energy








- max extreme 2020
- min extreme
- mean



Medium shading


Cooling Energy

- max extreme 2020
- min extreme
- mean





Deep combi

Carbon emission intensity - Cooling






Overheating Duration & Intensity







Baseline

Overheating Duration & Intensity








Simple shading

Overheating Duration & Intensity









Simple paint

Overheating Duration & Intensity




Simple combi

Overheating Duration & Intensity









Medium shading

Overheating Duration & Intensity










-34% -59%




Deep combi




Overheating Escalation Factor



Energy use intensity - Heating







Energy use intensity - Heating



Simple Distict Heating

Energy use intensity - Heating








100

Simple Distict Heating

Medium Windows

Energy use intensity - Heating






Simple Distict Heating


Medium Windows

Full Facade


Carbon emission intensity - Heating



Simple Distict Heating



Medium Windows



Full Facade

Performance Analysis

Let's recap!







Objective

Heating

Cooling

Overheating

Carbon



Performance Analysis

Let's recap!

Objective

Heating

Cooling

5.99 kWh/m²

- 6%

- 4%

- 10%

- 7%

- 8%

11.57 kWh/m²

- 3%

- 2%

- 5%

- 4%

- 6%

Overheating

309dh

- 37%







-23%

- 53%

- 24%

- 59%

Carbon









Performance Analysis

Let's recap!

Objective

Heating	160.7 kWh /m ²	- 15%	- 11%	- 11%	- 26%	- 54%
Cooling	5.99 kWh/m ²	- 6%	- 4%	- 10%	- 7%	- 8%
Overheating						
Carbon						









Performance Analysis

Let's recap!

Objective

Heating	160.7 kWh /m ²	- 15%	- 11%	- 11%	- 26%	- 54%
Cooling	5.99 kWh/m ²	- 6%	- 4%	- 10%	- 7%	- 8%
Overheating						
Carbon	37.15 kg/m ²	-48%	-46%	- 47%	- 55%	- 70%









Performance Analysis

Let's recap!

Objective

Heating	160.7 kWh /m ²	- 15%	- 11%	- 11%	- 26%	- 54%
Cooling	5.99 kWh/m ²	- 6%	- 4%	- 10%	- 7%	- 8%
Overheating	309dh	- 37%	-23%	- 53%	- 24%	- 59%
Carbon	37.15 kg/m ²	-48%	-46%	- 47%	- 55%	- 70%



Preliminary

Design & Planning

Performance

Cost-Benefit

Decision-making

Financial Feasibility



Performance



monetary value
of benefits



project cost

Financial Feasibility



3

Performance



10



9

project cost



7

monetary value
of benefits

What are cost and benefits?

project cost

Investment Cost


Revenue/Benefits

Operational Cost


Maintenance Cost

Replacement Cost

Hazard loss affecting project cost



Hazard loss affecting project cost



How to estimate a project's cost?

Investment Cost

Operational Cost

Maintenance Cost

Replacement Cost



Discounted Cashflows



Cashflows over time

Investment Cost

Operational Cost

Maintenance Cost


Replacement Cost




Total Cost

Cost-Benefit Analysis


Indicate Financial Feasibility



Net Present Value




How to assess risk in cost-benefit?



How to assess risk in cost-benefit?

based on climate uncertainty



Risk assessment



Investment Cost

Revenue/Benefits


Operational Cost
**climate uncertainty*

Maintenance Cost

Replacement Cost



Economic Risk - Worst-case




Cost-Benefit Analysis

But what is the worst case?

But what is the worst case?



15% chance for an extreme




6 out of 30 years

But what is the worst case?



15% chance for an extreme

Worst-case Scenario



8 out of 30 years
Exceptionally frequent extremes

Indicators

Total Cost of
Ownership

Risk for total cost
going up

Risk for added cost
worst-case


Net Present
Value

Risk for no profits

Risk for worst-case
outcome


Cost-Benefit Analysis

Analysis Outline








Cost-Benefit Analysis

Analysis Outline



Added project cost for retrofitting



Investment Cost

Heating	8,300.00 EUR	6,000.00 EUR	14,300.00 EUR	8,300.00 EUR	8,300.00 EUR
Cooling	12,149.00 EUR	12,149.00 EUR	12,149.00 EUR	54,849.00 EUR	96,349.00 EUR

Maintenance Cost


items	470.00 EUR	0.00 EUR	470.00 EUR	470.00 EUR	470.00 EUR
cycles	5 years	0 years	5 years	5 years	5 years

Replacement Cost

items	0.00 EUR	6000.00 EUR	6000.00 EUR	0.00 EUR	6000.00 EUR
cycles	0 years	15 years	15 years	0 years	15 years

Total Cost 22,185.00 Eur 22,000.00 Eur 31,035.00 Eur 64,884.00 Eur 110,235.00 Eur


Total Cost



Baseline Total Cost - Cooling

Total cost for the baseline just operational cost






Where are the worst-case results?








Defining a worst-case range



Scenario Total Cost Results




Scenario Total Cost Results




Now What?


What is the added cost for the worst-case?



Comparing the added cost for the worst case




Comparing the added cost for the worst case







What is the potential for cost recovery?






Cooling Energy Savings




NPV Cooling




NPV Cooling



Does the worst-case affect cost recovery?






Does the worst-case affect cost recovery?




Worst-case range for the scenarios?



mean	-9,031 Eur		-9376 Eur		-18,513 Eur	
min worst case	-8,959 Eur	+ 72 Eur	-9,331 Eur	+ 45 Eur	-18,404 Eur	+109 Eur
max worst-case	-8,918 Eur	+113 Eur	-9,309 Eur	+ 67 Eur	-18,344 Eur	+169 Eur




Heating Savings




Heating Only NPV



District Heating








Windows








Full Facade







Heating Only NPV







Heating Only NPV



Heating & Cooling Integration









Heating & Cooling Integration




Cost-Benefit Results

Heating & Cooling Integration




What was the influence of the worst-case?



NPV Results for Simple Shading

What was the influence of the worst-case?




Worst-case for cooling had no significant influence on the outcome.

Evaluation of Results

What did we learn?


Evaluation of Results



Combining passive measures has the highest impact on mitigation.

With larger qualitative than monetary benefit.

Evaluation of Results



However, cost-recovery is not possible with cooling savings.





Evaluation of Results




Integrating Heating & Cooling

Still, heating savings can compensate for cooling measures.

Evaluation of Results




11




Making the deep retrofit the most effective and profitable option!

Evaluation of Results



What did we learn about resilience for the long-term?

Evaluation of Results



Mitigating cost long-term indicates resilience improvement.

Improvement depends on the level of cost or savings.

However, it is hard to pin point with probabilistic simulation.

Reflecting on the framework



8

Cost for heat hazard long term



Climate uncertainty in cost-benefit



Outline extreme scenarios in cost-benefit



Informing renovation design

Reflecting on the framework



Estimate Energy Cost
-> might not align with functional loss



Climate uncertainty in cost-benefit



Outline extreme scenarios in cost-benefit



Informing renovation design

Reflecting on the framework



Estimate Energy Cost
-> might not align with functional loss



Adopt a probabilistic approach
to analyze the full range of outcomes



Outline extreme scenarios in cost-benefit



Informing renovation design

Reflecting on the framework



Estimate Energy Cost
-> might not align with functional loss



Adopt a probabilistic approach
to analyze the full range of outcomes



Define extremes for hazard years
Outline a worst-case scenario



Informing renovation design

Reflecting on use of outcome



Estimate Energy Cost
-> might not align with functional loss



Adopt a probabilistic approach
to analyze the full range of outcomes




Define extreme hazard years
Outline a worst-case scenario



Ensure cost-recovery including risk assessment
Understand long term financial impact of choices
Verifying combined benefits or adverse effects

Reflecting on use of outcome



What can be explored next?

The effect of **global warming** on **heat exposure and impact**.

As well as the **cost for greenhouse gas emissions**.



Resilience corresponds to mitigating loss before, during, and after heat hazard.



*Resilience corresponds to **mitigating risks long term** to **prevent added costs** from functionality loss in case of heat hazard.*

Thank You!



References for icons

- 1 thermometer *Side Project the noun project*
- 2 question mark *YURR.studio, the noun project*
- 3 performance measure *the noun project*
- 4 window *Laymik, the noun project*
- 5 paintbrush *bastian vieri & Trident, the noun project*
- 6 airconditioning *ainul muttaqin, the noun project*
- 7 financial value *nangicon, the noun project*
- 8 challenge *the noun project*
- 9 cost *Fran Couto, the noun project*
- 10 scale *Larea Design the noun project*
- 11 crown *ainul muttaqin, the noun project*
- 12 ventilation *Candy Design, the noun project*
- 13 flame *the noun project*
- 14 grid *Muhammad Syaifuddin, the noun project*
- 15 windproof *faldan, the noun project*
- 16 future city *generated with Dall-E from ChatGPT*
- 17 mykonos *danielaelenatentis-2743349, pixabay*