

P5 presentation
Aditya Parulekar

Mentors:
Paul de Ruyter
Barbara Lubelli

Examiner:
Roel van de Pas

ROBOTIC RESTORATION

Mask of Mayan Sun God

Temple of the Night Sun, 400 AD, Guatemala



- Shark swims every day from East to West through the sky → Sun God

Sculptures of Hindu gods

Temple of Shiva, 7th century AD, Chennai, India



- Human-like features: relationships, jewellery, war

Ornamented ceilings

Huize Nolet, 1804, Schiedam, Netherlands



- Juniper leaves & ships →

Booming world wide export of Gin from Schiedam from the 18th century onwards

Ornamentation



Temple of the Night Sun, 400 AD, Guatemala



Temple of Shiva, 7th century AD, Chennai, India



Huize Nolet, 1804, Schiedam, Netherlands

- Who were our ancestors?
- What did they do?
- What did they believe in?
- What was important to them?



Heritage



Widely used

Stucco



Temple of the Night Sun, 400 AD, Guatemala

Temple of Shiva, 7th century AD, Chennai, India

Huize Nolet, 1804, Schiedam, Netherlands

Binder + Aggregates + Water
Lime, gypsum sand, stone powder

Ornamented stucco ceilings: gypsum



Stucco ceiling, Huize Nolet, NL, 1804



Heritage



Widely used

Damage over time → fragile





Heritage



Widely used

Traditional restoration





Heritage



Widely used

Traditional restoration

On site restoration



Anton van Delden, restoration plasterer,
chairman Neerlandsch Stucgilde

Traditional restoration

(UWV, 2019), (Neerlands Stucgilde, 2017)



How can we restore stucco ornaments in the future?



Widely used



Physically demanding



Complex shapes



Labour intensive



Expensive





Shortage in personnel






Mismatch supply & demand

Digital Fabrication



Digital Fabrication



Heritage



Widely used



Physically demanding



Complex shapes



Labour intensive



Expensive





Shortage in personnel






Mismatch supply & demand

Digital Fabrication



Digital Fabrication



Conservation guidelines

International Charter of Venice:

Article 10: “Where **traditional techniques prove inadequate**, the consolidation of a monument can be achieved by the use of any **modern technique for conservation and construction**, the efficacy of which has been shown by **scientific data and proved by experience.**”



Heritage



Widely used



Physically demanding



Complex shapes



Labour intensive



Expensive



Shortage in personnel



Mismatch supply & demand


Objective

3D printing tools


3D printing material

Integration into
practise

Objective





Objective



3D printing tools

Extruder design

UR5 robot




Multi-axis robot


Extruder




Syringe extruder




Steel funnel + inlet




NEMA 23 stepper motor




Extruder mechanism





Cooling fans




Connector parts




Assembly with 1 type of bolt




Assembled elements






Nozzle variations







Extruder




Robot programming & simulation




Robot & extruder control




Material reservoir




Compressor



Material feeding principle



Complete setup




Corona


A photograph of a cluttered room, likely a home office or lab. In the center, a wooden bed frame is partially assembled. To the right, a desk holds a computer monitor and other electronic equipment. A windowsill in the background is decorated with a colorful parrot figurine, a potted plant, and other small items. The floor is covered with a patterned blanket featuring flamingos and palm trees. A large cardboard box is visible on the left side of the frame.

Mini-LAMA home-lab


Complete setup




Manual printing setup




Extruder
Driver
Arduino Uno
Power supply



Objective



Objective



Gypsum-based 3D printing material

Ceiling substrate: gypsum → Compatibility



Restoration material does not lead to accelerated damage to original material.

Gypsum-based printing mixtures



Binder
Knauf Rotband gypsum

Aggregates
Marble powder

Water

Mixed to form a paste



Optimal ratio for 3D printing




Binder
Knauf Rotband gypsum

Aggregates
Marble powder


Water

Framework for concrete 3D printing



Framework for In-situ gypsum 3D printing

Printability criteria



Printability criteria: gypsum

Pumpability

Extrudability


Buildability

Open Time

Adhesion

Shrinkage,
texture

Measurable parameters



Mixtures tested

Sample	Gypsum type	Water (mL)	Marble powder (fine aggregate) (g)	Gypsum (g)	Gypsum/Marble powder ratio(-)
G0	Molda 3 Normaal	500	0	775	-
G1	Molda 3 Normaal	170	0	300	-
G2	Molda 3 Normaal	195	150	300	02:01
G3	Knauf Rotband	195	0	300	-
G4	Knauf Rotband	295	300	330	01:01
G5	Knauf Rotband	200	100	300	03:01
G6	Knauf Rotband	200	50	300	06:01
G7	Knauf Rotband	130	100	200	02:01
G8	Knauf Rotband	130	80	200	2.5:01
G9	Knauf Rotband	130	50	200	04:01
G10	Knauf Rotband	82	0	100	-



Buildability



Pumpability
extrudability



Open Time




Fresh adhesion



Dry adhesion



Strong – Buildable



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion




Dry adhesion



Resolution

Strong – Buildable → thick



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution

Flowable/extrudable → liquid



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution

Setting

→ slow

→ print longer/larger



Liquid paste



Solid block



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion




Dry adhesion



Resolution

Stick to surface: adhesion in fresh state



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion




Dry adhesion



Resolution

Stick to surface: adhesion in fresh state



Buildability



Pumpability
extrudability



Open Time




Fresh adhesion



Dry adhesion



Resolution



90 degrees



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion





Dry adhesion



Resolution

House decorations





3D printing Upside down



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution



Buildability



Pumpability
extrudability



Open Time




Fresh adhesion



Dry adhesion





Sufficiently strong connection? → Adhesion: Dried



Buildability



Pumpability
extrudability



Open Time




Fresh adhesion



Dry adhesion



Resolution



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion




Resolution



Adhesion: Dried

Average pull-out force (Newtons)



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion




Resolution

Print resolution




(a)

Stucco ornaments: smooth surface



(b)

Contour effect: visible layers



(c)

Thin layers: look smooth



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution



Natural History Museum, Rotterdam

Print resolution



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion




Resolution

Print resolution

Smooth appearance → how thin must layers be?

4500mm





Buildability



Pumpability extrudability



Open Time



Fresh adhesion




Dry adhesion



Resolution

Print resolution



Required resolution: **0,8mm**

4500mm

2650mm = distance to object = y

1750mm

x


x

y



O

O = 1 Arc minute = 0,017 degrees



- 1 mm wide
- 0.5mm high



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion




Resolution


Print resolution

From **regular viewing distance**: restored parts **appear smooth**

→ Harmoniously integrated with the original work

4500mm





Print resolution

Upon **closer** inspection: Restored parts are **clearly distinguishable** → Not falsify the authenticity of the work



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution

Mixtures tested

Sample	Gypsum/marble powder	Gypsum/water	Printable time (min)	Line continuity (1-5)	Nozzle width (mm)	Extrusion width (mm)	Nr. Of layers without collapse	Shrinkage (%)	Cracking (1-5)
G0		1,55/1	4	1	.	.	1	-	1
G1		1,75/1	2	2	.	.	1	-	1
G2	02:01	1,55/1	1	3	.	.	1	-	3
G3		1,55/1	35	4	2,25	2,5	5	-	2
G4	01:01	1,02/1	84	4	4,55		5	-	.
G5	03:01	1,50/1	78	5	2,25	2,5	21	-	1
G6	06:01	1,50/1	85	4	4,55	5,5	11	-	2
G7	02:01	1,50/1	40	4	4,55	4,6	15	-	2
G8	2,5:01	1,50/1	45	4	4,55	4,8	9	-	3
G9	04:01	1,50/1	45	4	4,55	4,5	14	-	2
G10		1,22			1	1		-	(Sieved)



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution

Mixtures tested

Sample	Gypsum/marble powder	Gypsum/water	Printable time (min)	Line continuity (1-5)	Nozzle width (mm)	Extrusion width (mm)	Nr. Of layers without collapse	Shrinkage (%)	Cracking (1-5)
G0		1,55/1	4	1	.	.	1	-	1
G1		1,75/1	2	2	.	.	1	-	1
G2	02:01	1,55/1	1	3	.	.	1	-	3
G3		1,55/1	35	4	2,25	2,5	5	-	2
G4	01:01	1,02/1	84	4	4,55		5	-	.
G5	03:01	1,50/1	78	5	2,25	2,5	21	-	1
G6	06:01	1,50/1	85	4	4,55	5,5	11	-	2
G7	02:01	1,50/1	40	4	4,55	4,6	15	-	2
G8	2,5:01	1,50/1	45	4	4,55	4,8	9	-	3
G9	04:01	1,50/1	45	4	4,55	4,5	14	-	2
G10		1,22			1	1		-	(Sieved)



Buildability



Pumpability
extrudability



Open Time



Fresh adhesion



Dry adhesion



Resolution

G5 material recipe

3

•
•

1

•
•

1.54



•
•



•
•



Binder
Knauf Rotband gypsum

Aggregates
Marble powder

Water

G5 performance

→ Suitable for application



Buildability



21 layers



Pumpability
extrudability



4 bar



Open Time



1.5 hours



Fresh adhesion



360°



Dry adhesion



24kg



Resolution




0.5mm

Material design: manual vs robotic




Gypsum 3D prints by hand




Clay 3D print with robot


Objective



Objective



Extruder + printing material + ?



3D printing tools

Restoration Robot Platform (RRP)

RRP: Requirements



Size



Weight



Mobility



Reach


RRP: Requirements



Building codes



Size



Floor load




Weight



Arbo-laws



Mobility



Ceiling height




Reach

RRP: Requirements




Building codes



Size



Fit through doors



Floor load



Weight



Supportable by old wooden floors




Arbo-laws




Mobility



1 person, stairs



Ceiling height





Reach



Reach 4,5m tall ceilings

Aluminium frame: fits through doors



< 155kg



Stairs





4500mm



Mobility: can climb stairs





Electric stair climbing trolley
Weight: 30kg
Payload: 310kg
Feature: Powered mobility



Mobility





Mobility





Vertical reach: can reach tall ceilings

4500mm



Vertical reach

45000mm





Vertical reach

45000mm



Video camera crane





Vertical reach



40000mm



Video camera crane
Model: Kite-11
Feature: Gyroscopic stabilizing
Weight: 24kg
Payload: 25kg



Crane mounted



Robot selection: criteria



Weight



Payload



Reach




Accuracy



Safety



Protection



nr. Axes



Power

Robot selection: constraints



Weight



<25kg



Payload



>4kg



Reach



+/-750mm



Accuracy



<0,1mm



Safety




Cobot



Protection



IP54



nr. Axes



6 axes



Power



220 V

Robot selection

Name	Manufacturer
UR5	Universal Robotics
UR10	Universal Robotics
HC10	Yasakawa
HCR-5	Hanwha Techwin
HCR-12	Hanwha Techwin
I-5	AUBO
I-7	AUBO
I-10	AUBO
KR1205	Kassow Robots
KR1805	Kassow Robots



I-5



HCR-5



KR1205




UR5





Robot selection: UR5


Name	UR5
Manufacturer	Universal Robotics
Robot weight	20,6
Controller weight	15,2
Total weight	35,8
Payload	5
Reach	850
Repeatability	0,03
Type	Collaborative
Protection	IP154
Nr. Of axis	6
Power supply	220 V





Shelves & top





Stow crane + robot + extruder



Telescopic segments
Reach: 0 – 5,1m





Stow robot controller & compressor





Legs for stability





Stabilizing legs





Stability legs out during 3D printing



Protective doors



Final prototype design: Transportation mode



< 155kg





Stairs





4500mm



Transport to site





Movable by 1 person





Stair-proof





Working area




Tripod supports




Off the shelf components



Objective



Software plug-in: Robotic Restoration



Printer settings input

Quality		Note
Nozzle width (mm)	2,25	
Layer height (mm)	1	Extr. Speed
Initial layer height (mm)	1	
Outer wall line width (mm)		
Inner line width (mm)		
Top line width (mm)		Top of a sub-part
Bottom line width (mm)		Bottom of a sub-part
Infill line width (mm)	1	First layers
Initial layer line width (mm)		First layers
Finish layer line width (mm)		Visible layer

Shell		Note
Wall thickness (mm)	2	>1,3
Wall line count	1	
Top thickness (mm)	2	>1,3
Top layers	1	
Bottom thickness (mm)	2	>1,3
Bottom layers	1	

Infill		Note
Initial fill density (%)	100	Better adhesion
Infill density (%)	30	
Infill pattern...	Zig-zag	
Infill layer height (mm)	2	
Infill line width (mm)	2	

Travel		Note
Avoid collision with print	TRUE	RoboDK setting
Avoid collision with substrate	TRUE	RoboDK setting
Collision avoidance margin (mm)	50	
Z Hop	TRUE	Slicer setting
Z Hop height (mm)	350	Bounding box Z + 50

Speed		Note
Perimeter wall speed (mm/s)		Lower
Infill wall speed (mm/s)		Higher
Initial layer speed (mm/s)		Lower
Final layer speed (mm/s)		Lower
Average printing speed (mm/s)	40	
Extrusion speed (mm/s)		Motor speed (NEMA23)
Compressor pressure (bar)	4	

Printer settings output

Settings output		Note
Printing time (min)	41,66666667	TRUE
Layer count	300	FALSE
Print sections required	14,28571429	
Bounding box X	TRUE	
Bounding box Y	TRUE	
Bounding box Z	TRUE	
Robot stationing coordinates	(x,y,z)	Middle
Length of toolpath (mm)	100000	

CAD file

Print geometry		Note
Volume (m^3)	0,006	
Mass (kg)	6	TRUE
Bounding box X (mm)	500	TRUE
Bounding box Y (mm)	400	TRUE
Bounding box Z (mm)	300	TRUE
XY plane area (m^2)	0,2	

Robot specification

Robot specs		Note
UR5		
Max payload (kg)	5	
Reach X (mm)	750	
Reach Y (mm)	750	
Reach Z (mm)	750	

Nozzles

Name	Width (mm)	Note
N1	3,25	
N2	4,7	
N3	5,5	
N4	2,95	
N5	1,75	
N6	1	

Material specifications

Material specs		Note
Bulk density (kg/m^3)	1000	
Shrinkage (%)		
Buildable layers	21	
Min extrusion width (mm)	1	
Pumping pressure (bar)	4	
Open time (min)	78	
Adhesion fresh (1-5)	5	Excellent
Adhesion dry (kg)	27	TRUE

Crane

Kite-11 specs	Value
Reach (mm)	3320
Weight (kg)	24
Payload (kg)	25
PWR (-)	1,041666667
DOF (-)	3

Nozzles

Nozzle name	N1	N2	N3	N4	N5
Diameter (mm)	1,4	2,3	5,4	7	10
Length (mm)	45	82	36	37	85

Extruder

Printer specs	Value
Motor	NEMA23
Power (A)	4
AC/DC	DC
Torque (kg/cm)	12,85
DEG	1,85


Compressor

Compressor specs	Value
Air output (L/min)	45
Power (PK)	0,75
Max pressure	8
Voltage (V)	230
Capacity (L)	20
Weight (kg)	23

Robot specification

UR5 specs	Value	Note
Brand	Universal Robots	
Type	6 DOF	
Axes	6	
Weight	20	
Payload (kg)	5	
PWR (-)	0,25	
Reach Z (mm)	750	
Repeatability (mm)	0,1	

Software plug-in: Robotic Restoration



Printing Material

Ingredient	Ratio	Absolute (g)	Particle size (µm)
Optium powder	1.5	Value	0.2
Viscor	1	Value	-
Meltre powder (dry)	0.5	Value	0.05
Meltre powder (wetter)	0.5	Value	0.5

Parameter	Value
Bulk density (kg/m³)	1000
Buildtime layers	21
Required pumping pressure (bar)	4
Min. nozzle dia. (mm)	2.7
Open time (min)	70
Adhesion (Newt)	-

Printing geometry

Parameter	Value
Required resolution (mm)	Value
Volume (m³)	Value
Mass (kg)	Value
Dimensions (mm)	Value
Relative position (X, Y, Z)	Value

Context

Parameter	Value
Room length (mm)	VALUE
Room width (mm)	VALUE
Room height (mm)	VALUE
Height constant (kg)	VALUE

Hardware

Parameter	Value
Self weight (kg)	1.1
Nozzle width (mm)	2.7
Nozzle length (mm)	75
TOP offset X (mm)	0
TOP offset Y (mm)	0
TOP offset Z (mm)	200

Parameter	Value
Self weight (kg)	20
Min. payload (kg)	5
Working radius (mm)	750
Print repeatability (mm)	0.05
Push repeatability (mm)	9

Parameter	Value
Self weight (kg)	24
Min. payload (kg)	25
Working radius (mm)	3402
Vertical reach (mm)	3402

Check



Parameter	Value
XY plane area (cm²)	Value
Bounding box X (mm)	Value
Bounding box Y (mm)	Value
Bounding box Z (mm)	Value

Maximum reach (mm): 400

Slicer inputs

Parameter	Value (mm)
Nozzle width	Value
Layer height	Value
Wall line count	2
Outer wall line count	Value
Top layer width	1
Bottom layer width	2
Wall line width	Value
Inner layer width	1
Print layer line width	Value

Parameter	Value
Wall thickness (mm)	Value
Wall line count	Value
Top thickness (mm)	Value
Top layer count	1
Bottom thickness (mm)	2.7
Bottom layer count	1

Parameter	Value
Wall width density (%)	Value
Wall density (%)	Value
Wall pattern	0.5 step
Wall line count	2
Wall line width (mm)	2

Parameter	Value
Printable area speed (mm/s)	Value
TOP layer speed (mm/s)	Value
Wall layer speed (mm/s)	Value
Final layer speed (mm/s)	Value
Printer speed (mm/s)	Value
Printer layer count	Value
Extrusion speed (mm/s)	Value
Compression pressure (bar)	Value

Parameter	Value
Amal calibration	TRUE
Collision prevention	Value
Z step	TRUE
Z step height (mm)	Value

Parameter	Value
Robot calibration point	Coordinates (X, Y, Z)
Bounding box volume check?	Yes / No
Height within reach?	Yes / No

Robot robot by X mm

Slicer output

Generate milling toolpath

G-code milling

Generate printing toolpath

G-code printing

Generate driving path

Parameter	Value
Average printing speed (mm/s)	Value
Printing time (min)	Value
Layer count	Value
Number of print stages	Value
Length of toolpath (mm)	Value
Volume of material required (g)	Value
Water required (ml)	Value
Meltre powder required (g)	Value
Total mass print (g)	Value
Estimated drying time (min)	Value

Knauf Rotband

Mesh

3D scan of room

URS


Kite-11

Legend




Essential
Important
Optional

Objective



A white, empty room with a decorative ceiling medallion and crown molding. The room is brightly lit, and the walls and floor are a uniform white color. The ceiling features a central, ornate medallion with a floral or scrollwork design. The walls are adorned with multiple layers of crown molding, creating a classic architectural look. The overall atmosphere is clean, minimalist, and elegant.

Proposed New Restoration Method




Inspect damaged area




Place reference markers




High resolution 3D scan ornament




Low resolution 3D scan room




Point cloud from 3D scan




Convert point cloud to mesh





Identify repeating elements




Interpolate geometry




Model using historic documentation



Modelled missing geometry



Convert CAD geometry to STL format



Export STL-file to 3D printing software



RhinoCeros
3D modelling software



Ultimaker Cura slicer
3D printing software



UR5 robot



Generic ABS



Gypsum print 1 - Fine - 0.5mm




20%



Off



Off





UR5 robot



Generic PLA



Gypsum print 1 - Fine - 0.3mm



20%



Off



Off



Preset printers

Anycubic Chiron


Creality CR-10S

UR5 robot

Ultimaker S5


Add printer

Manage printers



UR5 robot < Generic PLA < Gypsum print 1 - Fine - 0.3mm 20% Off Off

- 🔄
- 📏
- 📐
- 🔍
- 🔧
- 📊
- 📄



Object list
Object 1

Untitled
683.8 x 686.4 x 143.4 mm




Slice

UR5 robot < RRP G5 Mixture Gypsum print 1 - Fine - 0.5mm 20% Off Off

Custom
Material

- G5 Mixture
- Generic
- Custom
- RRP
- Structur3d
- Ultimaker
- Manage Materials... Ctrl+K

Wet mixture • G5 Mixture



Object list
Object 1


Untitled
683.8 x 686.4 x 143.4 mm



Slice

UR5 robot < RRP G5 Mixture

Gypsum print 1 - Fine - 0.5mm 20% Off Off



Object list
Object 1

Untitled
683.8 x 686.4 x 143.4 mm



Print settings


Profile: Gypsum print 1 - Fine - 0.3mm

Search settings

- Quality**
 - Layer Height: 0.5 mm
 - Initial Layer Height: 0.5 mm
 - Line Width: 1 mm
 - Wall Line Width: 1 mm
 - Outer Wall Line Width: 1 mm
 - Inner Wall(s) Line Width: 1 mm
- Shell
- Infill
- Material
- Speed
- Travel
- Cooling
- Support
- Build Plate Adhesion
- Dual Extrusion

< Recommended

UR5 robot < RRP G5 Mixture < Gypsum print 1 - Fine - 0.5mm 20% Off Off




Object list
Object 1
Untitled
683.8 x 686.4 x 143.4 mm

Slicing...
[Progress bar]
Cancel






View type Layer view < Color scheme Material Color   Gypsum print 1 - Fine - 0.5mm  20%  Off  Off 



- 
- 
- 
- 
- 
- 

284


 **14 hours 38 minutes** 

 4999g · 783.59m · € 2.25

[Save to File](#)



View type Layer view < Color scheme Material Color Gypsum print 1 - Fine - 0.5mm 20% Off Off



Object list
Object 1
Untitled
683.8 x 686.4 x 143.4 mm

14 hours 38 minutes
 5000g · 783.73m · € 2.25
[Save to File](#)



Export 3D printing instructions (G-code) to Robot programming software



Ultimaker Cura slicer
3D printing software



RoboDK
Robot programming &
simulation software




▶ Robtic Restoration Setup






- ▼ Robtic Restoration Setup
 - Room dimensions
 - ▶ UR5 Base
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament






- ▼ Robtic Restoration Setup
 - Room dimensions
 - ▶ UR5 Base
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament





- ▼ Robtic Restoration Setup
 - Room dimensions
 - ▼ UR5 Base
 - ▼ UR5
 - Extruder
 - Reference Rhino
 - Ornament 1
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament











Online Library



Crane library

Brand ▾ ▶Type ▾ ▶Axes ▾ ▶Payload ▾ ▶Reach ▾ ▶Weight ▾

Reset filter

					
Brand AUBO	Brand HCR	Brand HCR	Brand Han's	Brand Han's	Brand Jaka
Type 6 DOF	Type 6 DOF	Type 6 DOF	Type 6 DOF	Type 6 DOF	Type 6 DOF
Axes 6	Axes 6	Axes 6	Axes 6	Axes 6	Axes 6
Payload 3.0 kg	Payload 3.0 kg	Payload 5 kg	Payload 3.0 kg	Payload 3.0 kg	Payload 3.0 kg
Reach 530 mm	Reach 630 mm	Reach 915 mm	Reach 590 mm	Reach 590 mm	Reach 587 mm
Repeat. 0.050 mm	Repeat. 0.100 mm	Repeat. 0.100 mm	Repeat. 0.100 mm	Repeat. 0.100 mm	Repeat. 0.030 mm
Weight 15 kg	Weight 13 kg	Weight 20 kg	Weight 15 kg	Weight 15 kg	Weight 14 kg
Download	Download	Download	Download	Download	Download

- Robtic Restoration Setup
 - Room dimensions
 - UR5 Base
 - UR5
 - Extruder
 - Reference Rhino
 - Ornament 1
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament






Online Library

<p>Repeat. 0.050 mm Weight 15 kg</p> <p>Download</p>	<p>Repeat. 0.020 mm Weight 15 kg</p> <p>Download</p>	<p>Repeat. 0.100 mm Weight 13 kg</p> <p>Download</p>	<p>Repeat. 0.100 mm Weight 20 kg</p> <p>Download</p>	<p>Repeat. 0.100 mm Weight 15 kg</p> <p>Download</p>	<p>Repeat. 0.100 mm Weight 15 kg</p> <p>Download</p>
<p>Jaka Zu3</p>  <p>Brand Jaka Type 6 DOF Axes 6 Payload 3.0 kg Reach 587 mm Repeat. 0.030 mm Weight 14 kg</p> <p>Download</p>	<p>Kawasaki FS03N</p>  <p>Brand Kawasaki Type 6 DOF Axes 6 Payload 3.0 kg Reach 620 mm Repeat. 0.050 mm Weight 20 kg</p> <p>Download</p>	<p>Kawasaki RS03N</p>  <p>Brand Kawasaki Type 6 DOF Axes 6 Payload 3.0 kg Reach 620 mm Repeat. 0.020 mm Weight 20 kg</p> <p>Download</p>	<p>Mitsubishi RV-2AJ</p>  <p>Brand Mitsubishi Type 6 DOF Axes 6 Payload 2.0 kg Reach 410 mm Repeat. 0.020 mm Weight 17 kg</p> <p>Download</p>	<p>Toshiba TV800</p>  <p>Brand other Type 6 DOF Axes 6 Payload 3.0 kg Reach 892 mm Repeat. 0.020 mm Weight 20 kg</p> <p>Download</p>	<p>UR3</p>  <p>Brand Universal Robots Type 6 DOF Axes 6 Payload 3.0 kg Reach 500 mm Repeat. 0.100 mm Weight 11 kg</p> <p>Download</p>
<p>UR3e</p>  <p>Brand Universal Robots Type 6 DOF Axes 6 Payload 3.0 kg Reach 500 mm Repeat. 0.030 mm Weight 11 kg</p> <p>Download</p>	<p>UR5</p>  <p>Brand Universal Robots Type 6 DOF Axes 6 Payload 5 kg Reach 850 mm Repeat. 0.100 mm Weight 18 kg</p> <p>Download</p>	<p>UR5e</p>  <p>Brand Universal Robots Type 6 DOF Axes 6 Payload 5 kg Reach 850 mm Repeat. 0.030 mm Weight 18 kg</p> <p>Download</p>			


Robtic Restoration Setup

- Room dimensions
- UR5 Base
 - UR5
 - Extruder
 - Reference Rhino
 - Ornament 1
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament








- ▼ Robtic Restoration Setup
 - Room dimensions
 - ▼ UR5 Base
 - ▼ UR5
 - Extruder
 - Reference Rhino
 - Ornament 1
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament





- ▼ Robtic Restoration Setup
 - Room dimensions
 - ▼ UR5 Base
 - ▼ UR5
 - Extruder
 - Reference Rhino
 - Ornament 1
 - Frame 2
 - Rest of ornament
 - Caddy RRP
 - Kite-11 crane
 - Reference markers
 - Ornament 1 Settings
 - Ornament





Save robot instructions (Toolpath)




RoboDK
Robot programming &
simulation software




Restoration site


Bring Restoration Robot to site




Stabilize platform




Mount crane on to chassis




Adjust crane height with handle




Adjust crane height with handle




Calibrate robot with markers




Calibrate robot with markers




Calibrate robot with markers




Calibrate robot with markers



Calibrate robot with markers



Calibrate robot with markers




Make (G5) printing mixture



Fill reservoir with mixture




Ready to print → Run script



Robot 3D prints geometry





Robot restores ornament by 3D printing




Inspect work




Retract crane




Store robot




Retract legs




Remove platform



Entertain yourself for 48+ hours





Final inspection



Remove reference markers




Remove reference markers




Result



Digital Fabrication method



Human knowledge




Machine labour

- Restoration
- Construction

The Great Pyramid of Giza

Egypt, 2580 – 2560 BC.

- Size and shape
- Pinnacle of construction in 2580 BC



The Great Pyramid of Giza


Egypt, 2580 – 2560 BC.



Construction method is unsustainable for workers

Al Wakrah football stadium

Qatar, 2020



- Air conditioned stadium in the dessert
- Pinnacle of construction in 2020

Al Wakrah stadium

Qatar, 2020

Migrant workers suffer from coronavirus-safe conditions in Qatar

Pressure to complete the construction project for the 2022 World Cup exacerbates the situation

Atalayar



AFP/IMARWAN NAAMANI - Foreign workers at the construction site of Al-Wakrah Football Stadium, one of the stadiums for the 2022 World Cup in Qatar

www.atalayar.com

Het morele besef van de voetbalwereld

Voetbalclubs zijn opecht verantwoordelijk over racisme, maar gaan wel naar Qatar, waar moderne slaven stadions bouwen.

Maarten de Gruyter 3 dec 2019 om 07:00 uur



Arbeiders werken aan het Al-Wakrah-stadion in een buitwijk van de Qatarrese hoofdstad Doha. Foto: ANP

www.hetgoedeleven.nl

Qatar covered up the death of 1200 workers

Rights groups accuse body of whitewashing Qatar's image and politicising rights issues

Published: April 14, 2019 15:38
Gulf News



A construction site in Doha. Rights groups say more than 1,200 migrant workers have died building World Cup facilities.

Image Credit: AFP

www.gulfnews.com

We are unable to **construct** buildings sustainably and responsibly for our workers?

How we build


2580 BC

2020 AD

Future



Great Pyramid of Giza, 2580 BC. www.com



Al Wakrah stadium 2020, www.asiatimes.com



Human labour




Human labour +
Machine labour




Human knowledge
+ Machine labour

Robotic Restoration: Human knowledge + machine labour



Preserve our Heritage for future generations





P5 presentation
Aditya Parulekar

Mentors:
Paul de Ruiters
Barbara Lubelli

Examiner:
Roel van de Pas

ROBOTIC RESTORATION

APPENDIX

Research question

*“To what extent can a **Digital Fabrication method** and **3D printable gypsum-based mixtures** be developed for restoration of stucco ornaments by means of in-situ additive manufacturing?”*