



Delft University of Technology

Development of two-beam femtosecond/picosecond CARS for high-fidelity thermometry in flames

Bohlin, Alexis

Publication date

2018

Document Version

Final published version

Citation (APA)

Bohlin, A. (2018). *Development of two-beam femtosecond/picosecond CARS for high-fidelity thermometry in flames*. Abstract from 32nd International Congress on High-Speed Imaging and Photonics, Enschede, Netherlands.

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

This work is downloaded from Delft University of Technology.

For technical reasons the number of authors shown on this cover page is limited to a maximum of 10.

Development of two-beam femtosecond/picosecond CARS for high-fidelity thermometry in flames

Alexis Bohlin

Faculty of Aerospace Engineering, Delft University of Technology, Delft, The Netherlands

E-mail: g.a.bohlin@tudelft.nl

Abstract

We develop simultaneous ultrafast CARS thermometry and species detection as a unique tool to investigate combustion modes with reduced emissions of NO_x, particulates, CO and unburned hydrocarbons. Coherent anti-Stokes Raman spectroscopy (CARS) has been developed over the last 4 decades for various gas-phase-, plasma-, flame- and combustion applications and is referred to as the “gold standard” for nonintrusive spectroscopic measurements in harsh environments. It is the combination of excellent chemical selectiveness, i.e. the ability in targeting distinct quantum states of individual molecular species, and the coherent properties of the generated signal beam, which makes this technique very powerful. For most of the gas-phase applications, with rapidly changing events ranging from μ s to ms, there is a constraint in performing instantaneous measurements and is beneficially fulfilled by the inherent property of the Raman process. It is the time-duration of the probe pulse which ultimately limits the temporal resolution, where today existing techniques, implemented with ultrafast laser systems operate around or even below collision lifetimes. Still, while a reacting flow is fully characterized in three-dimensional space, a limitation of CARS has been its main applicability as a point-wise measurement technique. Establishing ultrafast CARS for single-shot imaging, however, requires designing robust schemes for both the signal generation and the signal detection. Because the physical scalars quantifying an event in a reacting flow exist only for an instantaneous moment of time, laser-scanning or sample-rastering procedures may not be employed. Here we discuss two-beam femtosecond/picosecond CARS relevant for 0D, 1D, and 2D temperature measurements in flames, and we show that single-shot quantitative measurements for major species in combustion are within reach.

Keywords: Atomic and molecular physics; Nonlinear optics; Ultrafast optics; Laser diagnostics

