Delft University of Technology

Marchenko-based target replacement in laterally varying media

van IJsseldijk, John; Wapenaar, Kees

DOI

[10.1002/essoar.10501883.1](https://doi.org/10.1002/essoar.10501883.1)

Publication date

2019

Document Version

Final published version

Citation (APA)

van IJsseldijk, J., & Wapenaar, K. (2019). *Marchenko-based target replacement in laterally varying media*. Poster session presented at AGU Fall Meeting 2019, San Francisco, United States.
<https://doi.org/10.1002/essoar.10501883.1>

Important note

To cite this publication, please use the final published version (if applicable).
Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

Marchenko-based target replacement in laterally varying media: A geophysical way of replacing layers in a pre-baked cake

Johno van IJsseldijk^{1@} Kees Wapenaar¹

¹Delft University of Technology, [@]J.E.vanIJsseldijk@tudelft.nl

1. INTRODUCTION

Seismic time-lapse studies are generally concerned with variations in a specific target zone, situated inside an otherwise static medium. Ideally only the response of the target zone is remodeled, which is then inserted into the stationary response of the surrounding medium (Figure 1). Wapenaar and Staring (2018) show how to do this in layered media.

FIGURE 1 The principle of target replacement: the over- and underburden responses (a and c) are extracted from the original reflection response (left). Next, the response of the new target zone (b) is inserted (right).

2. TARGET EXTRACTION

The first step is to extract the reflection and transmission responses from units a and c using the original reflection response and Marchenko redatuming. One datum right below unit a and one above unit c allows us to retrieve three reflection responses (R_A^U , shown Figure 2, R_A^D and R_C^U) as well as two transmission responses (T_A^- and T_A^+).

FIGURE 2 The original reflection response (R_C^U) modeled with finite differences (left), from this the reflection response, including multiples, of unit A (R_A^U) is extracted (right). The velocities are shown in the left of Figure 1.

3. TARGET INSERTION

FIGURE 3 Target insertion: each row is a new equation with a desired response (blue), knowns (black) and unknowns (red). Altered responses are indicated with a bar. The asterisks denote multidimensional convolution.

4. RESULTS

FIGURE 4 The new reflection response ($\bar{R}_C^U$) retrieved with Marchenko-based target replacement (left) and reference modeled with finite differences (right). The velocities are shown in Figure 1.

Figure 1 shows the 2D model that is considered for the 2D target replacement. The middle layer had a velocity of 2600 m/s that was decreased to 2100 m/s in the new target zone, similarly the density of this layer is changed from 3000 kg/m³ to 2500 kg/m³. Next, the stationary responses are extracted from the old reflection response (shown on the left of in Figure 2) using Marchenko redatuming. Note that this method includes all the internal multiples in the retrieved responses. Then, the reflection and transmission response of the new target zone are modeled ($\bar{R}_b^U$ and $\bar{T}_b^+$). Finally, the new target zone is inserted into the medium as shown in Figure 3. The final results of this replacement is shown on the left in Figure 4, the right side shows the reference that was obtained by remodeling the entire medium. Since some of steep arrivals get lost in the target replacement due to the limited aperture, a weak fk-filter was applied for a better

comparison. Most of the events are accurately recovered by the scheme. However, near the edges the scheme is a little less accurate. Moreover, there are some differences in the retrieved amplitudes. In conclusion, we found that Marchenko-based target replacement can be used to accurately find the full response of the medium, while only the changing target zone has to be remodeled. This allows for a more effective modeling for time-lapse monitoring.

ACKNOWLEDGEMENTS

The authors thank Jan Thorbecke and Myrna Staring for help with the numerical examples and insightful discussions. This research was funded by the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement No: 742703).

REFERENCES

Wapenaar, K. and Staring, M. (2018). Marchenko-Based Target Replacement, Accounting for All Orders of Multiple Reflections. *Journal of Geophysical Research: Solid Earth*, 123(6):4942–4964.